

Product Datasheet model uvex super OTG 9169 175

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

1. Product Characteristics

- classic overspecs for prescription spectacle wearers with a flat lens for a wide field of vision, designed for maximum wearer acceptance
- side arms with soft-grip temple ends provide a comfortable, secure fit without pressure
- nose bridge designed for all-day comfort
- perfect colour recognition according to EN 172
- robust polycarbonate lens with uvex's proven infradur coating technology – permanent anti-fog and scratch-resistant lens
- multi-protection filter with pleasant grey-blue tint
 - Infrared protection according to EN 171 – excellent IR protection from 780-3,000 nm
 - Welding protection according to EN 169
 - UV protection according to EN 170 as well as uvex UV400 – 100% protection against dangerous UV radiation up to 400 nm
- detectable

2. Technical Details Body

Front piece

Material	PC+PBT
Colour	black

Rivet

Material	brass, nickel-plated
----------	----------------------

Temple

Material	PC+PBT+TPE
Colour	black, red

Marking

Manufacturer 's ID code	W
Applicable EN norm	166
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperature	T
Conformity symbol	CE

3. Technical Details Lens

Material	PC
Thickness	2.1 mm at PD
Coating	uvex infradur plus
Colour	grey / infrared protection level4-5
UV protection	UV 400





Marking according to EN

Filter	4C-5 (EN 171) 2C-5 (EN 170)
Manufacturer 's ID code	W
Optical class	1
Impact resistance	F (45 m/s)
Resistance to high speed particles at extremes of temperature	T
Scratch resistance	K
Antifog	N

Conformity symbol	CE
Factory symbol	

4. Logistical Information

Product


Weight	39g		
Dimensions (L x W x B) in approx. mm			
	161 x 157 x 58		
	Packing unit 1	Packing unit 2	Packing unit 3
EAN Code	4031101982236		
Quantity in pcs.	1	8	128
Dimensions (L x W x H) in approx. mm			
	76 x 160 x 58	185 x 290 x 97	600 x 400 x 400
Net weight in approx. g	39	312	4,992
Gross weight in approx. g	53	530	9,380
Country of Origin	Germany		

5. Miscellaneous

Standards

EN 166 + EN 171 + EN 169 + EN 170

Transmission curve



PPE Category

Category II