

Page 1 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 10.07.2015 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40®BIKE® Dry Lube

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**WD-40®BIKE® Dry Lube**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified uses of the substance or mixture:**

Lubricant

**Uses advised against:**

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

WD-40 Company Limited, PO Box 440, Kiln Farm, Milton Keynes, MK11 3LF, United Kingdom  
 Phone:+44 (0) 1908 555400, Fax:+44 (0) 1908 266900  
 www.wd40.co.uk

(IRL)

P.R. Rielly Limited KarKraft House, Kilbarrack Industrial Estate, Kilbarrack, Dublin 5, Ireland  
 Phone:01-832 0006, Fax:01-832 0016  
 web@team.ie

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

**Emergency information services / official advisory body:**

(IRL)

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:  
 +353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)  
 +353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

**Telephone number of the company in case of emergencies:**

+49 (0) 700 / 24 112 112 (WDC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification according to Regulation (EC) 1272/2008 (CLP)**

Hazard class	Hazard category	Hazard statement
Flam. Liq.	2	H225-Highly flammable liquid and vapour.
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.

#### 2.2 Label elements

**Labeling according to Regulation (EC) 1272/2008 (CLP)**



Danger

Page 2 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 10.07.2015 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40@BIKE® Dry Lube

H225-Highly flammable liquid and vapour. H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.  
 P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261-Avoid breathing vapours or spray. P271-Use only outdoors or in a well-ventilated area. P280-Wear eye protection.  
 P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312-Call a POISON CENTRE / doctor if you feel unwell.  
 P403+P233-Store in a well-ventilated place. Keep container tightly closed. P405-Store locked up.  
 P501-Dispose of contents / container safely.

Propan-2-ol

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substance

n.a.

### 3.2 Mixture

Propan-2-ol	
Registration number (REACH)	01-2119457558-25-XXXX
Index	603-117-00-0
EINECS, ELINCS, NLP	200-661-7
CAS	67-63-0
content %	50-70
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Amine phosphate	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	279-632-6
CAS	80939-62-4
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1/3.2 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

Never pour anything into the mouth of an unconscious person!

#### Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

#### Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

#### Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

### **Ingestion**

Rinse the mouth thoroughly with water.

Give copious water to drink - consult doctor immediately.

### **4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

Effects/damages the central nervous system

Coordination disorders

Unconsciousness

With long-term contact:

Product removes fat.

Drying of the skin.

Dermatitis (skin inflammation)

### **4.3 Indication of any immediate medical attention and special treatment needed**

n.c.

## **SECTION 5: Firefighting measures**

### **5.1 Extinguishing media**

#### **Suitable extinguishing media**

Water jet spray / alcohol resistant foam / CO2 / dry extinguisher

#### **Unsuitable extinguishing media**

High volume water jet

### **5.2 Special hazards arising from the substance or mixture**

In case of fire the following can develop:

Oxides of carbon

Oxides of phosphorus

Oxides of nitrogen

Toxic gases

Explosive vapour/air mixture

### **5.3 Advice for firefighters**

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

## **SECTION 6: Accidental release measures**

### **6.1 Personal precautions, protective equipment and emergency procedures**

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

### **6.2 Environmental precautions**

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

### **6.3 Methods and material for containment and cleaning up**

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

### **6.4 Reference to other sections**

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## **SECTION 7: Handling and storage**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 10.07.2015 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40@BIKE® Dry Lube

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

**7.1 Precautions for safe handling**

**7.1.1 General recommendations**

- Ensure good ventilation.
- Avoid inhalation of the vapours.
- Keep away from sources of ignition - Do not smoke.
- Take measures against electrostatic charging, if appropriate.
- Avoid contact with eyes or skin.
- Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
- Observe directions on label and instructions for use.
- Use working methods according to operating instructions.

**7.1.2 Notes on general hygiene measures at the workplace**

- General hygiene measures for the handling of chemicals are applicable.
- Wash hands before breaks and at end of work.
- Keep away from food, drink and animal feedingstuffs.
- Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

**7.2 Conditions for safe storage, including any incompatibilities**

- Keep out of access to unauthorised individuals.
- Not to be stored in gangways or stair wells.
- Store product closed and only in original packing.
- Do not store with flammable or self-igniting materials.
- Observe special storage conditions.
- Protect from direct sunlight and warming.
- Store in a well-ventilated place.
- Store cool.

**7.3 Specific end use(s)**

No information available at present.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control parameters**

GB	Chemical Name	Propan-2-ol	Content %:50-70
	WEL-TWA: 400 ppm (999 mg/m3)	WEL-STEL: 500 ppm (1250 mg/m3)	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-122 SA(C) (549 277)</li> <li>- Compur - KITA-150 U (550 382)</li> <li>- Draeger - Alcohol 25/a i-Propanol (81 01 631)</li> <li>- DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004)</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>	
	BMGV: ---	Other information: ---	

IRL	Chemical Name	Propan-2-ol	Content %:50-70
	OELV-8h: 200 ppm	OELV-15min: 400 ppm	---
	Monitoring procedures:	<ul style="list-style-type: none"> <li>- Compur - KITA-122 SA(C) (549 277)</li> <li>- Compur - KITA-150 U (550 382)</li> <li>- Draeger - Alcohol 25/a i-Propanol (81 01 631)</li> <li>- DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 1998, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004)</li> <li>- Draeger - Alcohol 100/a (CH 29 701)</li> </ul>	
	BLV: 40 mg/l (acetone, U, d) (ACGIH-BEI)	Other information: Sk	

GB	Chemical Name	Silica, amorphous	Content %:
	WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust)	WEL-STEL: ---	---
	Monitoring procedures:	---	
	BMGV: ---	Other information: ---	

IRL	Chemical Name	Silica, amorphous	Content %:
	OELV-8h: 2,4 mg/m3 (respirable dust), 6 mg/m3 (total inhalable dust) (Silica, amorphous)	OELV-15min: ---	---
	Monitoring procedures:	---	

BLV: ---

Other information: ---

⊗ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
\*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

⊗ OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction. | BLV = Biological limit value | Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

Propan-2-ol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	140,9	mg/l	
	Environment - marine		PNEC	140,9	mg/l	
	Environment - sediment, freshwater		PNEC	552	mg/kg	
	Environment - sediment, marine		PNEC	552	mg/kg	
	Environment - soil		PNEC	28	mg/kg	
	Environment - sewage treatment plant		PNEC	2251	mg/l	
Consumer	Human - dermal	Long term	DNEL	319	mg/kg	(1 d)
Consumer	Human - inhalation	Long term	DNEL	89	mg/m3	
Consumer	Human - oral	Long term	DNEL	26	mg/kg	(1 d)
Workers / employees	Human - dermal	Long term	DNEL	888	mg/kg	(1 d)
Workers / employees	Human - inhalation	Long term	DNEL	500	mg/m3	

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Safety gloves made of butyl (EN 374)

Protective Neoprene® / polychloroprene gloves (EN 374).

Protective nitrile gloves (EN 374)

Minimum layer thickness in mm:

0,5

Permeation time (penetration time) in minutes:

>= 480

The breakthrough times determined in accordance with EN 374 Part 3 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	12 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	Not determined
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	Not determined
Explosive properties:	Product is not explosive.
Oxidising properties:	No

### 9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

## SECTION 10: Stability and reactivity

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 10.07.2015 / 0002

Valid from: 07.03.2017

PDF print date: 09.03.2017

WD-40®BIKE® Dry Lube

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

Electrostatic charge

### 10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

WD-40®BIKE® Dry Lube						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Propan-2-ol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	4570-5840	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	13900	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	30	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing

Page 8 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 10.07.2015 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40@BIKE® Dry Lube

Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Carcinogenicity:						Negative
Reproductive toxicity:						Negative
Specific target organ toxicity - repeated exposure (STOT-RE):						Target organ(s): liver
Symptoms:						breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	

Amine phosphate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Irritant
Respiratory or skin sensitisation:				Guinea pig		Not sensitising

## SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

WD-40@BIKE® Dry Lube							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Propan-2-ol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	1400	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	2285	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus		

12.2. Persistence and degradability:		21d	95	%		OECD 301 E (Ready Biodegradability - Modified OECD Screening Test)	
12.2. Persistence and degradability:			99,9	%		OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units)	
12.3. Bioaccumulative potential:	Log Pow		0,05			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.4. Mobility in soil:	Koc		1,1				expert judgement
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		>1000	mg/l	activated sludge		
Other information:	ThOD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	COD		96	%			References
Other information:	COD		2,4	g/g			
Other information:	BOD5		53	%			
Other information:	BOD		1171	mg/g			

**Amine phosphate**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	5,5	mg/l	Brachydanio rerio	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	1,2	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>10	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:						OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable
12.2. Persistence and degradability:							Not readily biodegradable
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.2. Persistence and degradability:							Not readily biodegradable
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	

**SECTION 13: Disposal considerations**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 07.03.2017 / 0003

Replacing version dated / version: 10.07.2015 / 0002

Valid from: 07.03.2017

PDF print date: 09.03.2017

WD-40®BIKE® Dry Lube

### 13.1 Waste treatment methods

#### For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 06 99 wastes not otherwise specified

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

#### For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

Do not perforate, cut up or weld uncleaned container.

Residues may present a risk of explosion.

15 01 10 packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

### General statements

14.1. UN number: 1993

#### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL) (SPECIAL PROVISION 640D)

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

Classification code:

F1

LQ:

1 L

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

D/E

#### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

FLAMMABLE LIQUID, N.O.S. (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

EmS:

F-E, S-E

Marine Pollutant:

n.a

14.5. Environmental hazards:

Not applicable

#### Transport by air (IATA)

14.2. UN proper shipping name:

Flammable liquid, n.o.s. (ISOPROPYL ALCOHOL)

14.3. Transport hazard class(es):

3



14.4. Packing group:

II

14.5. Environmental hazards:

Not applicable

#### 14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Page 11 of 13  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 07.03.2017 / 0003  
 Replacing version dated / version: 10.07.2015 / 0002  
 Valid from: 07.03.2017  
 PDF print date: 09.03.2017  
 WD-40@BIKE® Dry Lube

Directive 2010/75/EU (VOC): ~ 60 %

Observe youth employment law (German regulation).

## 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

F00265  
 Revised sections: 2,16  
 These details refer to the product as it is delivered.  
 Employee instruction/training in handling hazardous materials is required.  
 Employee training in handling dangerous goods is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 2, H225	Classification based on test data.
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid  
 Eye Irrit. — Eye irritation  
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
 Skin Irrit. — Skin irritation  
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

### Any abbreviations and acronyms used in this document:

AC Article Categories  
 acc., acc. to according, according to  
 ACGIH American Conference of Governmental Industrial Hygienists  
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOEL Acceptable Operator Exposure Level  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)  
 BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)  
 BMGV Biological monitoring guidance value (EH40, UK)  
 BOD Biochemical oxygen demand  
 BSEF Bromine Science and Environmental Forum  
 bw body weight  
 CAS Chemical Abstracts Service  
 CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids  
 CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques  
 CIPAC Collaborative International Pesticides Analytical Council

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

COD Chemical oxygen demand

CTFA Cosmetic, Toiletry, and Fragrance Association

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

DT50 Dwell Time - 50% reduction of start concentration

DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEA European Economic Area

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ERC Environmental Release Categories

ES Exposure scenario

etc. et cetera

EU European Union

EWG European Waste Catalogue

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

HET-CAM Hen's Egg Test - Chorionallantoic Membrane

HGWP Halocarbon Global Warming Potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

IBC Intermediate Bulk Container

IBC (Code) International Bulk Chemical (Code)

IC Inhibitory concentration

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LC lethal concentration

LC50 lethal concentration 50 percent kill

LCLo lowest published lethal concentration

LD Lethal Dose of a chemical

LD50 Lethal Dose, 50% kill

LDLo Lethal Dose Low

LOAEL Lowest Observed Adverse Effect Level

LOEC Lowest Observed Effect Concentration

LOEL Lowest Observed Effect Level

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicable

n.av. not available

n.c. not checked

n.d.a. no data available

NIOSH National Institute of Occupational Safety and Health (United States of America)

NOAEC No Observed Adverse Effective Concentration

NOAEL No Observed Adverse Effect Level

NOEC No Observed Effect Concentration

NOEL No Observed Effect Level

ODP Ozone Depletion Potential

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.