

## Features

- Euro Plug Top
- DOE Level VI Efficiency
- 2.1 C+ve Connector
- Compact Design
- 24 Watts

## RS PRO AC/DC Adapters

RS Stock No.: **0303994**



RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

# AC/DC Adapters

## Product Description

This compact 12vdc 24watt Euro 2 pin Plug Top power supply is suitable many applications with a maximum load of 2amps

- Euro Plug Top
- 2.1 DC Connector

## General Specifications

Type	Switched Mode Power Supply
Input Plug Type	Euro Plug Top
Output Connector	2.1x5.5x12mm C+ve
Input Connector	Euro 2 pin
Cable Length	1.5mtr
Cable Type	2 core Fig 8
Power Indicator	No
Over Current Protection	Yes
Short Current Protection	Yes
Over Current Protection	Yes
MTBF	50000 hours at maximum load
Medical Approval	No

### Electrical Specifications

#### Input Specifications

Rated Input Voltage	100 to 240V ac
Full Input Voltage Range	90 – 264V ac
Rated Frequency	50/60Hz
Full Frequency Range	47/63Hz
Efficiency	86%
Power Factor	
Input Current (RMS Max.)	0.8A
Inrush Current	60A Max
Leakage Current (max.)	0.25mA / 240V ac
Input Protection	Thermal fuse in Primary; Current Limit, Short Circuit

#### Output Specifications

Output Voltage	12V dc	
Maximum No load Voltage	12V dc	
Output Maximum Current	2amp	
Output Minimum Current	0A	
Output Regulation	+/-5%	
Rated Power	24W	
Start Up Delay	20ms	
Start Up Rise Time	20ms	
Hold Up Time	20ms	
Transient Response		
Number of Outputs	1	
Efficiency	86%	
Efficiency Level	VI	
Output Voltage Precision	5%	
Ripple & Noise	200mV	
Turn On Delay	4 Seconds Max.	
Insulation Class	II	
Switching Frequency	70KHz	
Isolation Resistance	100MΩ @500V dc	
Voltage Isolation	Input-Output	3000V ac
	Input-Ground	
	Output-Ground	

### Mechanical Specifications

Dimension	
Length	72mm
Width	43mm
Depth	29mm
Weight	100g

**Operation Environment Specifications**

Operating Humidity	20% to 85% RH non-condensing
Cooling	Natural convection
Operating Temperature Range	0 to 40°C
Storage Temperature Range	-20 to 80°C
Temperature Coefficient	
Altitude During Operation	3000m
Vibration Resistance	To IEC-68-2-6
Shock Resistance	

**Approvals**

Compliance/Certifications	<u>CE</u>
Declarations	MFR Declaration of Conformity
Medical Approval	NO

