

## 4 THREADED BARS 250A L1000/ LINERGY BS BB

LVS04162

EAN Code: 3606481870254

### Main

| Range                     | Linergy                                                         |
|---------------------------|-----------------------------------------------------------------|
| Range of product          | Linergy                                                         |
| Product or component type | Busbar                                                          |
| product name              | Linergy BS                                                      |
| Range compatibility       | PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P enclosure |
| Busbar description        | Flat bar                                                        |
| Quantity per set          | Set of 4                                                        |

## Complementary

| Installation direction                   | Vertical, operating position: rear                                                                                                                                       |
|------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| installation description                 | Cubicle - width 650 mm Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Floor-standing duct - width 300 mm Wall-mounted duct - width 300 mm |
| [le] rated operational current           | 250 A at 35 °C                                                                                                                                                           |
| [lcw] rated short-time withstand current | 13 kA (1 s) for 2 supports                                                                                                                                               |
| [lpk] rated peak withstand current       | 40 kA                                                                                                                                                                    |
| Busbar cross section                     | 20 x 5 mm                                                                                                                                                                |
| Length                                   | 1000 mm                                                                                                                                                                  |
| Width                                    | 20 mm                                                                                                                                                                    |
| Depth                                    | 5 mm                                                                                                                                                                     |
| Net weight                               | 3.52 kg                                                                                                                                                                  |
| Colour                                   | Natural                                                                                                                                                                  |
| Type of busbar connection                | M6 threaded hole                                                                                                                                                         |
| Connection pitch                         | Connection each 25 mm                                                                                                                                                    |

### **Environment**

| Standards              | IEC 61439-2<br>IEC 61439-1 |
|------------------------|----------------------------|
| Product certifications | ASTA                       |

## **Packing Units**

Unit Type of Package 1 PCE

| Number of Units in Package 1 | 1          |
|------------------------------|------------|
| Package 1 Height             | 2.000 cm   |
| Package 1 Width              | 13.000 cm  |
| Package 1 Length             | 109.500 cm |
| Package 1 Weight             | 3.476 kg   |
| Unit Type of Package 2       | P12        |
| Number of Units in Package 2 | 60         |
| Package 2 Height             | 29.000 cm  |
| Package 2 Width              | 80.000 cm  |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 221.000 kg |

## **Logistical informations**

Country of origin FF

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

| Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) | 84                            |  |
|-------------------------------------------------------|-------------------------------|--|
| Environmental Disclosure                              | Product Environmental Profile |  |

### **Use Better**


| Packaging made with recycled cardboard | Yes                                |
|----------------------------------------|------------------------------------|
| Packaging without single use plastic   | No                                 |
| EU RoHS Directive                      | Compliant                          |
| REACh Regulation                       | REACh Declaration                  |
| Halogen content performance            | Halogen free plastic parts product |
| PVC free                               | Yes                                |

### **Use Again**

| ○ Repack and remanufacture |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| Take-back                  | No                                                                                                                          |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### **Technical Illustration**

#### **Dimensions**



- All dimensions are approximate and are in
   Also see technical documentation.