





Wheels Non-Reinforced Cut-Off - NRCO

Flat cutting off wheel Non-Reinforced Cut-Off-Norton NRCO-180x1x31.75-57A60RB25

Artical Number :69936625781

EAN:3157625803336

Video 1:



Non-reinforced cut-off wheels are only designed for use on fixed base machines, where the work is securely clamped, the wheel is adequately guarded and operating on a controlled cutting plane. They are suitable for use in dry or wet conditions, depending on bond type.

Benefits

Pure semi-friable 57A aluminium oxide or blended 23A of 57A aluminium oxide & white monocristalline 32A aluminium oxide

57A: Less tough than type A abrasive but offers better cutting quality

thanks to its pointed shape.

57A: Less tough than type A abrasive but offers better cutting quality thanks to its pointed shape.

Cool & burn free cutting

Very versatile: suitable for all steels

RecessDiameterB: RecessDepthB:

Shape

MaximumOperatingSpeed (m/s):

57A: Good compromise between cut quality & wheel life 23A: Improved metal removal rate compared to 57A pure semifriable aluminium oxide abrasive

57A: Ideal for heat-sensitive applications with light to moderate feed rates

Application Data

STEEL Material Application:

Stationary (Industrial) Machine:

Cut-Off Process:

Equipments:





Technical Data

WheelType: Flat cutting off wheel

ExternalSpecification: 57A60RB25

NON-REINFORCED CUTOFF WHEELS

EndUse:

FaceProfile:

Thickness:

ArborHole:

Diameter:

180 1 31.75

RecessDiameterA:

RecessDepthA:



80

Logistic Data

Naked Product Weight 67.45 Packed Product Dimension 228.000 mmx60.000 mmx60.000 mmmm

Naked Product Dimension 180x1x31.75 pack Qty (parts per pack) 25 pc Units per part Packed Product Weight 1686.250 g 1 pc