

# CA-17S1N8AT0DNS - Cable connector



1619428

<https://www.phoenixcontact.com/gb/products/1619428>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

M23, Cable connector, series: CA, angled, shielded: yes, SPEEDCON, No. of pos.: 17, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 3 mm ... 14.5 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243546



## Your advantages

- Angled cable outlet for confined spaces
- Can be adapted to various applications, thanks to adjustable cable outlet direction
- Safe use in the field, thanks to high degree of protection
- Connector for flexible on-site assembly
- Consistent EMC protection for reliable transmission of signals
- Reduced connection time with SPEEDCON fast locking system
- Crimping connection: vibration- and temperature-resistant assembly

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 1619428                        |
| Packing unit                         | 1 pc                           |
| Minimum order quantity               | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | ABRAED                         |
| Product key                          | ABRAED                         |
| Catalog page                         | Page 91 (C-2-2019)             |
| GTIN                                 | 4046356824194                  |
| Weight per piece (including packing) | 189.4 g                        |
| Weight per piece (excluding packing) | 189.4 g                        |
| Customs tariff number                | 85366990                       |
| Country of origin                    | DE                             |

# CA-17S1N8AT0DNS - Cable connector



1619428

<https://www.phoenixcontact.com/gb/products/1619428>

## Technical data

### Notes

|                    |                                           |
|--------------------|-------------------------------------------|
| Order information: | Order 17 x 1 mm crimp contacts separately |
|--------------------|-------------------------------------------|

### Product properties

|              |                                 |
|--------------|---------------------------------|
| Product type | Circular connector (cable-side) |
|--------------|---------------------------------|

### Data management status

|                  |    |
|------------------|----|
| Article revision | 06 |
|------------------|----|

### Connector

#### Connection 1

|             |        |
|-------------|--------|
| Head design | Socket |
|-------------|--------|

#### Insulating body

|                                              |                                                           |
|----------------------------------------------|-----------------------------------------------------------|
| Note                                         | Order information: Order crimp contacts Ø 1 mm separately |
| Coding                                       | N                                                         |
| Insulation body material                     | PA 6.6                                                    |
| Connection method                            | Crimp connection                                          |
| Contact switching type                       | Socket                                                    |
| Application                                  | Signal                                                    |
| Number of positions                          | 17                                                        |
| Direction of rotation                        | Standard                                                  |
| Connection profile                           | 17                                                        |
| Contact diameter                             | 1 mm                                                      |
| Signal contacts                              |                                                           |
| Litz wire cross-section Signal contacts min. | 0.08 mm²                                                  |
| Litz wire cross-section Signal contacts max. | 1 mm²                                                     |
| Nominal current per signal contact           | 8 A                                                       |
| Note                                         | for max. connection cross section                         |
| Rated voltage Signal contact                 | 48 V AC                                                   |
| Rated surge voltage                          | 1.5 kV                                                    |
| Overvoltage category                         | III                                                       |
| Degree of pollution                          | 3                                                         |

#### Housing

|                                   |          |
|-----------------------------------|----------|
| Housing material                  | Metal    |
| Type of locking                   | SPEEDCON |
| Pg screw connection               | none     |
| Degree of protection (plugged in) | IP67     |
| Thread type                       | M23      |

#### Seal

|                         |                  |
|-------------------------|------------------|
| External cable diameter | 3 mm ... 14.5 mm |
|-------------------------|------------------|

# CA-17S1N8AT0DNS - Cable connector



1619428

<https://www.phoenixcontact.com/gb/products/1619428>

|               |     |
|---------------|-----|
| Seal material | NBR |
|---------------|-----|

## Environmental and real-life conditions

### Ambient conditions

|                                          |                   |
|------------------------------------------|-------------------|
| Ambient temperature (operation)          | -40 °C ... 125 °C |
| Ambient temperature (storage/transport)  | 15 °C ... 25 °C   |
| Permissible humidity (storage/transport) | 50 % ... 65 %     |

# CA-17S1N8AT0DNS - Cable connector

1619428

<https://www.phoenixcontact.com/gb/products/1619428>



## Drawings

Schematic diagram



Connector pin assignment

# CA-17S1N8AT0DNS - Cable connector



1619428

<https://www.phoenixcontact.com/gb/products/1619428>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/1619428>

|                                                                                                                                          |                       |                       |                   |                             |
|------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>cUL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|                                                                                                                                          | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                          | 48 V                  | 3 A                   | 20 - 20           | -                           |

|                                                                                                                                         |                       |                       |                   |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|  <b>UL Recognized</b><br>Approval ID: E335019-20141210 |                       |                       |                   |                             |
|                                                                                                                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                                                                         | 48 V                  | 5 A                   | 20 - 20           | -                           |

|                         |  |  |  |  |
|-------------------------|--|--|--|--|
| <b>cULus Recognized</b> |  |  |  |  |
|-------------------------|--|--|--|--|

# CA-17S1N8AT0DNS - Cable connector



1619428

<https://www.phoenixcontact.com/gb/products/1619428>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27440102 |
| ECLASS-12.0 | 27440116 |
| ECLASS-13.0 | 27440116 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002635 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# CA-17S1N8AT0DNS - Cable connector



1619428  
<https://www.phoenixcontact.com/gb/products/1619428>

## Environmental product compliance

|                                         |                                                                                                                                                                                                                                   |
|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS                                 |                                                                                                                                                                                                                                   |
| Fulfills EU RoHS substance requirements | Yes                                                                                                                                                                                                                               |
| Exemption                               | 6(c)                                                                                                                                                                                                                              |
| China RoHS                              |                                                                                                                                                                                                                                   |
| Environment friendly use period (EFUP)  | EFUP-50                                                                                                                                                                                                                           |
|                                         | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. |
| EU REACH SVHC                           |                                                                                                                                                                                                                                   |
| REACH candidate substance (CAS No.)     | Lead(CAS: 7439-92-1)                                                                                                                                                                                                              |
| SCIP                                    | 636a5906-39e6-422c-8ce4-51481d828267                                                                                                                                                                                              |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd  
Halesfield 13, Telford  
Shropshire, TF7 4PG  
01952 681700  
[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)