

# PM3200 power meter

Local distributor code:

397406977 METSEPM3200

EAN Code: 3606480481581

#### Main

Range	PowerLogic	
Product name	PowerLogic PM3000	
Product or component type	Power meter	
Device short name	PM3200	
Market segment	Buildings small building cost management: billing: sub feeder Buildings medium building cost management: billing: sub feeder Buildings large building cost management: billing: sub feeder Buildings multi-site cost management: billing: sub feeder Data center cost management: billing: sub feeder Healthcare cost management: billing: sub feeder Industry cost management: billing: sub feeder Buildings small building cost management: cost allocation: sub feeder Buildings medium building cost management: cost allocation: sub feeder Buildings large building cost management: cost allocation: sub feeder Buildings multi-site cost management: cost allocation: sub feeder Data center cost management: cost allocation: sub feeder Healthcare cost management: cost allocation: sub feeder Industry cost management: cost allocation: sub feeder	

## Complementary

Power quality analysis	up to the 15th harmonic
Device application	Multi-tariff
	Sub billing
	Power monitoring
Type of measurement	Active and reactive power
	Apparent power
	Current
	Voltage
	Energy
	Power factor
	Frequency
supply voltage	100277 V AC 4565 Hz
	173480 V AC 4565 Hz
	100300 V DC
Network frequency	50 Hz
	60 Hz
[In] rated current	5 A
	1 A
type of network	3P + N
	3P
	1P + N
Power consumption in VA	5 VA
Display type	Backlit LCD
Display resolution	128 x 96 pixels

Sampling rate	32 samples/cycle	
Measurement current	0.056 A 0.021.2 A	
Analogue input type	Current 05 A Current 01 A	
Measurement voltage	50330 V AC 4565 Hz direct 50330 V AC 4565 Hz phase to neutral 80570 V AC 4565 Hz direct 80570 V AC 4565 Hz phase to phase 570999000 V AC 4565 Hz with external VT	
Frequency measurement range	4565 Hz	
Number of inputs	0	
Measurement accuracy	Current 0.3 % 0.56 A Current 0.5 % 0.11.2 A Voltage 0.3 % 50330 V Voltage 0.3 % 80570 V	
Accuracy class	Class 0.5S active energy conforming to IEC 62053-22 Class 1 active energy conforming to IEC 62053-21 Class 2 reactive energy conforming to IEC 62053-23 Class C active energy conforming to EN 50470-3	
Number of outputs	0	
Information displayed	Tariff (4)	
Communication port protocol	- k	
Communication port support	-	
Data recording	Min/max of instantaneous values	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Standards	BS EN 61557-12 IEC 61557-12 EN 61557-12 BS EN 61326-1 IEC 61326-1 EN 61326-1 EN 61326-1 EN 61326-1 EN 61326-1 EN 62052-11 IEC 62052-11 EN 62052-21 EN 62053-21 EN 62053-21 EN 62053-22 EN 62053-22 IEC 62053-22 EN 62052-22 BS EN 62052-22 BS EN 62052-23 BS EN 61010-1 EN 61010-1 IEC 61010-1 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 ANSI C12.20	
Product certifications	CE conforming to IEC 61010-1 (safety) CE conforming to EN 61557-12 (power monitor) CE conforming to EN/IEC 61326-1 (EMC) UKCA conforming to BS EN 61010-1 (safety) UKCA conforming to BS EN 61557-12 (power monitor) UKCA conforming to BS EN 61326-1 (EMC) CULus conforming to EN 61010-1 (safety) CULus conforming to UL 61010-1 (safety) EAC (sub-meter) RCM	

Width	90 mm
Depth	70 mm
Height	95 mm
Net weight	0.26 kg
Market segment	Residential Small commercial

### **Environment**

Electromagnetic compatibility	Electrostatic discharge level 4 conforming to IEC 61000-4-2 Susceptibility to electromagnetic fields level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 Surge immunity test level 4 conforming to IEC 61000-4-5 Conducted RF disturbances level 3 conforming to IEC 61000-4-6 Magnetic field at power frequency - test level: 0.5 mT conforming to IEC 61000-4-8 Conducted and radiated emissions class B conforming to EN 55022	
Overvoltage category	III	
IP degree of protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529	
Relative humidity	595 % at 50 °C	
Pollution degree	2	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	
Operating altitude	< 3000 m	
Compatibility code	PM3200	

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.800 cm
Package 1 Width	13.200 cm
Package 1 Length	13.700 cm
Package 1 Weight	401.800 g
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.829 kg

## **Logistical informations**

Country of origin CN

### **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Total lifecycle Carbon footprint	97
Environmental Disclosure	Product Environmental Profile

#### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant with Exemptions
SCIP Number	97b2464b-a770-4df3-ae2e-dece74cced54
REACh Regulation	REACh Declaration

#### **Use Again**

○ Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins