



tesapack® Solid & Strong

Product Information

BNR 58264, 58143, 58640, 58641, 58642, 58283

Product Description

tesapack® perfect & strong is a PP and solvent-free packaging tape. The brown or transparent tape stands out for its versatility and extra high performance.

Product Features

- Strong PP backing
- Solvent-free adhesive with high UV-resistance
- High sealing security
- Especially even, low-noise unwinding
- Suitable for use in all tesa® hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 60 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|-----------------------------|-----------|
| • Tensile strength | 55 N/cm | • Residue-free removability | no |
| • Adhesive strength | Very high adhesion | • Reusable | no |
| • Ageing resistance (UV) | yes | • Roll width max | 50 mm |
| • Applicationfield | Home, Office | • Serrated blade | _NULL |
| • Batteries included | no | • Solvent free | yes |
| • Batteries required | no | • Spare part service | no |
| • Hand tearability | no | • Suitable surfaces | Cardboard |
| • Humidity resistance | no | • Tear resistance | yes |
| • Low noise unwinding | yes | • Tensibility | 140 % |
| • Material | PP (polypropylene) | • Tension control | _NULL |
| • Max roll length | 66 m | • Writable | no |



tesapack[®] Solid & Strong

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>