

XF or MX voltage release, standard, Masterpact MTZ1/2/3, 200/250 VAC 50/60 Hz, 200/250 VDC, spare part

LV833662SP

EAN Code: 3606480932540

Main

Range	MasterPact	
Product or component type	Voltage release	
Device application	Control	
Range compatibility	Masterpact MasterPact MTZ2 circuit-breaker Masterpact MasterPact MTZ3 circuit-breaker Masterpact MasterPact MTZ1 circuit-breaker	
Voltage release type	Closing coil	

Complementary

[Un] voltage power supply	200250 V AC 50/60 Hz 200250 V DC	
Threshold tripping voltage	0.71.1 Un on opening 0.851.1 Un on closing	
Holding power consumption	4.5 W	
Circuit breaker mounting mode	Fixed/drawout	
Maximum response time	60 ms on opening for MasterPact MTZ1 60 ms on opening for MasterPact MTZ2 60 ms on opening for MasterPact MTZ3 65 ms on closing for MasterPact MTZ1 80 ms on closing for MasterPact MTZ2 90 ms on closing for MasterPact MTZ3	
Provided equipment	1 instruction sheet	
Offer type	Spare part	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.500 cm
Package 1 Width	6.200 cm
Package 1 Length	8.500 cm
Package 1 Weight	166.000 g
Unit Type of Package 2	S04
Number of Units in Package 2	40
Package 2 Height	30.000 cm
Package 2 Width	40.000 cm

Package 2 Length	60.000 cm
Package 2 Weight	7.340 kg

Logistical informations

Country of origin

Contractual warranty

Warranty 18 months

1 Jul 2025



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	4
Environmental Disclosure	Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions
SCIP Number	Fb7b4f31-e2d2-4b8c-a9f0-9a1e2c43da19
REACh Regulation	REACh Declaration
Halogen content performance	Product contains halogen above thresholds
PVC free	Yes
Silicon free	No

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

