




UD20-12MM-12MM-SS

Ruland UD20-12MM-12MM-SS, 12mm x 12mm Double Universal Joint, Friction Bearing, Stainless Steel, 31.6mm OD, 142.9mm Length









Description

Ruland UD20-12MM-12MM-SS is a double cardan friction bearing universal joint with 12mm x 12mm bores, 31.6mm OD, and 142.9mm length. It is ideal for applications with wide distances between shafts and can accommodate all forms of misalignment. This plain bearing double universal joint is comprised of pins and blocks that are precision machined, selectively heat treated, and ground for high strength, accuracy, and wear resistance. The combination of these components with precision ground and hardened yoke ears allow for a longer lifespan, increased performance in demanding applications, and greater angular misalignment of up to 90° when compared to commodity style double universal joints. UD20-12MM-12MM-SS is made from high grade stainless steel for increased corrosion resistance. It can be combined with boot UBOOT20/32-NI-KIT to protect the joints from unwanted contaminants such as dust or water and self lubricate reducing maintenance time. This double cardan universal joint is manufactured in the USA by Belden Universal for strict control of processes.

Product Specifications

	Small Bore (B2)	12 mm
1	B2 Max Shaft Penetration	31.8 mm
1	Bore Tolerance	+0.025 mm / -0.000 mm
	Center Yoke Length (LC)	47.6 mm
1	Hub Depth (LH)	31.8 mm
1	Rated Torque	69.1 Nm
I	Material Specification	Yokes: 303 Stainless Steel Pins and Blocks: 416 Stainless Steel
ersal	Country of Origin	USA
E No. 1200-2	Matching Boot Cover	UBOOT20/32-NI-KIT
8	Tariff Code	8483.60.4000
Performance ratings are for guidance only. The user must determine suitability for a particular application.		
	· ·	allic), known to the State of Californ
		cer. For more information go to www.P65Warnings.ca.gov .