

















< List of part numbers with package codes > LQH2HPZ1R0NJRL

Shape



Notes

When applied Rated current to the Products, Inductance will be within $\pm 30\%$ of intial inductance value range.

Keep the temperature(ambient temperature plus self-generation of heat) under 125℃.

When applied rated current to the Products, temperature rise caused by self-generated heat shall be limited to 40°C max. (Ambient temperature 85°C).

When applied rated current to the Products, temperature rise caused by self-generated heat shall be limited to 20° C max. (Ambient temperature $85\text{-}105^{\circ}$ C).

References

Packaging code	Specifications	Minimum quantity	
L	ϕ 180mm Embossed taping	2000	

Mass (Typ.)	
1 piece	0.023g

Specifications

Inductance	1.0μH ±30%
Inductance test frequency	1MHz
Rated current (Isat) (Based on Inductance change)	2600mA
Rated current (Itemp) (Based on Temperature rise)	2400mA(Ambient temp.85℃) 1440mA(Ambient temp.105℃)
Max. of DC resistance	0.0576Ω
Avg. of DC resistance	0.048Ω±20%
Self resonance frequency (min.)	120MHz
Operating temperature range (Self-temperature rise is included)	-40~125℃
Operating temperature range (Self-temperature rise is not included)	-40~105℃
Class of magnetic shield	Magnetic Resin

Attention

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.




^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.


 $^{2.} This \ data{sheet has only typical specifications because there is no \ space for \ detailed \ specifications.}$

Chart of characteristic data (The charts below may show another part number which shares its characteristics.)


Inductance-Frequency characteristics (Typ.)



Temperature rise characteristics (Typ.)



Inductance-Current characteristics (Typ.)



2 of 2

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

^{1.} This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

^{2.} This datasheet has only typical specifications because there is no space for detailed specifications.