

Datasheet

Product Name: UL1430 26AWG
Product Discription: UL1430 26AWG
Specification No.:
Customer's Name:

					Customer's Name:					
Description					Construction					
Rated V	/oltage:		300V		Conductor	Stranded Tinned Cop	pper			
Rated T	emperature:		105℃		Size(AWG)	26				
Referer	nce Standard:	UL7	58,UL1581		Construction(±0.008mm)	7/0.16				
Cross Section					Stranded Dia.(mm)Ref.	0.48				
					Insulation Material	XLPVC				
					Insulation Color	ANY COLOR				
					Ave Thickness(mm)	0.38				
					Insulation Dia.(±0.10mm)	1.30				
Marking					Remark:					
					8739901 Red	8739905 Blue	•	8739927 Violet		
AWM XLPVC 1430 26AWG 105°C 300V Horizontal flam					8739898 Black	8739914 Whi				
CAL AWM XLPVC 105°C 300V I A FT2 E214859 YANG TAI					8739908 Brown					
						Characteristic		Customer Approve		
Applications					Test Item		Standard Value			
For internal wiring of electronic and electrical equipment					Test Material		XLPVC(ROHS)			
					Insulation resistance(20°C MΩ*m		1000			
					Vol. Tesr(AC.V.60S) (V)		2000	Seal & Stamp		
					Flammability Test		Horizontal flame			
					Max.DC Resistance(20℃ Ω/km)		150(MAX)			
Version	Description		Approved by					_		
0	New document issue	Huang	Jason	14/04/2015						
								Signature:		
								Date:		

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.