# Product datasheet

Specifications



## auxiliary contact - 1 NO + 1 SD NC - for P25M - 415 V - 2.2 A

21120

**EAN Code: 3303430211204**

Discontinued

## Main

| | |
|---|---|
| **range of product** | Acti9 |
| **Product or component type** | OC or fault contact |
| **Device short name** | NO and SD |
| **Signal contacts composition** | 1 NO + 1 NC |
| **9 mm pitches** | 1 |
| **Standards** | EN/IEC 60947-5-1 |
| **Product certifications** | NEMKO<br>CEBEC<br>DEMKO<br>FIMKO<br>SEMKO |

## Complementary

| | |
|---|---|
| **Range compatibility** | Acti9 P25M |
| **mounting mode** | Fixed |
| **Mounting support** | DIN rail |
| **Height** | 89 mm |
| **Width** | 18 mm |
| **Depth** | 65 mm |
| **Connections - terminals** | Clamp terminal: 2 cable(s) 1 mm² - flexible<br>Clamp terminal: 2 cable(s) 2.5 mm² - flexible<br>Clamp terminal: 2 cable(s) 1 mm² - rigid |

## Environment

| | |
|---|---|
| **Tropicalisation** | 2 conforming to EN/IEC 60947-5-1 |
| **Relative humidity** | 95 % at 55 °C |
| **Ambient air temperature for operation** | -20…60 °C |
| **Ambient air temperature for storage** | -40…80 °C |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 6.600 cm |
| **Package 1 Width** | 1.200 cm |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Package 1 Length** | 9.000 cm |
| **Package 1 Weight** | 44.000 g |
| **Unit Type of Package 2** | BB1 |
| **Number of Units in Package 2** | 10 |
| **Package 2 Height** | 9.500 cm |
| **Package 2 Width** | 9.500 cm |
| **Package 2 Length** | 15.000 cm |
| **Package 2 Weight** | 495.000 g |
| **Unit Type of Package 3** | S03 |
| **Number of Units in Package 3** | 100 |
| **Package 3 Height** | 30.000 cm |
| **Package 3 Width** | 30.000 cm |
| **Package 3 Length** | 40.000 cm |
| **Package 3 Weight** | 5.292 kg |

## Logistical informations

| | |
|---|---|
| **Country of origin** | FR |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **0.9 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **0.3 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **0 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0.5 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **0.1 kg CO2 eq.** |
| Environmental Disclosure | **Product Environmental Profile** |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| SCIP Number | **9da5f8d9-d60f-424a-bb30-a856a097686c** |
| EU RoHS Directive | **Compliant By Exemption** |
| REACh Regulation | **Reference contains Substances of Very High Concern above the threshold** |
| Halogen-free status | **Product contains halogen above thresholds** |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | **No** |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **29** |
| End of life manual availability | **No need of specific recycling operations** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |