

PSM-520; 6 ... 30 bar; G 1/4 female

PSM-520; 6 ... 30 bar; G 1/4 female

Item number: 14269086

Quantity: 1 pcs.

Order code: PSM-520-B -1-TBL-Z

W101AP521 52

Overview: PSM-520; 6 ... 30 bar; G 1/4 female
Pressure switch, heavy-duty version
Specifications according to data sheet: PV 35.01
Switching function: Changeover SPDT
Setting of switching point: Factory setting
Rising pressure: switch point 18 bar, reset point 15 bar, switch differential 3 bar
Wetted parts: Copper alloy, free cutting steel tin-plated
Additional ordering information: without
Non-repeatability: $\leq 2\%$ of span
Measuring principle: Bellows
Electrical connection: Rubber grommet for cables $\square 6 \dots 14 \text{ mm}$ ($\square 0.24 \dots 0.55 \text{ in}$)
Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load
Permissible medium temperature: $-20 \dots +100\text{ }^{\circ}\text{C}$ / $-4 \dots +212\text{ }^{\circ}\text{F}$

Details: PSM-520; 6 ... 30 bar; G 1/4 female
Pressure switch, heavy-duty version
Specifications according to data sheet: PV 35.01
Switching function: Changeover SPDT
Setting of switching point: Factory setting
Rising pressure: switch point 18 bar, reset point 15 bar, switch differential 3 bar
Wetted parts: Copper alloy, free cutting steel tin-plated
Additional ordering information: without
Non-repeatability: $\leq 2\%$ of span
Measuring principle: Bellows
Electrical connection: Rubber grommet for cables $\square 6 \dots 14 \text{ mm}$ ($\square 0.24 \dots 0.55 \text{ in}$)
Electrical rating: AC-1: 10 A, AC 230 V resistive load AC-15: 6 A, AC 230 V inductive load
Permissible medium temperature: $-20 \dots +100\text{ }^{\circ}\text{C}$ / $-4 \dots +212\text{ }^{\circ}\text{F}$