


Smart Technology. Delivered.



## **RADIATION PATTERN**

### 1575.410354

**Elevation Plane** 



Americas: +1.847 839.6925 IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com Asia: +86.21.5855.0827.127 IAS-AsiaSales@lairdtech.com

# www.lairdtech.com

# **GPSU15M**

# **Omnidirectional Antenna**

The Laird GPSU15M antenna is a robust, rigorously tested and environmentally sealed unit suitable for a wide variety of GPS applications. The GPSU15M is ideal for vehicle tracking, fleet management and a variety of location applications installations requiring maximum security and durability. The GPSU15M antenna is fully waterproof and features o-ring sealing that protects the antenna against severe environmental conditions for reliable, long-lasting performance.

# FEATURES TROHS

- Fully waterproof o-ring sealing
- High gain engineered performance

## **APPLICATIONS**

- Vehicle Tracking
- · Fleet Management

MECHANICAL SPECIFICATIONS	
Model Number	GPSU15M
Weight	0.5 lbs
Housing Dimension	2.6" (66mm) dia x 1.4" (35.6mm) H
Radome Color	Black (UV Coated)
Mounting	NMO Mountable
Cable	Low Loss ATX195 (recommended)
Termination	NMO
Operating Temperature	-35°C to +85°C
Relative Humidity	20% to 90%
Water Resistance	100% waterproof
Storing Temperature Range	-40°C to +100°C
Humidity Conditions	80% RH, Max
Storage Products	Package in anti-static bag is recommended

ELECTRICAL SPECIFICATIONS	
Frequency Range	1,575.42 ± 1 MHz
Polarization	Right Hand Circularly Polarized (RHCP)
Gain	3dBi min (elevation = 90°) -5dBi min (elevation = 20°)
Axial Ratio	4.0 dB max (elevation = 90°) 6.0 dB max (elevation = 10°)
VSWR	<2:1
Nominal Gain	(26 ± 3) dB
Output Impedance	50 Ω
Noise Figure	1.5dB @25°C
Power Supply	3 to 5 Vdc
Current Consumption	20mA max
Power Handling	1W max
ESD	±8 KV min

#### ANT-DS-GPSU15M 0415

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of any laird materials or products for any specific or general uses. Laird shall not laible for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.