



Datasheet

ENGLISH

Stock No: 519-419

RS Pro Steel Grey Modular Shelving Clad Starter Bay, 2100mm x 1000mm x 400mm



Image representative of range

Product Details

Clad Starter Bay

The basic unit required to construct the first bay. Dimensions: 2.1m x 1m

Note

Clad bay starter units will require a rear cladding kit, to be ordered separately. See stock number [519-475](#)

**Caution**

The maximum safe working load per shelf is 160kg, to be uniformly distributed in both directions, maximum load per bay 1200kg.

Also: All runs of shelving require bracing. This must be in the form of a rear cross-brace assembly or a rear cladding kit and must be fitted at least one bay in six.

Modular Shelving

The RS modular shelving system has been designed as an integrated system in which each part slots together into standard modules. The shelf design incorporates a built-in box beam concept which creates inherent strength and rigidity as well as simplifying installation. A versatile system which is quick, easy and simple to erect or modify, with no nut and bolt assembly of the shelving. The uprights are perforated at 50 mm intervals to accept shelves that clip lock together with special shelf locking clips which have a wedging action when loaded, the greater the load, the stronger the structure. All major components are manufactured from steel with 'graphite' grey uprights and light (RAL7035) grey shelves and cladding paint finish. Available in open bay or clad bay versions, height 2.1 m, width 1 m, with a selection of shelf depths and accessories.

Contents			
	Starter bay qty	Extension bay qty	Shelf kit qty
Frame	2	1	
End cap	4	2	
Feet	4	2	
Cross brace	1 (open bay only)		
Shelves	4	4	2
Shelf clips	16	16	8

Specifications:

System	Modular Shelving
Component Type	Clad Starter Bay
Load Capacity	1200kg
Height	2100mm
Width	1000mm
Depth	400mm
Material	Steel
Colour	Grey