

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2031-1 RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Chronic aquatic toxicity, Category 2	H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET



according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 08.06.2018 SDS Number: 400001009653 Date of last issue: 20.02.2017
Date of first issue: 20.02.2017

Hazard pictograms	:		
Signal word	:	Warning	
Hazard statements	:	H315 H317 H319 H411	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P261 P264 P273 P280 Response: P333 + P313 P391	Avoid breathing mist or vapours. Wash skin thoroughly after handling. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection. If skin irritation or rash occurs: Get medical advice/ attention. Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 60 - <= 100

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorohydrin

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No data is available on the product itself.

5.3 Advice for firefighters

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

- For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.
- Local/Total ventilation : Ensure adequate ventilation.
- Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma,

ARALDITE® 2031-1 RESIN

Version Revision Date: SDS Number: Date of last issue: 20.02.2017
1.1 08.06.2018 400001009653 Date of first issue: 20.02.2017

allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Dermal	Systemic effects, Short-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Short-term exposure	12.25 mg/m3
	Workers	Dermal	Systemic effects, Long-term exposure	8.33 mg/kg bw/day
	Workers	Inhalation	Systemic effects, Long-term exposure	12.25 mg/m3

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 08.06.2018 SDS Number: 400001009653 Date of last issue: 20.02.2017
 Date of first issue: 20.02.2017

	Consumers	Dermal	Systemic effects, Short-term exposure	3.571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Short-term exposure	0.75 mg/kg bw/day
	Consumers	Dermal	Systemic effects, Long-term exposure	3.571 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	0.75 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l
Remarks:	Assessment Factors	
	Marine water	0.0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.018 mg/l
	Assessment Factors	
	Fresh water sediment	0.996 mg/kg
	Equilibrium method	
	Marine sediment	0.0996 mg/kg
	Equilibrium method	
	Soil	0.196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
	Fresh water	0.006 mg/l
	Assessment Factors	
	Marine water	0.0006 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.018 mg/l
	Assessment Factors	
	Fresh water sediment	0.996 mg/kg
	Equilibrium method	
	Marine sediment	0.0996 mg/kg

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 08.06.2018 SDS Number: 400001009653 Date of last issue: 20.02.2017
Date of first issue: 20.02.2017

	Equilibrium method	
	Soil	0.196 mg/kg
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg
	Assessment Factors	
	Soil	23 mg/kg
	Assessment Factors	

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Recommended Filter type:
Combined particulates and organic vapour type

Filter type : Filter type A-P

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: paste
Colour	: black
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: ca. 7 (20 °C) Concentration: 500 g/l
Freezing point	: No data is available on the product itself.
Melting point	: No data is available on the product itself.
Boiling point	: > 200 °C
Flash point	: 200 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: ca. 0.01 hPa (20 °C)
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: ca. 1.16 g/cm ³ (25 °C)
Solubility(ies)	
Water solubility	: practically insoluble (20 °C)
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Stable under recommended storage conditions.
No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

No decomposition if stored and applied as directed.
Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Stable under normal conditions.
No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Carbon oxides
Burning produces noxious and toxic fumes.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild skin irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Mild eye irritant

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Exposure routes: Skin

Species: Mouse

Assessment: May cause sensitisation by skin contact.

Method: OECD Test Guideline 429

Result: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Method: OECD Test Guideline 476
Result: positive

: Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Genotoxicity in vivo

: Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg
Frequency of Treatment: 7 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 days/week
Method: OECD Test Guideline 453
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: >750 milligram per kilogram
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level: 30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level: 60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level: 180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Ingestion

Exposure time: 14 Weeks Number of exposures: 7 d

Method: Subchronic toxicity

Species: Rat, male and female

NOEL: 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 5 d

Method: Subchronic toxicity

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 3 d

Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n- : log Pow: 3.242 (25 °C)
octanol/water pH: 7.1
Method: OECD Test Guideline 117

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Distribution among : Koc: 445
environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of
information unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Can be landfilled or incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal or incineration.
Send to a licensed waste management company.
- The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
- Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

- 14.1 UN number : UN 3082
- 14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN)
- 14.3 Transport hazard class(es) : 9
- 14.4 Packing group : III
- Labels : Miscellaneous
- Packing instruction (cargo aircraft) : 964
- Packing instruction (passenger aircraft) : 964
- IATA (Passenger)**
- Environmentally hazardous : yes
- IATA (Cargo)**
- Environmentally hazardous : yes

IMDG

- 14.1 UN number : UN 3082

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version 1.1 Revision Date: 08.06.2018 SDS Number: 400001009653 Date of last issue: 20.02.2017
Date of first issue: 20.02.2017

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

EmS Code : F-A, S-F

14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

14.5 Environmental hazards
Environmentally hazardous : yes

Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Chronic aquatic toxicity
-----------------	----------------------------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 20.02.2017
1.1	08.06.2018	400001009653	Date of first issue: 20.02.2017

Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® 2031-1 HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40

E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin corrosion, Sub-category 1B	H314: Causes severe skin burns and eye damage.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

ARALDITE® 2031-1 HARDENER

Version Revision Date: SDS Number: Date of last issue: 21.02.2017
1.1 24.07.2018 400000005303 Date of first issue: 21.02.2017

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/
eye protection/ face protection.

Response:
P303 + P361 + P353 IF ON SKIN (or hair): Take off
immediately all contaminated clothing.
Rinse skin with water.
P304 + P340 + P310 IF INHALED: Remove person to fresh
air and keep comfortable for breathing.
Immediately call a POISON
CENTER/doctor.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously
with water for several minutes. Remove
contact lenses, if present and easy to do.
Continue rinsing. Immediately call a
POISON CENTER/doctor.
P391 Collect spillage.

Hazardous components which must be listed on the label:

2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated

1,3-Cyclohexanedimethanamine

2,4,6-Tris(dimethylaminomethyl)phenol

3-Aminopropyltriethoxysilane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version 1.1 Revision Date: 24.07.2018 SDS Number: 400000005303 Date of last issue: 21.02.2017
Date of first issue: 21.02.2017

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated	68683-29-4 -	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	≥ 30 - < 50
1,3-Cyclohexanedimethanamine	2579-20-6 219-941-5	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Aquatic Chronic 3; H412	≥ 10 - < 20
Bis(isopropyl)naphthalene	38640-62-9 254-052-6 01-2119565150-48	Asp. Tox. 1; H304 Aquatic Chronic 1; H410	≥ 2.5 - < 10
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2 202-013-9 603-069-00-0 01-2119560597-27	Skin Corr. 1C; H314 Eye Dam. 1; H318	≥ 1 - < 3
3-Aminopropyltriethoxysilane	919-30-2 213-048-4 612-108-00-0 01-2119480479-24	Acute Tox. 4; H302 Skin Corr. 1B; H314 Skin Sens. 1; H317	≥ 0.1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : No hazardous combustion products are known

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Specific extinguishing methods : No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information.,
For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : Ensure that eyewash stations and safety showers are close to the workstation location.

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version 1.1 Revision Date: 24.07.2018 SDS Number: 400000005303 Date of last issue: 21.02.2017
Date of first issue: 21.02.2017

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
barium sulfate	7727-43-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
Further information	For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m ⁻³ 8-hour TWA of inhalable dust or 4 mg.m ⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version 1.1 Revision Date: 24.07.2018 SDS Number: 400000005303 Date of last issue: 21.02.2017
Date of first issue: 21.02.2017

	TWA (Respirable dust)	4 mg/m ³	GB EH40
Further information	<p>For the purposes of these limits, respirable dust and inhalable dust are those fractions of airborne dust which will be collected when sampling is undertaken in accordance with the methods described in MDHS14/3 General methods for sampling and gravimetric analysis of respirable and inhalable dust, The COSHH definition of a substance hazardous to health includes dust of any kind when present at a concentration in air equal to or greater than 10 mg.m⁻³ 8-hour TWA of inhalable dust or 4 mg.m⁻³ 8-hour TWA of respirable dust. This means that any dust will be subject to COSHH if people are exposed above these levels. Some dusts have been assigned specific WELs and exposure to these must comply with the appropriate limit., Most industrial dusts contain particles of a wide range of sizes. The behaviour, deposition and fate of any particular particle after entry into the human respiratory system and the body response that it elicits, depend on the nature and size of the particle. HSE distinguishes two size fractions for limit-setting purposes termed 'inhalable' and 'respirable'. Inhalable dust approximates to the fraction of airborne material that enters the nose and mouth during breathing and is therefore available for deposition in the respiratory tract. Respirable dust approximates to the fraction that penetrates to the gas exchange region of the lung. Fuller definitions and explanatory material are given in MDHS14/3., Where dusts contain components that have their own assigned WEL, all the relevant limits should be complied with., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure should be used</p>		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
bis(isopropyl)naphthalene	Workers	Inhalation	Systemic effects, Long-term exposure	30 mg/m ³
	Workers	Dermal	Systemic effects, Long-term exposure	4.3 mg/kg bw/day
	Consumers	Inhalation	Systemic effects, Long-term exposure	7.4 mg/m ³
	Consumers	Dermal	Systemic effects, Long-term exposure	2.1 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	2.1 mg/kg bw/day
barium sulfate	Workers	Inhalation	Long-term systemic effects	10 mg/m ³
	Workers	Inhalation	Long-term local effects	10 mg/m ³
	Consumer use	Inhalation	Long-term systemic effects	10 mg/m ³
	Consumer use	Oral	Long-term systemic effects	13000 mg/kg
Bis(isopropyl)naphthalene	Workers	Inhalation	Systemic effects, Long-term exposure	30 mg/m ³
	Workers	Dermal	Systemic effects,	4.3 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version 1.1 Revision Date: 24.07.2018 SDS Number: 400000005303 Date of last issue: 21.02.2017
Date of first issue: 21.02.2017

			Long-term exposure	bw/day
	Consumers	Inhalation	Systemic effects, Long-term exposure	7.4 mg/m ³
	Consumers	Dermal	Systemic effects, Long-term exposure	2.1 mg/kg bw/day
	Consumers	Oral	Systemic effects, Long-term exposure	2.1 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
bis(isopropyl)naphthalene	Fresh water	0.26 µg/l
Remarks:	Assessment Factors	
	Marine water	0.026 µg/l
	Assessment Factors	
	Sewage treatment plant	0.15 mg/l
	Assessment Factors	
	Fresh water sediment	0.94 mg/kg
	Equilibrium method	
	Marine sediment	0.094 mg/kg
	Equilibrium method	
	Soil	0.1872 mg/kg
	Equilibrium method	
	Secondary Poisoning	25 mg/kg
	Assessment Factors	
2,4,6-tris(dimethylaminomethyl)phenol	Fresh water	0.084 mg/l
	Assessment Factors	
	Marine water	0.0084 mg/l
	Assessment Factors	
	Sewage treatment plant	0.2 mg/l
	Assessment Factors	
2,4,6-Tris(dimethylaminomethyl)phenol	Fresh water	0.084 mg/l
	Assessment Factors	
	Marine water	0.0084 mg/l
	Assessment Factors	
	Sewage treatment plant	0.2 mg/l
	Assessment Factors	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version 1.1 Revision Date: 24.07.2018 SDS Number: 400000005303 Date of last issue: 21.02.2017
Date of first issue: 21.02.2017

barium sulfate	Fresh water	115 µg/l
	Sewage treatment plant	62.2 mg/l
	Assessment Factors	
	Fresh water sediment	600.4 mg/kg
	Assessment Factors	
	Soil	207.7 mg/kg
	Assessment Factors	
Bis(isopropyl)naphthalene	Fresh water	0.26 µg/l
	Assessment Factors	
	Marine water	0.026 µg/l
	Assessment Factors	
	Sewage treatment plant	0.15 mg/l
	Assessment Factors	
	Fresh water sediment	0.94 mg/kg
	Equilibrium method	
	Marine sediment	0.094 mg/kg
	Equilibrium method	
	Soil	0.1872 mg/kg
	Equilibrium method	
	Secondary Poisoning	25 mg/kg
	Assessment Factors	
Siloxanes and Silicones, di-Me, reaction products with silica	Fresh water sediment	> 100 mg/kg
	Assessment Factors	
	Soil	23 mg/kg
	Assessment Factors	

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Material : Nitrile rubber
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Recommended Filter type:
Combined particulates and organic vapour type

Filter type : Filter type A-P

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : paste

Colour : black

Odour : very faint, amine-like

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : > 200 °C
Method: estimated

Flash point : > 100 °C
Method: estimated, closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : ca. 1.4 g/cm³ (23 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : > 200 °C
Method: estimated

Viscosity

Viscosity, dynamic : 125 - 225 Pas (20 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

None known.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

Components:

Bis(isopropyl)naphthalene:

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.64 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

3-Aminopropyltriethoxysilane:

Acute inhalation toxicity : LC50 (Rat, male): > 5 ppm
Exposure time: 6 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Product:

Assessment: Causes burns.

Remarks: Information given is based on data obtained from similar substances.

Serious eye damage/eye irritation

Components:

2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated:

Species: Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Assessment: Mild eye irritant
Result: slight irritation

Bis(isopropyl)naphthalene:
Species: Rabbit
Assessment: No eye irritation
Method: OECD Test Guideline 405
Result: No eye irritation

2,4,6-Tris(dimethylaminomethyl)phenol:
Species: Rabbit
Assessment: Corrosive
Result: Corrosive

3-Aminopropyltriethoxysilane:
Species: Rabbit
Method: OECD Test Guideline 405
Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation

Components:

2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: May cause sensitisation by skin contact.

1,3-Cyclohexanedimethanamine:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Bis(isopropyl)naphthalene:
Test Type: Maximisation Test
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

2,4,6-Tris(dimethylaminomethyl)phenol:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

3-Aminopropyltriethoxysilane:
Exposure routes: Skin
Species: Guinea pig
Method: OECD Test Guideline 406
Result: The product is a skin sensitiser, sub-category 1B.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Components:

Bis(isopropyl)naphthalene:
Assessment:

May be harmful if swallowed or if inhaled.
Does not cause skin sensitisation.

Germ cell mutagenicity

Components:

1,3-Cyclohexanedimethanamine:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: positive

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Bis(isopropyl)naphthalene:
Genotoxicity in vitro

: Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Concentration: 9.5 - 60 µg/L
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

: Test Type: Ames test
Test system: Salmonella typhimurium
Concentration: 92 mg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Test Type: In vitro mammalian cell gene mutation test
Test system: mouse lymphoma cells
Concentration: 40 - 60 mg/ml
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

2,4,6-Tris(dimethylaminomethyl)phenol:

Genotoxicity in vitro : Concentration: 5000 µg/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Concentration: 2500 µg/plate
Metabolic activation: with and without metabolic activation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Method: OECD Test Guideline 473
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

3-Aminopropyltriethoxysilane:
Genotoxicity in vitro

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Components:

1,3-Cyclohexanedimethanamine:
Genotoxicity in vivo

: Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Bis(isopropyl)naphthalene:
Genotoxicity in vivo

: Test Type: Micronucleus test
Test species: Mouse (male and female)
Application Route: Intraperitoneal injection
Dose: 1.92 g/kg
Method: OECD Test Guideline 474
Result: negative

3-Aminopropyltriethoxysilane:
Genotoxicity in vivo

: Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Components:

Bis(isopropyl)naphthalene:
Germ cell mutagenicity-
Assessment

: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Germ cell mutagenicity-
Assessment

: No data available

Carcinogenicity

No data available

Carcinogenicity -
Assessment

: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Reproductive toxicity

Components:

1,3-Cyclohexanedimethanamine:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422

2,4,6-Tris(dimethylaminomethyl)phenol:

Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422
Remarks: No significant adverse effects were reported

Components:

Bis(isopropyl)naphthalene:

Effects on foetal development : Species: Rat, female
Application Route: Oral
Dose: 100, 250, 625 mg/kg
Duration of Single Treatment: 20 d
Frequency of Treatment: 7 days/week
General Toxicity Maternal: Lowest observed adverse effect level: 250 mg/kg body weight
Teratogenicity: No observed adverse effect level: 625 mg/kg body weight
Embryo-foetal toxicity: No observed adverse effect level: 625 mg/kg body weight
Method: Directive 67/548/EEC, Annex V, B.31.
Result: No teratogenic effects

Components:

Bis(isopropyl)naphthalene:

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

1,3-Cyclohexanedimethanamine:

Species: Rat, male
NOAEL: 60
Application Route: Ingestion
Exposure time: 1,008 h Number of exposures: 7 d
Method: Subacute toxicity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Bis(isopropyl)naphthalene:
Species: Rat, male and female
NOAEL: 170 mg/kg
Application Route: oral (feed)
Exposure time: 4,320 h Number of exposures: 7 d
Dose: 170, 340, and 670 mg/kg
Method: Subchronic toxicity
Remarks: No significant adverse effects were reported

2,4,6-Tris(dimethylaminomethyl)phenol:
Species: Rat, male and female
NOEL: 15 mg/kg
Application Route: Ingestion
Exposure time: 1,032 h Number of exposures: 7 d
Method: Subacute toxicity

3-Aminopropyltriethoxysilane:
Species: Rat, male and female
NOAEL: 200 mg/kg
Application Route: Ingestion
Exposure time: 2,160 h Method: Subchronic toxicity

Components:

Bis(isopropyl)naphthalene:
Repeated dose toxicity - Assessment : May be harmful if swallowed or if inhaled.
No adverse effect has been observed in chronic toxicity tests.

Aspiration toxicity

Components:

Bis(isopropyl)naphthalene:
May be fatal if swallowed and enters airways.

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (No information available.): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

1,3-Cyclohexanedimethanamine:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 130 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 33.1 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae : EbC50 (Selenastrum capricornutum (green algae)): 29.7 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Ecotoxicology Assessment
Acute aquatic toxicity : This product has no known ecotoxicological effects.

Bis(isopropyl)naphthalene:
Toxicity to fish : LC50 : > 0.5 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: Directive 67/548/EEC, Annex V, C.1.
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 0.16 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility

EL50 (Daphnia magna (Water flea)): 1.7 mg/l
Exposure time: 48 h
Test Type: semi-static test
Method: OECD Test Guideline 202

Toxicity to algae : NOECr (Desmodesmus subspicatus (green algae)): ca. 0.15 mg/l
Exposure time: 72 h
Test Type: static test
Method: DIN 38412
GLP: no
Remarks: Aquatic toxicity is unlikely due to low solubility.

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.013 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment
Acute aquatic toxicity : No toxicity at the limit of solubility

2,4,6-Tris(dimethylaminomethyl)phenol:
Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 175 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other : LC50 : 718 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

aquatic invertebrates : Exposure time: 96 h
Test Type: static test
Test substance: Marine water

Toxicity to algae : ErC50 (Desmodesmus subspicatus (green algae)): 84 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 6.25 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Ecotoxicology Assessment
Chronic aquatic toxicity : This product has no known ecotoxicological effects.

3-Aminopropyltriethoxysilane:
Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 934 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 331 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): > 1,000 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to microorganisms : EC50 (Pseudomonas putida): 43 mg/l
Exposure time: 5.75 h
Test Type: static test
Test substance: Fresh water

12.2 Persistence and degradability

Components:

2-propenenitrile polymer with 1,3-butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated:

Biodegradability : Result: Not readily biodegradable.

1,3-Cyclohexanedimethanamine:

Biodegradability : Inoculum: activated sludge

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Concentration: 10 mg/l
Result: Not readily biodegradable.
Biodegradation: 29 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Stability in water : Degradation half life (DT50): > 1 yr (25 °C)
pH: 6.5
Method: OECD Test Guideline 111
Remarks: Fresh water

Bis(isopropyl)naphthalene:
Biodegradability : Inoculum: activated sludge
Concentration: 0.2 mg/l
Result: Not readily biodegradable.
Biodegradation: 30 - 35 %
Exposure time: 56 d
Method: OECD Test Guideline 310

2,4,6-Tris(dimethylaminomethyl)phenol:
Biodegradability : Inoculum: activated sludge
Concentration: 2 mg/l
Result: Not biodegradable
Biodegradation: 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

3-Aminopropyltriethoxysilane:
Biodegradability : Inoculum: activated sludge
Concentration: 8.95 mg/l
Result: Not readily biodegradable.
Biodegradation: 67 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.A.

12.3 Bioaccumulative potential

Components:

1,3-Cyclohexanedimethanamine:
Partition coefficient: n-
octanol/water : log Pow: 0.783 (21.5 °C)
Method: OECD Test Guideline 107

Bis(isopropyl)naphthalene:
Bioaccumulation : Species: Cyprinus carpio (Carp)
Exposure time: 60 d
Bioconcentration factor (BCF): 770 - 6,400
Test substance: Fresh water
Method: flow-through test

Partition coefficient: n-
octanol/water : log Pow: 6.081
Method: QSAR

2,4,6-Tris(dimethylaminomethyl)phenol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

Partition coefficient: n-octanol/water : log Pow: 0.219 (21.5 °C)
Method: OPPTS 830.7550

3-Aminopropyltriethoxysilane:
Bioaccumulation : Species: Cyprinus carpio (Carp)
Bioconcentration factor (BCF): 3.4
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 1.7 (20 °C)
pH: 7

12.4 Mobility in soil

Components:

Bis(isopropyl)naphthalene:
Distribution among environmental compartments : Koc: 36108
Method: QSAR

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

SECTION 14: Transport information

IATA

14.1 UN number : UN 2735
14.2 UN proper shipping name : Polyamines, liquid, corrosive, n.o.s.
(1,3-CYCLOHEXANEDIMETHANAMINE, DIISOPROPYLNAPHTHALENE ISOMERS)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : Corrosive
Packing instruction (cargo aircraft) : 855
Packing instruction (passenger aircraft) : 851

IMDG

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,3-CYCLOHEXANEDIMETHANAMINE, DIISOPROPYLNAPHTHALENE ISOMERS)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : 8
EmS Code : F-A, S-B
14.5 Environmental hazards
Marine pollutant : yes

ADR

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,3-CYCLOHEXANEDIMETHANAMINE, DIISOPROPYLNAPHTHALENE ISOMERS)
14.3 Transport hazard class(es) : 8
14.4 Packing group : II
Labels : 8
14.5 Environmental hazards
Environmentally hazardous : yes

RID

14.1 UN number : UN 2735
14.2 UN proper shipping name : POLYAMINES, LIQUID, CORROSIVE, N.O.S.
(1,3-CYCLOHEXANEDIMETHANAMINE, DIISOPROPYLNAPHTHALENE ISOMERS)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

14.3 Transport hazard class(es) : 8

14.4 Packing group : II

Labels : 8

14.5 Environmental hazards

Environmentally hazardous : yes

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - List of substances subject to authorisation - Future sunset date : Not applicable

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

TSCA : On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

Further information

Classification of the mixture:

Skin Corr. 1B	H314
Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® 2031-1 HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 21.02.2017
1.1	24.07.2018	400000005303	Date of first issue: 21.02.2017

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.