


COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)

16_N-50-4-121/133_N

Properties

- Screwed coupling mechanism for sturdy and reliable connection
- IP rating (interface, mated) IP67
- Interface dimensions according IEC/MIL

**Product configuration**

Interface type	Gender	Standard
N	plug	IEC 61169-16_MIL-STD-348A/304_CECC 22210

Interface and material data

Piece parts	Material	Plating
Centre contact	Brass	SUCOPRO Plating
Outer conductor	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Other body part	Brass	SUCOPLATE (R) Plating
Insulator	PTFE (Polytetrafluoroethylene)	
Coupling nut	Brass	SUCOPLATE (R) Plating
Gasket	VMQ (Silicone rubber)	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

Electrical data

Impedance	50 Ω
Interface frequency	18 GHz

Mechanical data

Mating cycles	500
Cable entry centre contact	soldered
Cable entry outer contact	crimped

Environmental data

Operation temperature	-65 °C ... 165 °C
Ingress protection (IP Rating)	Mated / IP67

COAXIAL CONNECTOR, N, 50 Ohm, Right angle cable plug (male)

16_N-50-4-121/133_N

Material compliance			
Item number	Directive / Regulation	Rating	Exemptions / Details
85157254	RoHS 2011/65/EU and (EU) 2015/863	Compliant with exemption	6C
	REACH 1907/2006 Article 33 SVHC	Contains one or more SVHC >0,1%	6C
			CAS: 7439-92-1 Lead

Ordering Information Table		
Item number	Item description	Packaging type
85157254	16_N-50-4-121/133_NE	Single

Suitable cables	
Cable group	X34 - 4 mm / 50 Ohm
	X28 - 4 mm / 50 Ohm
Suitable cables	SPUMA_240-RS-FR
Suitable cables	SPUMA_240
	SPUMA_240-UF
	SPUMA_240-FR-01
	SPUMA_240-FR-AM

Additional Information	
Only as assembly	No

Suitable tools		
Item number	Item description	Type of tool
22543189	76_Z-0-4-1	Crimping dies

HUBER+SUHNER is certified by ISO 9001, ISO 14001, ISO 45001, IATF 16949, AS/EN 9100 and ISO/TS 22163-IRIS. Waiver: Facts and figures herein are for information only and do not represent any warranty of any kind.
DOCUMENT PIM-P3090 / Date of publication: 09.12.2025 / uncontrolled copy