SRT1500RMXLI APC Smart-UPS SRT 1500VA RM 230V



Overview

Lead time	Usually in Stock	<u>.</u>
General		
Provided equipment	CD with software Communication cable Documentation CD Installation guide Rack mounting hardware Rack mounting brackets Rack mounting support rails USB cable Warranty card	
Physical		
Cable length	1.83 m	
Number of rack unit	2U	
Colour	Black	
Depth	50.5 cm	
Height	8.5 cm	
Net weight	21 kg	
Width	43.2 cm	
Input		
Network frequency	4070 Hz auto-sensing	
Plug standard	IEC 60320 C14	
Input voltage limits	50150 V 40% load 80150 V	

Output

Inputvolt_other

Input voltage

Rated power in W

220 V 240 V 230 V

1500 W

Maximum configurable power in W	1500 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13
Bypass type	Built-in bypass
Output voltage	230 V

Conformance

Product certifications	CE
	EAC

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 % non-condensing
Operating altitude	010000 ft
Ambient air temperature for storage	-2050 °C
Storage altitude	0.0015240.00 m
Acoustic level	50 dBA
Heat dissipation	317 Btu/h
IP degree of protection	IP20

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	1
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Liquid value	0

Communications & Management

Free slots	1	
Control panel	Multifunction LCD status and control console	
Alarm	Audible and visible alarms prioritized by severity	
Emergency power off	Yes	

Surge Protection and Filtering

Surge energy rate	432 J	

Packing Units

Package 1 Weight	29.6 kg
Package 1 Height	24.6 cm
Package 1 width	59.4 cm
Package 1 Length	74.9 cm
Number of Units in Package 3	12

Warranty

3 years repair or replace (excluding battery) and 2 years for battery