# **Product datasheet** Characteristics

# LX1FJ110

TeSys F - contactor coil - LX1FJ - 110...120 V AC 40...400 Hz



Price\*: 212.11 GBP



#### Main

	Pri	
Main		
Range	TeSys	
Product or component type	Contactor coil	
Device short name	LX1FJ	
Range compatibility	TeSys F LC1F contactor	
Product compatibility	LC1F400	
Control circuit type	AC 40400 Hz	
[Uc] control circuit voltage	110120 V AC 40400 Hz	
Average resistance	9.8 Ohm inrush at 20 °C 230 Ohm holding at 20 °C	
Inductance of closed circuit	1.35 H	
Operating time	4075 ms closing 100170 ms opening	
Mechanical durability	10 Mcycles	
Operating rate	<= 2400 cyc/h at <= 55 °C	
Complementary		
Coil technology	Without built-in suppressor module	
Control circuit voltage limits	0.851.1 Uc at 55 °C operational 40400 Hz 0.30.5 Uc at 55 °C drop-out 40400 Hz	
Inrush power in VA	1075 VA at 20 °C (cos f 0.9) 40400 Hz	
Hold-in power consumption in VA	15 VA at 20 °C (cos f 0.3) 40400 Hz	
Heat dissipation	14 W at 40400 Hz	
Environment		
Ambient air temperature for operation	> -555 °C	
	1 kg	

#### Complementary

Coil technology	Without built-in suppressor module	-
Control circuit voltage limits	0.851.1 Uc at 55 °C operational 40400 Hz 0.30.5 Uc at 55 °C drop-out 40400 Hz	
Inrush power in VA	1075 VA at 20 °C (cos f 0.9) 40400 Hz	
Hold-in power consumption in VA	15 VA at 20 °C (cos f 0.3) 40400 Hz	
Heat dissipation	14 W at 40400 Hz	2.

#### Environment

Ambient air temperature for operation	> -555 °C
Product weight	1 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0830 - Schneider Electric declaration of conformity
	Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
	Reference not containing SVHC above the threshold
Product environmental profile	Available
	Product environmental
Product end of life instructions	Available
	End of life manual

## Contractual warranty

Warranty period	18 months