

## **Datasheet**

Product Name:	UL1213 18AWG
<b>Product Discription:</b>	UL1213 18AWG
Specification No.:	
Customer's Name:	

PRC	י	D.	Customer's Name:					
	Des	scription			Construction			
Rated V	/oltage:	No	t specified		Conductor	Stranded Sliver plated	copper	
Rated T	emperature:	105°C	C, 60 ℃ Oil		Size(AWG)	18		
Referer	nce Standard:		UL758		Construction(±0.015mm)	19/0.254		
					Stranded Dia.(mm)Ref.	1.27		
					Insulation Material	PTFE		
					Insulation Color	ANY COLO	R	
					Ave Thickness(mm)	0.25		
					Insulation Dia.(±0.10mm)	1.76		
ı								
	M	larking			Remark:			
						Characterist	tice	Customer Approv
Applications					Test Item		Standard Value	
				cal abuse.	Test Material		PTFE(ROHS)	
Oil Resistant 60 deg C.				Í	Insulation resistance(20°C MΩ*m		1000	
					Vol. Tesr(AC.V.60S) (V)		2000	0 - 1 0 01
					Flammability Test		Horizontal flame	Seal & Stamp
					Max.DC Resistance(20℃ Ω/km)		19.0(MAX)	
Version	Description	Drawn by	Approved by	Date				
0	New document issue	Danniel	Jason	14/12/2015				
								Signature:
		1						
								Date:

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.