

Endress+Hauser Vibronic level switch FTL31-AA4U2AAVBJLC

Vibronic point level switch for overflow prevention or pump protection in liquids.



Picture for reference only. Product appearance may vary based on configuration

The Liquiphant FTL31 is a vibronic point level switch for liquids. The device is used for overflow prevention or pump dry-run protection in cleaning systems. The measurement is not affected by conductivity, build-up, turbulence, flow or air bubbles and does not require calibration. The optional IO-Link capability allows easy and time-saving configuration.

- The FTL31 works in areas where other measuring principles are not suitable due to conductivity, build-up, turbulences, flow conditions or air bubbles
- Smallest vibronic sensor on the market

Configuration of FTL31-AA4U2AAVBJLC:

Approval:	AA	Non-hazardous area
Power Supply; Output:	4	10-30VDC; 3-wire PNP
Electrical Connection:	U	Valve plug ISO4400 M16, IP65 NEMA Type 4X Encl.
Sensor Design:	2	Max. process temperature 100oC/212oF
Sensor Type:	AA	Compact version 316L Ra<3.2um/126uin
Process Connection:	VBJ	Thread ASME MNPT3/4, 316L
>>Additional Approval:	LC	WHG overflow protection, leakage, certificate copy

Alternative part number: FTL31-2840/0