



Notice: MECAFLEX 3/4

Index : 2

GUYARD SAS

22-24, rue Lucien Rouzet

Z.A. Villedieu sur Indre/Niherne
36250 NIHERNE FRANCE

Intermediate risks – Category II PPE EN 420:2003+ A1:2009 EN 388:2016+A1:2018

EN ISO 13997:1999

FEATURES:

- Nylon support glove, 3/4 black nitrile coating
- Ventilated back.
- Elasticated cuff with colored overlock to indicate size.

Length from 20 to 26 cm depending on size.

AVAILABLE SIZE:

Size 6 to 10.

PRECAUTIONS FOR USE:

- Wear the gloves on dry and clean hands. It is recommended to carry out a preliminary test of the gloves. Real conditions of use may differ from EU type tests.
- Before each use, check that the gloves do not have any defects, holes, tears, abnormal wear.
- Expiry date: 5 years from the date of manufacture indicated in the glove.

SAFETY COMFORT AND DEXTERITY:

- Dexterity level 5
- The glove does not contain substances at levels that are known or suspected to have adverse effects on the hygiene or health of the user in the conditions of predictable use.

PACKAGING

- In case of unpacking, a copy of the instructions must be attached with the smallest packaging.
- Bag of 10 pairs.
- Box of 200 pairs.

MARKING:

 The CE marking affixed to this glove signifies compliance with the essential health and safety requirements of European Regulation 2016/425 relating to personal protective equipment (PPE). EN 420 :2003+A1 :2009



EN 388:2016+A1:2018

4131X

PERFORMANCE LEVELS:

FN 388 · 2016

<u> 38</u>	<u> 88 :2016</u>	
•	Abrasion :	4/4
•	Blade cut :	1/5
•	Tear:	3/4
•	Puncture:	1/4

• Cutting by sharp objects (ISO 13997)Abrasion: X/F

PROTECTION LIMITS

- Do not use for handling objects of a temperature above 50°C.
- Do not use to handle chemicals products.

RECOMMENDED USES:

- Handling of greasy or oily parts, in the automotive and aerospace industries.
- Machine tool maintenance.
- Household appliances.
- Waste collection: glass, metal cans, plastics.

MAINTENANCE AND STORAGE:

 No special maintenance is recommended. It is advisable to store the products in a cool, dry and ventilated place, keep away from light.

END OF LIFE

 End of life destruction must be controlled and comply with European Traceability and environmental requirements.

EU type certificate issued in accordance with module B Regulation (EU) 2016/425 The EU declaration of conformity is available on

MK n°: 2474

www.guyard-sa.com