

Jun.1.2019 Copyright 2019 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	— °C TO — °C			STORAGE TEMPERATURE RANGE	— °C TO — °C				
	VOLTAGE	—			OPERATING HUMIDITY RANGE	— % TO — %				
	CURRENT	—			APPLICABLE CABLE					
SPECIFICATIONS										
ITEM	TEST METHOD				REQUIREMENTS				QT	AT
CONSTRUCTION										
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				<input type="radio"/>	<input type="radio"/>
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
					<i>F. Taniguchi</i> 01.8.31	<i>S. Wada</i> 01.8.31	<i>Y. Erani</i> 01.8.7	<i>S. Matsuyama</i> 01.08.31		
Unless otherwise specified, refer to JIS C 5402. Note QT:Qualification Test AT:Assurance Test ○:Applicable Test										
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO.		
					CL			RDBD DUMMY PIN		
CODE NO.(OLD)			DRAWING NO.			CODE NO.			1	
CL			ELC4-021186			CL211-0436-6			1	

TO
Q1

