



**Part Number: 9207**

100Ω Twinax, #20-1c TC/1c BC, PO, Duofoil® + 86% TC Braid, CMG

**Product Description**

100 Ohm Twinax, IBM p/n 7362211, 20 AWG stranded (7x28) one tinned copper conductor, one bare copper conductor, polyethylene insulation, polyethylene inner jacket, Duofoil® (100% coverage) + a tinned copper braid shield (85% coverage), PVC outer jacket.

**Technical Specifications**

**Physical Characteristics (Overall)**

**Conductor**

AWG	Stranding	Material	Construction n x D	Nominal Diameter	No. of Conductors	No. of Pairs
20	7x28	TC - Tinned Copper	Stranded	0.037 in	1	1
20	7x28 AWG	BC - Bare Copper	Stranded		1	

Conductor Count:	2
Conductor Size:	20 AWG

**Insulation**

Material	Nominal Diameter
PE - Polyethylene	0.083 in

**Color Chart**

Number	Color
1	Natural (bare copper conductor)
2	Natural (tinned copper conductor)

**Inner Jacket Material**

Material	Nominal Diameter
PE - Polyethylene	0.236 in

**Outer Shield Material**

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Aluminum/Polyester/Aluminum	Duofoil®	100 %
Braid	2	TC - Tinned Copper		85 %

**Outer Jacket Material**

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.33 in

**Electrical Characteristics**

**Conductor DCR**

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
9.5 Ohm/1000ft	1.74 Ohm/1000ft	1.74 Ohm/1000ft

**Capacitance**

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
14.5 pF/ft	23 pF/ft

## Inductance

### Nominal Inductance

0.155 µH/ft

## Impedance

### Nominal Characteristic Impedance

100 Ohm

## High Frequency (Nominal/Typical)

Frequency [MHz]	Nom. Insertion Loss
1 MHz	0.3 dB/100m
10 MHz	1.2 dB/100m
50 MHz	2.8 dB/100m
100 MHz	4.1 dB/100m
200 MHz	6.4 dB/100m
400 MHz	10.2 dB/100m

## Delay

Max. Delay Skew	Nominal Delay	Nominal Velocity of Propagation (VP) [%]
66 ns/100m	1.54 ns/ft	66 %

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

Operating Temp Range:	-30°C To +75°C
-----------------------	----------------

## Mechanical Characteristics

UV Resistance:	Yes - Black only
Bulk Cable Weight:	63 lbs/1000ft
Max Recommended Pulling Tension:	112 lbs
Min Bend Radius/Minor Axis:	3.5 in

## Standards

Customer Part Number Reference Spec:	IBM P/N 7362211
NEC/(UL) Specification:	CL2, CMG
CEC/C(UL) Specification:	CMG
CPR Euroclass:	Eca

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

## Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire
Suitability - Burial:	No
Suitability - Hazardous Locations:	No
Suitability - Indoor:	Yes
Suitability - Outdoor:	Yes - Black only

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 FT4 Loading
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	89207

## Part Number

### Variants

Item #	Color	Footnote
9207 010100	Black	
9207 0101000	Black	C
9207 0101640	Black	C
9207 0103280	Black	C
9207 010500	Black	C
9207 0105000	Black	C
9207 010U500	Black	

Footnote:	C - CRATE REEL PUT-UP.
-----------	------------------------

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.