


Header - PTSM 0,5/ 7-HH0-2,5-SMD R44 - 1808242

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 7, Pitch: 2.5 mm, Color: black, Contact surface: Tin, Mounting: SMD/THT/THR



Key commercial data

Packing unit	600 pc
Minimum order quantity	600 pc
GTIN	 4 046356 697309
Weight per Piece (excluding packing)	1.86 g
Custom tariff number	85369010
Country of origin	Germany
Note	Made to Order (non-returnable)

Technical data

Dimensions

Length	7.5 mm
Height	5 mm
Pitch	2.5 mm
Dimension a	15 mm

General

Range of articles	PTSM 0,5/..-HH-SMD
Insulating material group	IIIa
Rated surge voltage (III/3)	2.5 kV
Rated surge voltage (III/2)	2.5 kV
Rated surge voltage (II/2)	2.5 kV
Rated voltage (III/3)	50 V
Rated voltage (III/2)	160 V
Rated voltage (II/2)	160 V
Connection in acc. with standard	EN-VDE

Header - PTSM 0,5/ 7-HH0-2,5-SMD R44 - 1808242

Technical data

General

Nominal current I _N	6 A
Maximum load current	6 A
Insulating material	LCP
Inflammability class according to UL 94	V0
Color	black
Number of positions	7

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27141190
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC002637

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

UL Recognized / UL Recognized / EAC

Ex Approvals

Header - PTSM 0,5/ 7-HH0-2,5-SMD R44 - 1808242

Approvals

Approvals submitted

Approval details


UL Recognized	
	B
Nominal current I_N	5 A
Nominal voltage U_N	150 V

UL Recognized	
	B
Nominal current I_N	5 A
Nominal voltage U_N	150 V

EAC

Drawings

Drilling diagram



Dimensioned drawing

