Eaton 100514

Catalog Number: 100514

Eaton Moeller series NZM - Molded Case Circuit Breaker. Connection width extension 3p, size 3

General specifications



Eaton Moeller series NZM connection

type

Product Length/Depth

6 mm

Product Width

188 mm

Compliances

IEC UL/CSA

RoHS conform

Catalog Number

100514

EAN

4015081004980

Product Height

80 mm

Product Weight

0.75 kg

Certifications

CSA (Class No. 1432-01)

CSA certified

UL (File No. E140305)

UL (Category Control Number DIHS)

CE marking

CSA-C22.2 No. 5-09

UL489

CSA (File No. 22086)

UL listed IEC60947





Product specifications

Used with

NZM3, PN3, N(S)3

Type

Accessory

Connection width extension

Terminal

Special features

One hole

Amperage Rating

630 A

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Resources

Brochures

eaton-digital-nzm-brochure-br013003en-en-us.pdf eaton-feerum-the-whole-grain-solution-success-story-en-us.pdf

Catalogs

eaton-digital-nzm-catalog-ca013003en-en-us.pdf

Declarations of conformity

DA-DC-03_NZM3

Drawings

eaton-circuit-breaker-connection-nzm-mccb-dimensions-003.eps eaton-circuit-breaker-connection-nzm-mccb-3d-drawing.eps

Installation instructions

eaton-circuit-breakers-nzm3(-4)-xk22-connection-extension-instruction-leaflet-il01219032z.pdf

Installation videos

The new digital NZM Range

Introduction of the new digital circuit breaker NZM

mCAD model

 $nzm3_xkv70.stp$

nzm3_xkv70

Technical data sheets

eaton-nzm-technical-information-sheet

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Frame

NZM3

Suitable for

Copper cable lugs

Three-pole

Number of poles

Three-pole

Terminal capacity (copper strip)

10 segments of 50 mm x 1 mm (2x)

Terminal capacity (flexible cable)

300 mm² (2x)

500 AWG/kcmil (2x)

Terminal capacity (copper busbar)

10 mm x 50 mm (2x)



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia