

1619732

https://www.phoenixcontact.com/gb/products/1619732

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



M23, Cable connector, series: CA, straight, shielded: yes, Screw locking mechanism, No. of pos. : 16, Direction of rotation: Standard, contact connection type: Socket, Crimp connection, cable diameter range: 4 mm ... 6 mm, coding: N, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1243784

Your advantages

- · Safe use in the field, thanks to high degree of protection
- · Connector for flexible on-site assembly
- · Consistent EMC protection for reliable transmission of signals
- · Crimping connection: vibration- and temperature-resistant assembly

Commercial data

Item number	1619732
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	ABRAEA
Product key	ABRAEA
GTIN	4046356821858
Weight per piece (including packing)	92.8 g
Weight per piece (excluding packing)	86.217 g
Customs tariff number	85366990
Country of origin	DE



1619732

https://www.phoenixcontact.com/gb/products/1619732

Technical data

	Order information:	Order 6 x Ø 1 mm crimp contacts separately
Pr	oduct properties	
	Product type	Circular connector (cable-side)
	Data management status	
	Article revision	05

Socket

Connector

Connection 1

Head design

Note	Order information: Order 6 x Ø 1 mm crimp contacts separately
Coding	N
Insulation body material	PA 6.6
Connection method	Crimp connection
Contact switching type	Socket
Application	Signal
Number of positions	16
Direction of rotation	Standard
Connection profile	16
Contact diameter Signal contacts	1 mm
Litz wire cross-section Signal contacts min.	0.08 mm²
Litz wire cross-section Signal contacts max.	1 mm²
Nominal current per signal contact	8 A
Rated voltage Signal contact	48 V AC
Rated surge voltage	1.5 kV
Overvoltage category	III
Degree of pollution	3

Housing

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Type of locking	Screw locking mechanism
Pg screw connection	none
Degree of protection (plugged in)	IP67
Thread type	M23

Seal

External cable diameter	4 mm 6 mm
External cable diameter	7 11111 0 111111



1619732

https://www.phoenixcontact.com/gb/products/1619732

Seal material NBR		
Environmental and real-life conditions Ambient conditions		
Ambient temperature (operation)	-40 °C 125 °C	
Ambient temperature (storage/transport)	15 °C 25 °C	
Permissible humidity (storage/transport)	50 % 65 %	



https://www.phoenixcontact.com/gb/products/1619732



Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/gb/products/1619732

.71	cUL Recognized Approval ID: E335019-20141210			
	Nominal voltage $\mathbf{U}_{\mathbf{N}}$	Nominal current I _N	Cross section AWG	Cross section mm ²
	48 V	3 A	20 - 20	-

7.1	UL Recognized Approval ID: E335019-20141210				
		Nominal voltage U _N	Nominal current I _N	Cross section AWG	Cross section mm ²
		48 V	5 A	20 - 20	-

ᆈᄟ	 Dago	anized



1619732

https://www.phoenixcontact.com/gb/products/1619732

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27440102
ECLASS-12.0	27440116
ECLASS-13.0	27440116
ETIM	
ETIM 9.0	EC002635
UNSPSC	

39121400



1619732

https://www.phoenixcontact.com/gb/products/1619732

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	d4d86b9f-df82-4ddf-9234-fca11a28be2d

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT Ltd Halesfield 13, Telford Shropshire, TF7 4PG 01952 681700 info@phoenixcontact.co.uk