

BOSTIK 1430 CONT ADHESIVE MOD
 Supersedes Date: 06-Feb-2020

 Revision date 17-Feb-2020
 Revision Number 1.06

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK 1430 CONT ADHESIVE MOD
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited
 Common Rd
 ST16 3EH
 Stafford UK
 Tel: +44 (1785) 27 26 25
 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom +44 (1785) 272650
Ireland +353 (1) 8624900 (Monday- Friday 9am-5pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1A - (H317)
Reproductive toxicity	Category 2 - (H361)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 2 - (H411)
Flammable liquids	Category 2 - (H225)

2.2. Label Elements

Contains: Maleic anhydride, Toluene, Methyl ethyl ketone, Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Rosin



Signal word
 DANGER

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Hazard statements

H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
H225 - Highly flammable liquid and vapour

Precautionary statements

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P260 - Do not breathe dust/fume/gas/mist/vapours/spray
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P391 - Collect spillage
P403 + P235 - Store in a well-ventilated place. Keep cool
P501 - Dispose of contents/container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public. Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. .

Reserved for industrial and professional use.

2.3. Other Hazards

In use may form flammable/explosive vapour-air mixture

PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2. Mixtures

Chemical name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Methyl ethyl ketone	201-159-0	78-93-3	15 - 25	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119457290-43-XXXX
Toluene	203-625-9	108-88-3	15 - 25	Skin Irrit. 2 (H315) Repr. 2 (H361d) STOT SE 3 (H336)		01-2119471310-51-XXXX

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

				STOT RE 2 (H373) Asp. Tox. 1 (H304) Flam. Liq. 2 (H225)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	--	10 - <20	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)		01-2119475515- 33-XXXX
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	--	5 - <10	STOT SE 3 (H336) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)		01-2119484651- 34-XXXX
Acetone	200-662-2	67-64-1	5 - <10	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330- 49-XXXX
Zinc oxide	215-222-5	1314-13-2	0.1 - <1	Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119463881- 32-XXXX
Rosin	232-475-7	8050-09-7	0.1 - <1	Skin Sens. 1 (H317)		01-2119480418- 32-XXXX
Maleic anhydride	203-571-6	108-31-6	0.01 - <0.05	Acute Tox. 4 (H302) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Resp. Sens. 1 (H334) Skin Sens. 1A (H317) STOT RE 1 (H372) (EUH071)	Skin Sens. 1A :: C>=0.001%	01-2119472428- 31-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. Get medical attention immediately if symptoms occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a doctor or poison control centre immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. Burning sensation. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitiser. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides.

5.3. Advice for firefighters

Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

SECTION 6: Accidental release measures

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapours or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Keep people away from and upwind of spill/leak.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Dyke far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Remove contaminated clothing and shoes.
General hygiene considerations	Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store locked up. Keep out of the reach of children.
---------------------------	--

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

7.3. Specific end use(s)

Specific Use(s)

Adhesives.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*
Toluene 108-88-3	TWA: 50 ppm TWA: 192 mg/m ³ *	TWA: 192 mg/m ³ TWA: 50 ppm STEL: 384 mg/m ³ STEL: 100 ppm Sk*	TWA: 50 ppm TWA: 191 mg/m ³ STEL: 100 ppm STEL: 384 mg/m ³ Sk*
Acetone 67-64-1	TWA: 500 ppm TWA: 1210 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3630 mg/m ³	TWA: 500 ppm TWA: 1210 mg/m ³ STEL: 1500 ppm STEL: 3620 mg/m ³
Zinc oxide 1314-13-2	-	TWA: 2 mg/m ³ STEL: 10 mg/m ³	-
Rosin 8050-09-7	-	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³	TWA: 0.05 mg/m ³ STEL: 0.15 mg/m ³
Magnesium oxide (MgO) 1309-48-4	-	TWA: 4 mg/m ³ TWA: 5 mg/m ³ TWA: 10 mg/m ³ STEL: 10 mg/m ³ STEL: 12 mg/m ³ STEL: 30 mg/m ³	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Methyl ethyl ketone 78-93-3	-	-	70 µmol/L urine

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)

Methyl ethyl ketone (78-93-3)

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	1161 mg/kg bw/d

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	600 mg/m ³

Toluene (108-88-3)

Type	Long term Systemic health effects worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	384 mg/kg bw/d

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Type	Long term Systemic health effects Local health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	192 mg/m ³

Type	Short term Local health effects Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	384 mg/m ³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2085 mg/m ³

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	300 mg/kg bw/d

Acetone (67-64-1)

Type	Long term Systemic health effects worker
Exposure route	Dermal
Derived No Effect Level (DNEL)	186 mg/kg bw/d

Type	Short term Local health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2420 mg/m ³

Type	Long term Systemic health effects worker
Exposure route	Inhalation
Derived No Effect Level (DNEL)	1210 mg/m ³

Zinc oxide (1314-13-2)

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	5 mg/m ³

Type	worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.5 mg/m ³

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	83 mg/kg bw/d

Rosin (8050-09-7)

Type	worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	10 mg/m ³

Type	worker Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	2131 mg/kg bw/d

Maleic anhydride (108-31-6)

Type	worker Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.4 mg/m ³

Type	worker Short term Systemic health effects
------	---

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.8 mg/m ³

Type	worker Long term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.4 mg/m ³

Type	worker Short term Local health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	0.8 mg/m ³

Derived No Effect Level (DNEL)	
Methyl ethyl ketone (78-93-3)	
Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	412 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	106 mg/m ³

Type	Consumer Local health effects Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	31 mg/kg bw/d

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	447 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	149 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	149 mg/kg bw/d

Acetone (67-64-1)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	200 mg/m ³

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	62 mg/kg bw/d

Zinc oxide (1314-13-2)	
Type	Consumer Long term Systemic health effects
Exposure route	Inhalation
Derived No Effect Level (DNEL)	2.5 mg/m ³

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	83 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	0.83 mg/kg bw/d

Rosin (8050-09-7)	
Type	Consumer Long term Systemic health effects
Exposure route	Dermal
Derived No Effect Level (DNEL)	1065 mg/kg bw/d

Type	Consumer Long term Systemic health effects
Exposure route	Oral
Derived No Effect Level (DNEL)	1065 mg/kg bw/d

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Methyl ethyl ketone (78-93-3)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	55.8 mg/l
Marine water	55.8 mg/l
Freshwater sediment	287.74 mg/l
Marine sediment	287.7 mg/l
Soil	22.5 mg/l

Acetone (67-64-1)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10.6 mg/l
Freshwater - intermittent	21 mg/l
Marine water	1.06 mg/l
Microorganisms in sewage treatment	100 mg/l
Freshwater sediment	30.4 mg/kg dry weight
Marine water	3.04 mg/kg dry weight
Soil	29.5 mg/kg dry weight

Zinc oxide (1314-13-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.0206 mg/l
Marine water	0.0061 mg/l
Freshwater sediment	235.6 mg/kg dry weight
Marine sediment	113 mg/kg dry weight
Soil	106.8 mg/kg dry weight
Microorganisms in sewage treatment	0.1 mg/l

Rosin (8050-09-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.002 mg/l
Marine water	0 mg/l
Sewage treatment plant	1000 mg/l
Freshwater sediment	0.007 mg/l
Marine sediment	0.001 mg/l

Maleic anhydride (108-31-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Microorganisms in sewage treatment	44.6 mg/l
Freshwater sediment	0.334 mg/kg dry weight

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Marine water	0.033 mg/kg dry weight
Soil	0.042 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal Protective Equipment

Eye/face protection Tight sealing safety goggles. Face protection shield.
Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves.
Skin and body protection Antistatic footwear. Wear fire/flame resistant/retardant clothing. Wear appropriate personal protective clothing to prevent skin contact. Suitable protective clothing.
Respiratory protection In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. In case of inadequate ventilation wear respiratory protection.
Recommended filter type: Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid, viscous
Colour Amber, Off-white
Odour Solvent
Odour threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	>= 48 °C	
Flash point	<= -20 °C	CC (closed cup)
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Vapour density	No data available	
Relative density	0.9	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	> 2500 mm ² /s	
Dynamic viscosity	2250 - 2750 mPa s	@ 23 °C
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%) >= 22
VOC Content (%) approx. 700 g/L
Density 0.85 g/cm³

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Irritating to eyes. Causes serious eye irritation.

Skin contact May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity

Acute Toxicity

The following values are calculated based on chapter 3.1 of the GHS document

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Toluene 108-88-3	=5580 mg/kg (Rattus)	= 12000 mg/kg (Oryctolagus cuniculus)	>20 mg/L (Rattus) 4 h
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m ³ (vapour) (rat OECD 403)
Acetone 67-64-1	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Zinc oxide 1314-13-2	>5000 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LC50 (4h) >5.7 mg/l
Rosin 8050-09-7	>2000 mg/Kg (Rattus)	> 2500 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Maleic anhydride 108-31-6	LD50 = 1090 mg/kg (Rattus) OECD 401	= 2620 mg/kg (Oryctolagus cuniculus)	>4.35 mg/L (Rattus) 1 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Component Information			
Maleic anhydride (108-31-6)			
Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Injection	sensitising
Not available	Rat	Inhalation	sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Classification based on data available for ingredients. Contains a known or suspected reproductive toxin. The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Toluene 108-88-3	Repr. 2

Component Information

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Toluene (108-88-3)		
Method	Species	Results
OECD 407	in vivo	reproductive toxicant

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to Micro-organisms	Crustacea	M-Factor	M-Factor (long-term)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)		
Toluene 108-88-3	EC50 72 h = 12.5 mg/L (Pseudokirchneriella subcapitata)	LC50 96 h 5.89 - 7.81 mg/L (Oncorhynchus mykiss flow-through) LC50 96 h = 5.8 mg/L (Oncorhynchus mykiss semi-static)	EC50 = 19.7 mg/L 30 min	EC50: =11.5mg/L (48h, Daphnia magna) EC50: 5.46 - 9.83mg/L (48h, Daphnia magna)		
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics --	-	-	-	EL50 (48h) =3mg/L Daphnia		
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	13.6 mg/l (Pseudokirchneriella subcapitata)	18.3 mg/l (Oncorhynchus mykiss)	-	31.9 mg/l (Daphnia magna)		
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss)	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)		
Zinc oxide 1314-13-2	LC 50 (72Hr) 0.136 mg/L	LC50 (96h) =0.7 mg/L (Danio rerio)	-	LC 50 (48Hr) =0.5 mg/l (Ceriodaphnia dubia)	1	1
Rosin 8050-09-7	EC50: =400mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) >10mg/L (Danio rerio)	EC50 = 31.5 mg/L 30 min	EC50 48 h >100 mg/L (Daphnia magna)		
Maleic anhydride 108-31-6	EC50: =29mg/L (72h, Desmodesmus subspicatus)	LC50 (96h) = 75 mg/L (Oncorhynchus mykiss)	-	EC50: =84mg/L (24h, Daphnia magna)		

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (--)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	83%	Readily biodegradable

Zinc oxide (1314-13-2)			
Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Methyl ethyl ketone 78-93-3	0.3	-
Toluene 108-88-3	2.7	-
Hydrocarbons, C6, isoalkanes, <5% n-hexane --	3.6	501
Acetone 67-64-1	-0.24	0.69
Maleic anhydride 108-31-6	-2.61	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Methyl ethyl ketone 78-93-3	The substance is not PBT / vPvB
Toluene 108-88-3	The substance is not PBT / vPvB PBT assessment does not apply
Acetone	The substance is not PBT / vPvB

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

67-64-1	
Zinc oxide 1314-13-2	The substance is not PBT / vPvB PBT assessment does not apply
Rosin 8050-09-7	The substance is not PBT / vPvB Further information relevant for the PBT assessment is necessary
Maleic anhydride 108-31-6	The substance is not PBT / vPvB PBT assessment does not apply

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances 15 01 10*: Packaging containing residues of or contaminated by dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition). The information shown here, may not always agree with the bill of lading shipping description for the material.

Land transport (ADR/RID)

14.1 UN Number	UN1133
14.2 Proper Shipping Name	Adhesives, Environmentally Hazardous
14.3 Transport hazard class(es)	3
Labels	3
14.4 Packing Group	II
Description	UN1133, Adhesives, 3, II, (D/E), Environmentally Hazardous
14.5 Environmental hazards	Yes
14.6 Special Provisions	640D
Classification Code	F1
Tunnel restriction code	(D/E)
Limited Quantity (LQ)	5 L
ADR Hazard Id (Kemmler Number)	33

IMDG

14.1 UN number	UN1133
14.2 Proper Shipping Name	Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), Marine Pollutant
14.3 Transport hazard class(es)	3
14.4 Packing group	II
Description	UN1133, Adhesives (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 3, II, (-20°C c.c.), Marine Pollutant
14.5 Marine Pollutant	P.

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

14.6 Special Provisions None
Limited Quantity (LQ) 5 L
EmS-No. F-E, S-D
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number UN1133
14.2 Proper Shipping Name Adhesives
14.3 Transport hazard class(es) 3
14.4 Packing group II
Description UN1133, Adhesives, 3, II
14.5 Environmental hazards Yes
14.6 Special Provisions A3
Limited Quantity (LQ) 1 L
ERG Code 3L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Toluene	108-88-3	48.

48 . Reserved for industrial and professional use. Adhesives or spray paint shall not be placed on the market containing above substance equal to or greater than 0.1% where supplied to the general public.

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS
P5b - FLAMMABLE LIQUIDS
P5c - FLAMMABLE LIQUIDS
E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Persistent Organic Pollutants

Not applicable

National Regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
EUH071 - Corrosive to the respiratory tract
H225 - Highly flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways
H314 - Causes severe skin burns and eye damage
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H319 - Causes serious eye irritation
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H336 - May cause drowsiness or dizziness
H361d - Suspected of damaging the unborn child
H372 - Causes damage to organs through prolonged or repeated exposure
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H411 - Toxic to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 17-Feb-2020

Indication of changes

Revision note SDS sections updated: 14.

Training Advice Provide adequate information, instruction, and training for operator

SAFETY DATA SHEET

BOSTIK 1430 CONT ADHESIVE MOD
Supersedes Date: 06-Feb-2020

Revision date 17-Feb-2020
Revision Number 1.06

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet