

RING TONGUE TERMINALS WITH CONTAINED PALM A37B-M10/24.5

for L.V. circuit breakers for copper conductors

□

This range of lugs features contained palm width. Our lugs have been specifically developed for application on L.V. circuit breakers with reduced space terminal blocks. In fact the contained palm width allows an immediate and easier installation. Our lugs are manufactured from electrolytic copper tube. The specifically designed section of the barrel and the choice of principal dimensions are optimising the best combination of mechanical strength and electrical conductivity. Our lugs are annealed to guarantee optimum ductility and are electrolytically tinplated to avoid oxidation. The barrel is provided with an internal taper to ease the introduction of the conductor; furthermore, its length grants a comfortable and correct positioning between dies, during crimping operations. Each lug palm is marked with the Cembre logo and part number.

Manufactured from electrolytic copper tube Cu-OF CW008A conform to UNI EN 13600

Certificates

□ E125401

RING TONGUE TERMINALS WITH CONTAINED PALM A37B-M10/24.5

Technical characteristics

	Properties
Width	0.96 in.
Length	3.03 in.
Diameter	0.76 in.
Hole diameter	0.41 in.
Pack qty	30
Min. pack qty	15
M	0.71 in.
N	0.35 in.
Maximum diameter of the stripped cable	0.76 in.
Without inspection hole	Y
Material (Body)	ETP Copper elettrolyticaly tinned
Material (Seam)	ETP Copper elettrolyticaly tinned

□ □