

Power Double Lock

TE Internal #: 2005247-6

Housing, Plug, Crimp, Wire-to-Wire, UL 94V-0, 2 Position, Power

Double Lock, Rectangular Wire & Cable Connectors & Housings

View on TE.com >



Connectors > Rectangular Connectors > Standard Rectangular Connectors > Glow Wire Power Double Lock Plug











Connector Product Type: Housing

Connector & Housing Type: Plug

Termination Method to Wire & Cable: Crimp

Connector System: Wire-to-Wire

Contact Retention Within Housing: Without

All Glow Wire Power Double Lock Plug (55)

Features

Product Type Features

Compatible With Discrete Wire Type	Stranded
Connector Product Type	Housing
Connector & Housing Type	Plug
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Signal Positions	0
Number of Power Positions	0
Number of Positions	2
Number of Rows	1

Operating Voltage	50 VAC, 300 VAC



Body Features

Primary Product Color	Blue
Contact Features	
Contact Layout	Inline
Contact Type	Receptacle
Contact Retention Within Housing	Without
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA 66
Centerline (Pitch)	3.96 mm[.156 in]
Usage Conditions	
Operating Temperature Range	-30 - 65 °C[-22 - 149 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Compatible With Agency/Standards Products	CNR, USR
Compatible With Approved Standards Products	CSA/C22.2 No. 182.3-M1987, UL 1977
Glow Wire Rating	GWT 750°C (Without Flame)
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



	EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
PPIII.	Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Product Compliance Disclaimer

Solder Process Capability

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | Power Double Lock



Connector Contacts(24)



Connector Hardware(14)



PCB Headers & Receptacles(43)



Not applicable for solder process capability

Power Contacts(24)





Rectangular Connector Housings (240)



Rectangular Power Connectors(283)



Standard Rectangular Connectors(240)

Customers Also Bought



TE Part #1-368575-1
PDL 4P PLUG 3.96 D/R(GWT) NAT



TE Part #2237149-2 8POS,TAB0.64X0.64,HDR ASSY, 90DEG,SMD




TE Part #2362662-1 8POS,0.50,HDR ASSY,90DEG,KEY-A, KEY-D



TE Part #1747063-1 GRACE INERTIA CONN 2.5 REC CON



TE Part #1-368589-4
PDL 4P CAP 3.96 D/R P/M(GWT) Y



TE Part #177915-1
AMP POWER DBL LOCK REC (L)



TE Part #2005250-1
PDL 3P CAP 3.96 P/M(GWT) NAT



TE Part #2315739-3 8POS,0.50,HDR ASSY,180DEG,COD C, HSI





Documents

Product Drawings
PDL 2P PLUG 3.96(GWT) BLU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2005247-6_B.2d_dxf.zip

Housing, Plug, Crimp, Wire-to-Wire, UL 94V-0, 2 Position, Power Double Lock, Rectangular Wire & Cable Connectors & Housings



English

Customer View Model

ENG_CVM_CVM_2005247-6_B.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2005247-6_B.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Engineering Report

English

Agency Approvals

UL Report

English