## SIEMENS

## Data sheet

## 8WA1205



Through-type terminal thermoplast Screw terminal on both sides Single terminal 16 mm, Sz. 35  $\,$ 

Model			
product brand name	SENTRON		
product designation	Terminal blocks		
design of the product	through-type terminal		
product variations	through-type terminal, for mounting on mounting rail acc. to IEC 60715		
design of terminal terminal levels internally linked	No		
General technical data			
terminal contact spacing	16 mm		
operating voltage rated value	800 V		
Protection class			
combustibility class according to UL 94	V2		
Main circuit			
operational current rated value	125 A		
Appearance			
color	beige		
Product details			
product component required end cover plate	No		
Number			
number of terminal levels	1		
number of terminal points per terminal level	2		
Connections			
stripped length	17 mm		
connectable conductor cross-section solid			
• minimum	4 mm <sup>2</sup>		
• maximum	35 mm²		
connectable conductor cross-section stranded			
• minimum	10 mm <sup>2</sup>		
• maximum	35 mm²		
connectable conductor cross-section finely stranded			
<ul> <li>with core end processing minimum</li> </ul>	6 mm <sup>2</sup>		
<ul> <li>with core end processing maximum</li> </ul>	35 mm²		
<ul> <li>without core end processing minimum</li> </ul>	6 mm <sup>2</sup>		
<ul> <li>without core end processing maximum</li> </ul>	35 mm²		
tightening torque with screw-type terminals			
• minimum	2.5 N·m		
• maximum	3 N·m		
type of connection 1	screw-type terminal		
type of connection 2	screw-type terminal		
position of the terminal	lateral		
Mechanical Design			

la stadat outle la cosa d'una d'							
height with lowest-profile installation			26 mm				
length		53 mm					
fastening method		DIN rail 35 mm					
net weight			65 g				
material of the insulating body			Thermoplast				
Environmental conditions							
ambient temperature du	iring operation						
• minimum			-25 °C				
• maximum		55 °C					
Approvals Certificates							
General Product Ap-	Declaration of Con-	other			Environment		
proval	formity						
Proval	tormity	Confirmation	D	<u>Miscellaneous</u>	Environmental Con- firmations		

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1205

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/8WA1205

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=8WA1205

**CAx-Online-Generator** 

http://www.siemens.com/cax

**Tender specifications** 

http://www.siemens.com/specifications

last modified:

4/20/2023 🖸