

## **ToLEDo Retro Candle**

## ToLEDo RT Candle 420LM E27 SL

### 0027284



### Range features

- LED Chip technology using a virtual filament design which creates a warm ambiance similar to traditional lamps
- First lamp of its type to achieve A++ rating up to 134 lm/W
- Suitable for replacement of up to 60W incandescent lamps
- Available in clear and satin versions
- Packed in individual boxes (SL) or in blisters (BL)
- Up to 90% energy saving compared to incandescent lamps
- Cooler burning versus standard LED lamps
- Dimensional compatibility with all fixtures
- Average lifetime from 6000 hours up to 15 000 hours
- 3 years warranty
- WARNING: If the outer glass jacket is broken conductive parts may still be active. Lamps must not be touched before making sure the mains cable is not live. Switch off the main electrical supply before replacing lamp!

#### **PRODUCT OVERVIEW**

o Candle
349



# **ToLEDo Retro Candle**

ToLEDo RT Candle 420LM E27 SL

# 0027284

### **DATA TABLE**

General	l data

Technology	LED
Ordering number	0027284
Dry applications use only	Yes
Energy saving lamp	Yes
Average life (Rated) (h)	6000
Average life (Nominal) (h)	6000
Energy class	A++
Lamp finish	Clear
Lamp shape	Candle
Dim m able	No
Cap/Bas e	E27
Туре	ToLEDo Retro Candle
EAN code	5410288272849
Range features	LED Chip technology using a virtual filament design which creates a warm ambiance similar to traditional lamps. First lamp of its type to achieve A++ rating - up to 134 lm/W. Suitable for replacement of up to 60W incandescent lamps. Available in clear and satin versions. Packed in individual boxes (SL) or in blisters (BL). Up to 90% energy saving compared to incandescent lamps. Cooler burning versus standard LED lamps. Dimensional compatibility with all fixtures. Average lifetime from 6000 hours up to 15 000 hours. 3 years warranty. WARNING: If the outer glass jacket is broken conductive parts may still be active. Lamps must not be touched before making sure the mains cable is not live. Switch off the main electrical supply before replacing lamp!
Product name	ToLEDo RT Candle 420LM E27 SL
Lamp mercury content (mg)	0
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Control gear availability	No
General application	Hospitality; Residential & Consumer
Intended purpose	No
No. of switching cycles before premature failure (min)	>5000
Special purpose lamp	No
Transformer required	No
Optimal operating condition (°C)	25

© Havells Sylvania | Date Printed: 26 Jun 2015 | Data Last Updated: 24 Jun 2015 Page 2 of 3



# ToLEDo Retro Candle

# ToLEDo RT Candle 420LM E27 SL

# 0027284

### Optical data

Light colour	Homelight
CRI (Ra)	80
Suitable for accent lighting	No
Colour temperature (K)	2700
Luminous flux (Rated) (lm)	420
Luminous flux (Nominal) (lm)	420
Lumen maintenance at end of nominal life (%)	80
Chromaticity coordinate Y	-1
Chromaticity coordinate X	-1
Adjustable chromaticity	No

#### Electrical data

kWh per 1000 hours burning time	4
Efficacy (Rated) (Im/w)	105
Watt (Nominal) (W)	4
Watt (Rated) (W)	4
Equivalent watt (W)	37
Voltage (V)	230-240
Drive current (mA)	32
Lamp power factor	0.5

### Physical data

Lamp Length (mm) - C/L	92
Lamp dimension equal to filament lamp equivalent	Yes
Diameter (mm)	35

### **ENERGY LABEL**



© Havells Sylvania | Date Printed: 26 Jun 2015 | Data Last Updated: 24 Jun 2015