



PRODUCT NUMBER: 1032373
Miller kernmantel edge shock absorbing lanyard 1,5 meters with a twist lock + GO55 karabiner.

Miller kernmantel edge shock absorbing lanyard 1,5 meters with a steel twist lock and a GO55 steel scaffold hook karabiner.



Overview

Reference Number

1032373

Product Type

Fall Protection

Range

Shock Absorbing Lanyards

Line

Cut resistant

Brand

Miller by Honeywell

Industry

- Building and Construction

Product Use

Fall arrest lanyards will allow the worker to fall but prevents him from hitting the next lower level, such as the ground, (if well attached). It includes a shock absorber that dissipates the forces exerted on the body in the case of a fall to stay below 6 KN.

This single lanyard is edge tested for safe working on edges ($r \geq 0,5$ mm).

Features & Benefits

Feature

New design : * Lanyard manufactured with a light green rope with black stripes, which are highly visible from a distance increasing safety at work. * The stitches are highly visible which facilitates the safety check before use.

Benefit

* Lanyard edge tested : manufactured with high quality kernmantel rope and have special. * The rope is 2 times more resistant to the abrasion than the other standard ropes.

Technical Description

Length

1,5 M

Weight

0,990 KG

Breaking Strength

> 22 KN

Operating Temperature

-30°C to +50°C

Rope

Rope Raw Material

Kernmantel Ø 11 mm polyester sheath and polyamide core

Connector

Connector Type

Twist lock karabiner

Connector Raw Material

steel

Connector Opening

17 mm

Connector Breaking Strength

> 22 KN

Connector Standard

EN 362 : 2004

Connector

Connector Type

GO55 scaffold hook

Connector Raw Material

steel

Connector Opening

55 mm

Connector Breaking Strength

> 25 KN

Connector Standard

EN 362 : 2004

Energy Absorber

Energy Absorber Raw Material

Resistant webbing shock absorber with protective cover

Certifications

 E.C. Declaration of Conformity**EC Category PPE**

3

Quality Assurance

ISO 9001 / 2000

EC Attestation

 EC Attestation

EC Attestation Number

0082-490-160-06-13-0169

Certifications

- EN 355 / VG 11 PFE 11.074

REACH

EU Regulation 1907/2006 (REACH) Compliance

The substance(s) listed below may be contained in this product above the threshold level of 0.1% by weight of the listed article.

Product Reference Sold in Europe	Substance > 0.1%
Substance Name	CAS Number
No Substance Content	

Additional Information

User Manual

NT90004208 IND L

User Information Sheet

User manual

Maintenance

Life Cycle

Life expectancy of our lanyards is 10 years from the date of manufacture.

Care Instructions

Some factors can contribute to reduce the performance or life expectancy of the product:

- Incorrect stocking
- Incorrect use
- Stopping a fall
- Mechanical deformation or cut
- Contact with chemical products (an acid or a base)
- Exposure to extreme heat sources > 60°C
- Exposure to UV rays

Please remember that:

- the product must be checked at least once a year by a qualified person. This inspection must be registered.
- before each use, the product must be visually inspected by the user.

The compulsory annual inspection will be the deciding factor as to whether your PPE should be put back into service or not.



Centre d'Essais de Fontaine
17, Boulevard Paul Langevin
38600 FONTAINE - France
Tél. +33.(0)4.76.53.52.22
Fax +33.(0)4.76.53.32.40
lab38chute@apave.com

En exécution de la directive 89/686/CEE du 21 décembre 1989 modifiée concernant le rapprochement des législations des états membres relatives aux équipements de protection individuelle et des dispositions pertinentes du code du travail, portant transposition de cette directive en droit français,
In enforcement of amended directive 89/686/EEC of 21st of December 1989 on the approximation of the laws of the Members States relating to personal protective equipment and in enforcement of relevant requirements of the French labour code, providing for the transcription of this directive into French regulations.

APAVE SUDEUROPE SAS, organisme notifié, identifié sous le numéro 0082, attribue l'
APAVE SUDEUROPE SAS, notified body, identified under number 0082, awards the

ATTESTATION D'EXAMEN CE DE TYPE

(EC Type examination certificate)

N° 0082/490/160/06/13/0169

A l'équipement suivant :
To the following equipment:

➤ Type d'équipement : **EPI de catégorie III - Absorbent d'énergie**
Category of equipment: PPE category III - Energy absorber

➤ Marque commerciale : **MILLER®**
Trademark

➤ Equivalence : la présente attestation est attribuée aux deux modèles suivantes :
Equivalence: this certificate is awarded to the two following models:

- Modèle : **LONGE ABSORBEUR DRISSE NUE** : Absorbent d'énergie intégrant une longe simple fixe
Model Energy absorber integrating a fixe single lanyard
- Modèle : **LONGE ABSORBER DRISSE XM+CONNECTEURS** : Absorbent d'énergie intégrant une longe fixe simple avec connecteurs
Model Energy absorber integrating a fixe single lanyard with connectors

➤ Fabricant : **HONEYWELL FALL PROTECTION France SAS – 35-37 Rue de la Bidauderie – 18100 VIERZON Cedex France**
Manufacturer

➤ Description : Absorbent d'énergie à sangle à déchirement, en polyamide 6, largeur 30 mm, longueur 0,18 m, protégé par une gaine thermoretractable, intégrant une longe fixe simple en cordage polyester/polyamide, diamètre 11 mm. A chaque extrémité de la longe, une boucle cousue cossée, soit de référence 90001626, soit 90022716, protégée par une gaine thermoretractable de référence 90002874 ou 90022718. L'absorbent d'énergie peut être équipé des connecteurs intégrés suivant : 1006452 ou 1018973 ou 1018972 ou 1018977 ou 1009249 ou 1018976 ou 1029701 ou 1004300. Longueurs disponibles de 0.5 m à 2m (description détaillée dans le rapport d'examen CE de type 13.6.0234).

Description: Energy absorber with wrench webbing, in polyamide 6, width 30 mm, length 0.18 m, protected by a thermoretractable sheath integrating a single fixe lanyard rope, in polyester/polyamide, diameter 11mm. On each end of lanyard, a sewn thimble buckle, either of reference 90001626 or 90022716 protected by a thermoretractable sheath of reference 90002874 or 90022718. The energy absorber can be equipped with integrated connector of reference: 1006452 or 1018973 or 1018972 or 1018977 or 1009249 or 1018976 or 1029701 or 1004300. Available lengths from 0.5m to 2m (detailed description in EC type examination report 13.6.0234).

➤ Référentiel technique utilisé : EN 355 : 2010.
Technical referential used

Date : 6 juin 2013
Date: the 6th June 2013

Document authentifié par tampon sec
Document certified by dry stamp

Le Responsable du Centre d'Essais de Fontaine – Certification EPI
Head of Fontaine Testing-Centre – PPE Certification

Vincent MAILLOCHEAU

NOTA : Toute modification apportée au matériel neuf objet de la présente attestation d'examen CE de type doit être portée à la connaissance de l'organisme habilité en application de l'article R4313-38 du code du travail.

Any modification brought about a new equipment covered by this CE type examination certificate must be notified to the body in enforcement of article R4313-38 of French labour code.

Cette attestation comporte une page. Elle est établie en deux exemplaires originaux transmis au demandeur. Aucun duplicata ne sera délivré.
This certificate includes one page. This certificate is edited in two original copies. No duplicate will be issued.



E.C. Declaration of Conformity

The manufacturer or its legal representative supplier in the European Community:

Honeywell Safety Products Europe

Declares that the Personal Protective Equipment described here after conforms to the provisions of the European Council Directive 89/686/CEE:

Designation: Miller kernmantel edge shock absorbing lanyard 1,5 meters with a twist lock + GO55 karabiner.

Reference: 1032373

Standard(s): EN355

This PPE is the object of the below EC examination certificate n°:

And is subject to the procedure set out in Article 11 point B of Directive 89/686/EEC under the supervision of the below notified body.

Delivered by:

APAVE SUDEUROPE SAS

BP 3

33370

ARTIGUES près BORDEAUX

France

Drawn up in , on the 17/06/2015

By: Frederic Wagner

Division: Fall Protection

ZI Paris Nord II 33, rue des Vanesses BP 50288 95958 Roissy CDG France

Tel: +33 (0) 49 90 79 79 Fax: +33 (0)1 49 90 79 80

www.honeywellsafety.com