



Technical data

4T-07098/07204

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

KIT CONTENT

4T-07204, 4T-07098

VISUAL (S)



4T-07098/07204
Single row tapered roller bearings



PRODUCT DEFINITION	
Brand	NTN
d - Internal diameter	24,981 mm
D - External diameter	51,994 mm
B - Bearing/Inner ring width	14,26 mm
C - Outer ring width	12,7 mm
T - Total width	15,011 mm
a - Charge load application point	18 mm
rs - Min fillet radius	1,5 mm
r1s - Min fillet radius	1,3 mm
Mass	0,14 kg

PRODUCT PERFORMANCE	
C - Dynamic load	28,8 kN
C0 - Static load	27,9 kN

PRODUCT PERFORMANCE

A2 - Rating life coefficient	1
e - Coefficient	0.4
Y0 - Static axial load coefficient	0.82
Y2 - Upper axial load coefficient	1.49
N lim - Oil lubrication limit speed	10000 tr/min
N lim - Grease lubrication limit speed	7500 tr/min
Tmin - Min operating temperature	-40 °C
Tmax - Max operating temperature	120 °C

ABUTMENT

da max - Max shoulder diameter IR	29 mm
db min - Min IR shoulder diameter	31 mm
Da max - Max shoulder diameter OR	48 mm
Db min - Min OR shoulder diameter	45 mm
ra max - Max fillet radius	1,5 mm
r1a - Max fillet radius	1,3 mm

KIT COMPONENT

Cone designation	4T-07098
Cup designation	4T-07204

ESHOPDONOTDISPLAY

Tracepart	Oui/Yes
Reference	4T-07098/07204
Image	TRB_1.jpg, TRB_2.jpg, TRB_3.jpg
ULTAGE	Non/No



ESHOPDONOTDISPLAY

Rolling element material

Acier de cémentation

INDUSTRY CALCUL FACTORS

Equivalent dynamic radial load

$P = X.F_r + Y.F_a$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$P_o = X_o.F_r + Y_o.F_a$

X _o	Y _o
0.5	Y0

If $P_o \leq F_r$, then use $P_o = F_r$

The values for e, Y2 and Y0 are shown in the above table

