Product Information



SILKAIR VG 22 AIRLINE OIL

ISO VG22 pneumatic airline lubricant

Description

SILKAIR VG 22 AIRLINE OIL is a premier quality airline oil of naturally high viscosity index intended for the lubrication of pneumatic tools, valves and associated equipment. The product is intended for use in systems where it may be necessary to draw off any separated water. SILKAIR VG 22 AIRLINE OIL is inhibited to minimise thermal degradation and foaming, and protect against corrosion and deposit formation. The product is formulated to ensure rapid formation of a mist for lubrication of downstream pneumatic equipment.

In instances where low discharge temperatures are known to cause freezing of exhausts SILKAIR ICE FREE should be considered, (See separate sheet).

Application

SILKAIR VG 22 AIRLINE OIL is designed specifically as an airline lubricant for use on pneumatic tools and may also be used as a hydraulic fluid where appropriate.

Advantages/Benefits

- Dyed blue for ease of identification
- Provides enhanced corrosion protection
- · Readily separates from water
- May also be used as a hydraulic medium for certain applications
- · Contains no added silicon

August 2013 GDUK Page 1 of 2

Product Information



CHARACTERISTICS: SILKAIR VG 22 AIRLINE OIL

Characteristics	Unit		Test Method	
Appearance	Clear blue fluid			
Kinematic viscosity at 100°C at 40°C	mm²/s mm²/s	4.32 22.08	IP71	
VI		95 min.		
Flash point (PMCC)	°C	185	IP34	
Pour point	°C	-30	IP15	
Specific gravity at 15.6°C		0.870	IP160	

August 2013 GDUK Page 2 of 2

Tel +44-1782 -20 37 00 Fax +44-1782 -20 20 73 contact-uk@fuchs-oil.com

