

Auxiliary contact, Multi9 M9A, SD, 1 C/O, 2mA to 100mA, 24VAC to 250VAC, 24VDC to 220VDC, bottom connection

M9A26917

EAN Code: 3606482129214

### Main

range of product	Multi9	
Product or component type	Fault contact	
Device short name	SD	
Signal contacts composition	1 C/O	
[In] rated current	2100 mA at 24240 V, AC 50/60 Hz 2100 mA at 24 V, DC 2100 mA at 48 V, DC 2100 mA at 60 V, DC 2100 mA at 130 V, DC 2100 mA at 220 V, DC	
9 mm pitches	1	
Standards	EN/IEC 60947-5-1 EN/IEC 60947-5-4 GB/T 14048.5 EN 62019-2 UL 1077 UL 489 C22.2 No. 5 C22.2 No. 235	
Product certifications	CE UKCA UL	
Quality labels	EAC CCC	

## Complementary

Operating mode	Daisy chain up to 100 devices	
[Ui] rated insulation voltage	500 V	
[Uimp] rated impulse withstand voltage	4 kV	
Local signalling	Mechanical indicator	
Mounting mode	Clip-on	
Mounting location	Left side of circuit-breaker	
Mounting support	DIN rail	
Comb busbar and distribution block compatibility	Top: YES	
Height	85 mm	
Width	9 mm	
Depth	68 mm	
Product weight	29 g	

Colour	Grey	
Connections - terminals	Screw clamp terminal (bottom) 1 cable(s) 2.5 mm² - rigid Screw clamp terminal (bottom) 2 cable(s) 1.5 mm² - rigid	
Wire stripping length	9 mm	
Tightening torque	1 N.m bottom	

## **Environment**

IP degree of protection	IP20
Pollution degree	3
Tropicalisation	2
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4085 °C

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	7.700 cm
Package 1 Length	9.500 cm
Package 1 Weight	38.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.500 cm
Package 2 Width	10.200 cm
Package 2 Length	23.500 cm
Package 2 Weight	518.000 g
Unit Type of Package 3	\$03
Number of Units in Package 3	120
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	5.730 kg

# Logistical informations

Country of origin CN

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

#### Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	1
Environmental Disclosure	Product Environmental Profile

### **Use Better**

Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration

### **Use Again**

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins