

line paralleling module , Altivar Process Modular, 500...690V, liquid cooled

APM1L0LPMY6

EAN Code: 3606481012814

Main

Range of product	Altivar Process Modular	
Product or component type	Power module	
Mounting mode	Cabinet mount	
IP degree of protection	IP00 conforming to IEC 61800-5-1 IP21 (for cabinet integration) conforming to IEC 61800-5-1 IP66 (for cabinet integration) conforming to IEC 61800-5-1	
Supply frequency	5060 Hz - 55 %	
Network number of phases	3 phases	
[Us] rated supply voltage	500690 V - 1010 %	

Complementary

Degree of protection	UL type 1 conforming to UL 61800-5-1 (cabinet integration) UL type 12 conforming to UL 61800-5-1 (cabinet integration)	
Width	230 mm	
Height	348 mm	
Depth	350 mm	
Net weight	40 kg	
Marking	CE	

Environment

Insulation resistance	> 1 MOhm 500 V DC for 1 minute to earth	
Operating position	Vertical integrated in cabinet	
Electromagnetic compatibility	Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test level 3 conforming IEC 61000-4-3 Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4 1.2/50 μs - 8/20 μs surge immunity test level 3 conforming to IEC 61000-4-5 Conducted radio-frequency immunity test level 3 conforming to IEC 61000-4-6	
Pollution degree	2 conforming to IEC 61800-5-1	
Vibration resistance	1.5 mm peak to peak (f= 213 Hz) conforming to IEC 60068-2-6 0.5 gn (f= 13200 Hz) conforming to IEC 60068-2-6	
Shock resistance	4 gn for 11 ms conforming to IEC 60068-2-27	
Relative humidity	595 % without condensation conforming to IEC 60068-2-3	
Ambient air temperature for operation	-1040 °C (without derating) 4050 °C (with derating factor)	
Ambient air temperature for storage	-4070 °C	

Rates duty January 2016

Operating altitude	<= 4800 m with current derating above 1000m Chemical pollution resistance class 3C3 conforming to IEC 60721-3-3 Dust pollution resistance class 3S3 conforming to IEC 60721-3-3	
Environmental characteristic		
Standards	UL 61800-5-1	
	IEC 61800-3	
	IEC 61800-5-1	
	IEC 61000-3-12	
	IEC 60721-3	
	IEC 61508	
	IEC 13849-1	
Product certifications	TÜV	
	cULus	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.000 cm
Package 1 Width	59.000 cm
Package 1 Length	79.000 cm
Package 1 Weight	40.000 ka



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∇ Environmental footprint	
Carbon footprint (kg.eq.CO2 per CR, Total Life cycle)	9688
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
REACh Regulation	REACh Declaration

Use Again

○ Repack and remanufacture	
Circularity Profile	End of Life Information
Take-back	No
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins