



**SAFETY DATA SHEET**  
EPOXY PUTTY 2122 RESIN

Page: 1

Compilation date: 12/08/16

Revision No: 7

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** EPOXY PUTTY 2122 RESIN

**Product code:** 307434

**Synonyms:** EP2122 RESIN

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** Part A (resin) of a two pack, epoxy repair paste; to be used only with the corresponding Part B (catalyst) component.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Kopex-Ex

CMG House

Station Road

Coleshill

Birmingham

B46 1HT

UK

**Tel:** +44 (0) 1675 468 217

**Fax:** +44 (0) 1675 468 280

**Email:** [Sales@kopex.co.uk](mailto:Sales@kopex.co.uk)

**1.4. Emergency telephone number**

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205

**Most important adverse effects:** Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H412: Harmful to aquatic life with long lasting effects.

EUH205: Contains epoxy constituents. May produce an allergic reaction.

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 2

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.  
P273: Avoid release to the environment.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see information on this label).  
P332+313: If skin irritation occurs: Get medical advice/attention.

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### TALC

| EINECS    | CAS        | PBT / WEL  | CLP Classification | Percent |
|-----------|------------|--|--------------------|---------|
| 238-877-9 | 14807-96-6 | Substance with a Community workplace exposure limit. | -                  | 10-30%  |

##### LIMESTONE

|           |           |  |   |        |
|-----------|-----------|--|---|--------|
| 215-279-6 | 1317-65-3 | Substance with a Community workplace exposure limit. | - | 10-30% |
|-----------|-----------|--|---|--------|

##### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

|           |            |   |  |        |
|-----------|------------|---|--|--------|
| 500-033-5 | 25068-38-6 | - | Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411 | 10-30% |
|-----------|------------|---|--|--------|

##### SILICA QUARTZ

|           |            |  |   |        |
|-----------|------------|--|---|--------|
| 238-878-4 | 14808-60-7 | Substance with a Community workplace exposure limit. | - | 10-30% |
|-----------|------------|--|---|--------|

##### MAGNESIUM CARBONATE

|           |          |  |   |       |
|-----------|----------|--|---|-------|
| 208-915-9 | 546-93-0 | Substance with a Community workplace exposure limit. | - | 1-10% |
|-----------|----------|--|---|-------|

## Section 4: First aid measures

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 3

## 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS.  
Do not create dust.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 4

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**TALC**

**Workplace exposure limits:**

**Respirable dust**

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA          | 15 min. STEL |
|-------|------------|--------------|---------------------|--------------|
| UK    | -          | -            | 1 mg/m <sup>3</sup> | -            |

**LIMESTONE**

|    |   |   |                     |   |
|----|---|---|---------------------|---|
| UK | - | - | 4 mg/m <sup>3</sup> | - |
|----|---|---|---------------------|---|

**SILICA QUARTZ**

|    |   |   |                       |   |
|----|---|---|-----------------------|---|
| UK | - | - | 0.1 mg/m <sup>3</sup> | - |
|----|---|---|-----------------------|---|

**MAGNESIUM CARBONATE**

|    |   |   |                     |   |
|----|---|---|---------------------|---|
| UK | - | - | 4 mg/m <sup>3</sup> | - |
|----|---|---|---------------------|---|

### DNEL/PNEC Values

**DNEL / PNEC** No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not required.

**Hand protection:** Protective gloves. PVC gloves. Neoprene gloves. Nitrile gloves. Butyl gloves.

Breakthrough time of the glove material > 1 hour.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Solid

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 5

**Colour:** Dark red

**Odour:** Barely perceptible odour

**Solubility in water:** Insoluble

**Flash point°C:** > 100

**Relative density:** 1.92 - 1.98

## 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Acids. Bases. Amines.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

| Route | Species | Test | Value | Units |
|-------|---------|------|-------|-------|
| ORAL  | RAT     | LD50 | 11400 | mg/kg |

#### Hazardous ingredients:

##### BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

|     |     |      |       |       |
|-----|-----|------|-------|-------|
| ORL | MUS | LD50 | 15600 | mg/kg |
| ORL | RAT | LD50 | 11400 | mg/kg |
| SKN | RBT | LD50 | >20   | ml/kg |

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 6

## Relevant hazards for substance:

| Hazard                         | Route | Basis                 |
|--------------------------------|-------|-----------------------|
| Skin corrosion/irritation      | DRM   | Hazardous: calculated |
| Serious eye damage/irritation  | OPT   | Hazardous: calculated |
| Respiratory/skin sensitisation | DRM   | Hazardous: calculated |

## Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Not readily biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Heavier than water. Insoluble in water.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Harmful to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 12

**Disposal of packaging:** Dispose of in a regulated landfill site or other method for hazardous or toxic wastes. Waste disposal No. 15 01 08.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

# SAFETY DATA SHEET

EPOXY PUTTY 2122 RESIN

Page: 7

## Section 14: Transport information

**Transport class:** This product does not require a classification for transport.

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

For transport, the 'environmentally hazardous substance' mark is not required when transported in sizes of  $\leq 5L$  or  $\leq 5kg$ .

**Phrases used in s.2 and s.3:** EUH205: Contains epoxy constituents. May produce an allergic reaction.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

## SAFETY DATA SHEET

### EPOXY PUTTY 2122 HARDENER

Page: 1

Compilation date: 12/08/2016

Revision No: 6

#### Section 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name:** EPOXY PUTTY 2122 HARDENER

**Product code:** 307435

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** To be used in conjunction with Resin Pack

##### 1.3. Details of the supplier of the safety data sheet

**Company name:** Kopex-Ex

CMG House

Station Road

Coleshill

Birmingham

B46 1HT

UK

**Tel:** +44 (0) 1675 468 217

**Fax:** +44 (0) 1675 468 280

**Email:** [Sales@kopex.co.uk](mailto:Sales@kopex.co.uk)

##### 1.4. Emergency telephone number

#### Section 2: Hazards identification

##### 2.1. Classification of the substance or mixture

**Classification under CLP:** Eye Dam. 1: H318; Repr. 2: H361f

**Most important adverse effects:** Causes serious eye damage. Suspected of damaging fertility.

##### 2.2. Label elements

**Label elements:**

**Hazard statements:** H318: Causes serious eye damage.

H361f: Suspected of damaging fertility.

**Hazard pictograms:** GHS05: Corrosion

GHS08: Health hazard



**Signal words:** Danger

**Precautionary statements:** P102: Keep out of reach of children.

P202: Do not handle until all safety precautions have been read and understood.



# SAFETY DATA SHEET

## EPOXY PUTTY 2122 HARDENER

Page: 2

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical attention.

P310: Immediately call a POISON CENTER/doctor/.

P501: Dispose of contents/container to comply with all local, regional, national and international regulations.

### 2.3. Other hazards

**Other hazards:** Danger of serious damage to health by prolonged exposure.

**PBT:** This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

##### SILICA QUARTZ

| EINECS    | CAS        | PBT / WEL  | CLP Classification | Percent |
|-----------|------------|--|--------------------|---------|
| 238-878-4 | 14808-60-7 | Substance with a Community workplace exposure limit. | -                  | 50-70%  |

##### TALC

|           |            |  |   |        |
|-----------|------------|--|---|--------|
| 238-877-9 | 14807-96-6 | Substance with a Community workplace exposure limit. | - | 10-30% |
|-----------|------------|--|---|--------|

##### 4-TERT-BUTYLPHENOL

|           |         |   |   |       |
|-----------|---------|---|---|-------|
| 202-679-0 | 98-54-4 | - | Repr. 2: H361f; Skin Irrit. 2: H315; Eye Dam. 1: H318 | 1-10% |
|-----------|---------|---|---|-------|

##### PETROLATUM - PETROLATUM

|           |           |   |   |       |
|-----------|-----------|---|---|-------|
| 232-373-2 | 8009-03-8 | - | - | 1-10% |
|-----------|-----------|---|---|-------|

##### 2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL

|           |         |   |   |       |
|-----------|---------|---|---|-------|
| 202-013-9 | 90-72-2 | - | Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315 | 1-10% |
|-----------|---------|---|---|-------|

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

[cont...]

# SAFETY DATA SHEET

## EPOXY PUTTY 2122 HARDENER

Page: 3

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust. Evacuate the area immediately. Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Alert the neighbourhood to the presence of fumes or gas.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

[cont...]

**SAFETY DATA SHEET**  
EPOXY PUTTY 2122 HARDENER

Page: 4

**6.4. Reference to other sections**

**Reference to other sections:** Refer to section 8 of SDS.

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.  
Avoid the formation or spread of dust in the air.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.  
**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

**Specific end use(s):** No data available.

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Hazardous ingredients:**

**SILICA QUARTZ**

**Workplace exposure limits:**

**Respirable dust**

| State | 8 hour TWA | 15 min. STEL | 8 hour TWA            | 15 min. STEL |
|-------|------------|--------------|-----------------------|--------------|
| UK    | -          | -            | 0.1 mg/m <sup>3</sup> | -            |

**TALC**

|    |   |   |                     |   |
|----|---|---|---------------------|---|
| UK | - | - | 1 mg/m <sup>3</sup> | - |
|----|---|---|---------------------|---|

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

**Hand protection:** Impermeable gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Paste

**Colour:** Pale brown

[cont...]

**SAFETY DATA SHEET**  
EPOXY PUTTY 2122 HARDENER

Page: 5

**Odour:** Ammoniacal

**Solubility in water:** Insoluble

**Flash point°C:** >93

**Relative density:** 1.82 - 1.88

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**

**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Polymerisation may occur on exposure to conditions or materials listed below.

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat. Hot surfaces. Flames.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**

**11.1. Information on toxicological effects**

**Hazardous ingredients:**

**PETROLATUM - PETROLATUM**

|     |     |      |     |       |
|-----|-----|------|-----|-------|
| IPR | MUS | LD50 | >50 | gm/kg |
|-----|-----|------|-----|-------|

**2,4,6-TRIS(DIMETHYLAMINOMETHYL)PHENOL**

|     |     |      |      |       |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 1200 | mg/kg |
| SKN | RAT | LD50 | 1280 | mg/kg |

**Relevant hazards for substance:**

| Hazard                        | Route | Basis                 |
|-------------------------------|-------|-----------------------|
| Serious eye damage/irritation | OPT   | Hazardous: calculated |
| Reproductive toxicity         | --    | Hazardous: calculated |

[cont...]

**SAFETY DATA SHEET**  
EPOXY PUTTY 2122 HARDENER

Page: 6

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**

**12.1. Toxicity**

**Ecotoxicity values:** No data available.

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Insoluble in water. Heavier than water.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 04 09

**Disposal of packaging:** Waste Code number 15 01 10 Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

[cont...]

**SAFETY DATA SHEET**  
EPOXY PUTTY 2122 HARDENER

Page: 7

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H319: Causes serious eye irritation.  
H361f: Suspected of damaging fertility.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.