

# Product datasheet

Specifications



## FRONT PLATE TARIF NSX250 W600 9M

LVS03258

EAN Code: 3606481872197

### Main

Range	PrismaSeT
Range of product	PrismaSeT G PrismaSeT P
Product or component type	Front plate
Accessory / separate part category	Installation accessory
Range compatibility	PrismaSeT PrismaSeT G enclosure PrismaSeT PrismaSeT P cubicle
Type of front plate	Cut-out
Installed device	ComPact: fixed INV100 - control: direct front rotary handle - vertical installation ComPact: fixed INV160 - control: direct front rotary handle - vertical installation ComPact: fixed INV200 - control: direct front rotary handle - vertical installation ComPact: fixed INV250 - control: direct front rotary handle - vertical installation ComPact: fixed NSX100...160 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 without earth leakage protection - control: toggle - vertical installation ComPact: fixed NSX250 with earth leakage protection - control: toggle - vertical installation
Poles description	1 x 4P: mounting plate support: INV100 vertical installation 1 x 4P: mounting plate support: INV160 vertical installation 1 x 4P: mounting plate support: INV200 vertical installation 1 x 4P: mounting plate support: INV250 vertical installation 1 x 4P: mounting plate support: NSX100...160 vertical installation 1 x 4P: mounting plate support: NSX250 vertical installation
Operating position	Superposed

### Complementary

Enclosure/cubicle description	Floor-standing enclosure - width 600 mm Wall-mounted enclosure - width 600 mm Cubicle - width 650 + 150 mm depth 400 mm
Number of vertical modules [50 mm]	9
Standards	IEC 61439-1 NF C 15-100 IEC 61439-2
Product certifications	ASTA
Surface finish	Textured Matt
Protective treatment	Electrophoresis treatment and hot-polymerised polyester epoxy powder
Colour	White (RAL 9003)
Height	450 mm
Width	600 mm

<b>Net weight</b>	1.7 kg
<b>Quantity per set</b>	Set of 1
<b>functional unit</b>	600 mm PrismaSeT G floor-standing enclosure ComPact INV100 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact INV100 fixed direct front rotary handle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact INV100 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact INV160 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact INV160 fixed direct front rotary handle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact INV160 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact INV200 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact INV200 fixed direct front rotary handle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact INV200 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact INV250 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact INV250 fixed direct front rotary handle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact INV250 fixed direct front rotary handle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact NSX100...160 without fixed toggle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact NSX100...160 without fixed toggle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact NSX250 without fixed toggle vertical 4P 1 direct 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact NSX100...160 without fixed toggle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 without fixed toggle vertical 4P 1 direct 600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 without fixed toggle vertical 4P 1 direct 600 mm PrismaSeT G floor-standing enclosure ComPact NSX250 with fixed toggle vertical 4P 1 direct 13 600 mm PrismaSeT G wall-mounted enclosure ComPact NSX250 with fixed toggle vertical 4P 1 direct 13 650 + 150 mm 400 mm PrismaSeT P cubicle ComPact NSX250 with fixed toggle vertical 4P 1 direct 13

## Environment

<b>IP degree of protection</b>	IP30
--------------------------------	------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	3 cm
<b>Package 1 Width</b>	46.5 cm
<b>Package 1 Length</b>	51.5 cm
<b>Package 1 Weight</b>	1.719 kg
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	6
<b>Package 2 Height</b>	10.5 cm
<b>Package 2 Width</b>	52.5 cm
<b>Package 2 Length</b>	53 cm
<b>Package 2 Weight</b>	10.739 kg

<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	24
<b>Package 3 Height</b>	35 cm
<b>Package 3 Width</b>	80 cm
<b>Package 3 Length</b>	120 cm
<b>Package 3 Weight</b>	54.5 kg

## **Contractual warranty**

<b>Warranty (in months)</b>	18
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

Yes

[EU RoHS Directive](#)

Compliant

REACH Regulation

[REACH Declaration](#)

Halogen-free status

Halogen free plastic parts product

PVC free

Yes

Silicone-free

Yes

## Use Longer

### Lifetime extension

Repair

No

## Use Again

### Repack and remanufacture

End of life manual availability

No need of specific recycling operations


Take-back

No

Technical Illustration

Dimensions

---



- All dimensions are approximate and are in mm  
- Also see technical documentation.