



Image may differ from product. See technical specification for details.

361207 R

Single row cam roller with crowned outer surface and seals on both sides

Single row cam rollers, with seals on both sides, are designed to run on all types of tracks and to be used in cam drives, conveyor systems, etc. They are based on a single-row deep groove ball bearing and have a thick-walled outer ring with a crowned running surface. They are supplied sealed and greased for the life of the bearing, and are ready-to-mount. The integral sealing can significantly prolong bearing service life because it keeps lubricant in the bearings and contaminants out.

- Run on all types of tracks, for use in cam drives, conveyor systems, etc.Crowned outer running surface
- Greased, sealed and ready to mount
- Integral sealing prolongs bearing service life
- Typical benefits of single row deep groove ball bearings

Overview

Dimensions

Functional outside diameter	80 mm
Bore diameter	35 mm
Width	17 mm

Performance

Basic dynamic load rating	22.1 kN
Basic static load rating	11.8 kN
Limiting speed	4 500 r/min


Properties

Bearing part	Complete track roller
Rolling elements	Balls
Number of rows	1
Outer ring profile	Crowned
Axial guidance of outer ring	Yes
Number of flanges, outer ring	0
Cage	With
Radial internal clearance	C3
Axial internal clearance	Not applicable
Tolerance class	Normal (except crowned running surface)
Material, bearing	Bearing steel
Coating	Without
Sealing	Seal on both sides
Sealing type	Contact
Lubricant	Grease
Relubrication feature	Without

Logistics

Product net weight	0.414 kg
eClass code	23-05-08-01
UNSPSC code	31171504

Technical specification



Dimensions

D	80 mm	Outside diameter
d	35 mm	Bore diameter
В	17 mm	Width
d_1	≈ 46.9 mm	Shoulder/recess diameter inner ring
D_1	≈ 62.7 mm	Recess diameter outer ring
R	400 mm	Profile running surface (crown) outer ring
r _{1.2}	min. 1.1 mm	Chamfer dimension

Calculation data

Basic dynamic load rating	С	22.1 kN
Basic static load rating	C ₀	11.8 kN
Fatigue load limit	$P_{\rm u}$	0.5 kN
Maximum dynamic radial load	F _r	max. 12.9 kN
Maximum static radial load	F _{0r}	max. 18.3 kN
Limiting speed		4 500 r/min
Calculation factor	f ₀	13.8

Tolerances and clearances

GENERAL CAM ROLLER SPECIFICATIONS

- Tolerances: Normal
- Internal clearance: Single row cam rollers, Double row cam rollers

CAM ROLLER INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

More Information

Product details	Engineering information	Tools
Designs and variants		SKF Product select
General cam roller specifications	Principles of rolling bearing selection	Bearing Frequency Calculator
Loads	General bearing knowledge	SimPro Quick
Temperature limits	Bearing selection process	LubeSelect for SKF greases
Speed limits	Bearing interfaces	Heater selection tool
·	Lubrication	- Treater selection tool
Design consideration Designation system	External sealing, mounting and dismounting	
	Bearing failure and how to prevent it	



Terms of use

By accessing and using this website / app owned and published by AB SKF (publ.) ($556007-3495 \cdot Gothenburg$) ("SKF"), you agree to the following terms and conditions:

Warranty Disclaimer and Limitation of Liability

Although every care has been taken to assure the accuracy of the information on this website / app, SKF provides this information "AS IS" and DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. You acknowledge that your use of this website / app is at your sole risk, that you assume full responsibility for all costs associated with use of this website / app, and that SKF shall not be liable for any direct, incidental, consequential, or indirect damages of any kind arising out of your access to, or use of the information or software made available on this website / app.

Any warranties and representations in this website / app for SKF products or services that you purchase or use will be subject to the agreed upon terms and conditions in the contract for such product or service.

Further, for non-SKF websites / apps that are referenced in our website / app or where a hyperlink appears, SKF makes no warranties concerning the accuracy or reliability of the information in these websites / apps and assumes no responsibility for material created or published by third parties contained therein. In addition, SKF does not warrant that this website / app or these other linked websites / apps are free from viruses or other harmful elements.

Third Party Services

When viewing YouTube content via the SKF website(s) (i.e. using YouTube API Services), you agree to be bound by the YouTube Terms of Service.

Copyright

Copyright in this website / app copyright of the information and software made available on this website / app rest with SKF or its licensors. All rights are reserved. All licensed material will reference the licensor that has granted SKF the right to use the material. The information and software made available on this website / app may not be reproduced, duplicated, copied, transferred, distributed, stored, modified, downloaded or otherwise exploited for any commercial use without the prior written approval of SKF. However, it may be reproduced, stored and downloaded for use by individuals without prior written approval of SKF. Under no circumstances may this information or software be supplied to third parties.

This website /app includes certain images used under license from Shutterstock, Inc.

Trademarks and Patents

All trademarks, brand names, and corporate logos displayed on the website / app are the property of SKF or its licensors, and may not be used in any way without prior written approval by SKF. All licensed trademarks published on this website / app reference the licensor that has granted SKF the right to use the trademark. Access to this website / app does not grant to the user any license under any patents owned by or licensed to SKF.

Changes

SKF reserves the right to make changes or additions to this website / app at any time.