

Product datasheet

Specifications



LXM62 Single Axis Servo Drive Advanced 6A, HW STO SIL 3 PLE, ACCKIT

LXM62DU60G21000

EAN Code: 3606489595739

Main

Range of product	PacDrive 3
Device short name	LXM 62
Product or component type	Single axis servo drive
Component name	LXM62

Complementary

Product compatibility	Servo motor SHS Servo motor SH3 (55 mm, 1 motor stacks) optimized in terms of torque and speed Servo motor SH3 (55 mm, 2 motor stacks) optimized in terms of torque and speed Servo motor SH3 (55 mm, 3 motor stacks) optimized in terms of torque and speed Servo motor SH3 (70 mm, 1 motor stacks) optimized in terms of torque and speed Servo motor SH3 (70 mm, 2 motor stacks) optimized in terms of high torque Servo motor SH3 (70 mm, 3 motor stacks) optimized in terms of high torque Servo motor SH3 (100 mm, 1 motor stacks) optimized in terms of high torque Servo motor MH3 (70 mm, 1 motor stacks) optimized in terms of torque and speed Servo motor SH3 (40 mm, 1 motor stacks) optimized in terms of torque and speed
Network number of phases	Three phase
[Us] rated supply voltage	400 V (- 10...10 %) for three phase 230 V (- 10...10 %) for three phase 230 V (- 10...10 %) for single phase
Supply frequency	50/60 Hz - 5...5 %
Continuous output current	2 A at 4 kHz
Output current 3s peak	6 A at 4 kHz
Continuous power	0.95 kW
Nominal power	0.95 kW
Switching frequency	8 kHz
Overvoltage category	III
Electrical connection	Terminal, clamping capacity: 0.2...15 mm ² , AWG 24...AWG 16 (CN4) Terminal, clamping capacity: 0.5...16 mm ² , AWG 20...AWG 6 (CN5) Terminal, clamping capacity: 0.75...16 mm ² , AWG 18...AWG 6 (CN6) Terminal, clamping capacity: 0.2...6 mm ² , AWG 24...AWG 10 (CN7)
Tightening torque	CN1: 2.5 N.m
Number of inputs	2 digital 2 touch probe
Discrete input voltage	24 V DC for - 20...25 %
Number of outputs	2 digital
Discrete output voltage	24 V DC
Safety function	STO (safe torque off)
Communication interface	SERCOS III, integrated

Depth	270 mm
Height	310 mm
Width	44 mm
Net weight	3 kg

Environment

Standards	CSA C22.2 No 14 ISO 13849-2 IEC 61800-5-2 IEC 61800-3 IEC 62061 IEC 61800-5-1 ISO 13849-1 IEC 61508 UL 508C
Product certifications	EAC CE UL TÜV CSA
IP degree of protection	IP20 conforming to IEC 60529
Vibration resistance	10 m/s ² conforming to IEC 60721-3-3
Shock resistance	100 m/s ² conforming to IEC 60721-3-3
Pollution degree	2 conforming to IEC 61800-5-2
Environmental characteristic	3K3 conforming to IEC 60721-3-3
Relative humidity	5...85 %
Ambient air temperature for operation	5...55 °C
Operating altitude	> 1000 m 1 % per 100 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.500 cm
Package 1 Width	33.500 cm
Package 1 Length	44.000 cm
Package 1 Weight	3.900 kg
Unit Type of Package 2	S06
Number of Units in Package 2	10
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	48.800 kg

Contractual warranty

Warranty (in months)	18
-----------------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
SCIP Number	60beca05-ce1c-43ef-b5f4-b7c0f3eb7d27
REACH Regulation	REACH Declaration
PVC free	Yes

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Take-back	No