



Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)

RS Components

Chemwatch Hazard Alert Code: 1

Chemwatch: 5422-31
Version No: 2.1.1.1
Safety Data Sheet according to HSNO Regulations

Issue Date: 28/08/2020
Print Date: 07/09/2020
L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Application as thermal insulation, heat shields, heat containment, gaskets and expansion joints in industrial furnaces, ovens, kilns, boilers and other process. Equipment and in the aerospace, automotive and appliance industries, and as passive fire protection systems and fire stops.
--------------------------	--

Details of the supplier of the safety data sheet

Registered company name	RS Components
Address	PO Box 12-127 Penrose, Auckland New Zealand
Telephone	+64 27 4747122
Fax	+64 9 579 1700
Website	www.nz.rs-online.com
Email	Not Available

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	+61 2 9186 1132
Other emergency telephone numbers	+64 800 700 112

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Skin Corrosion/Irritation Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3B

Label elements

Hazard pictogram(s)	Not Applicable
Signal word	Warning

Hazard statement(s)

H316	Causes mild skin irritation.
------	------------------------------

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

P332+P313	If skin irritation occurs: Get medical advice/attention.
-----------	--

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
436083-99-7	>60	alkaline earth silicate wool (biosoluble)

SECTION 4 First aid measures**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<ul style="list-style-type: none"> ▶ Gently brush or vacuum off adherent fibres. ▶ Wash affected areas thoroughly with water (and soap if available). ▶ Seek medical attention if irritation exists and persists.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area. ▶ Other measures are usually unnecessary.
Ingestion	<ul style="list-style-type: none"> ▶ Immediately give a glass of water. ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Mineral fibres are a mechanical irritant, and are not expected to produce any chronic health effects from acute exposures.

Treatment should be directed toward removing the source of irritation with symptomatic treatment as necessary.

Lung function should be monitored, periodically, in individuals chronically exposed to fibres in an occupational setting

SECTION 5 Firefighting measures**Extinguishing media**

- ▶ There is no restriction on the type of extinguisher which may be used.
- ▶ Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water courses. ▶ Use fire fighting procedures suitable for surrounding area. <p>Slight hazard when exposed to heat, flame and oxidisers.</p>
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Non combustible. ▶ Not considered a significant fire risk, however containers may burn.

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid all personal contact, including inhalation. ▶ Access to area should be restricted by the use of ropes or other similar barriers and appropriate signs be utilised. ▶ Employees not engaged in the clean up should not be allowed within 3 metres of the work unless wearing suitable personal protective equipment (PPE).
Major Spills	<ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Control personal contact with the substance, by using protective equipment and dust respirator.

- Access to area should be restricted by the use of ropes or other similar barriers and appropriate signs be utilised.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▸ The use of ceramic fibres in the work place should be reviewed in the context of frequency of use and potential for exposure. ▸ In circumstances where the respiratory standards or excursion limits are approached, work areas should be designated by the use of ropes or other similar barriers and appropriate signs be utilised, where possible. This is especially true for all overhead work involving ceramic fibres. ▸ Employees not engaged in the ceramic fibre work should not be allowed within 3 metres of the work unless wearing suitable personal protective equipment (PPE).
Other information	<ul style="list-style-type: none"> ▸ Store away from incompatible materials.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▸ Polyethylene or polypropylene container. ▸ Packing as recommended by manufacturer. ▸ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	None known

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Not Available


Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)	Not Available	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
alkaline earth silicate wool (biosoluble)	Not Available	Not Available

MATERIAL DATA

Exposure controls

Appropriate engineering controls	<ul style="list-style-type: none"> ▸ If measured respirable fibre is less than the recommended occupational exposure level, wear approved dust respirator Class P1 (half-face). ▸ Use a Class P2 or P3 respirator (full-face), where exposure is above the recommended occupational exposure level ▸ Use an approved respirator if power tools without dust extraction or containment are used. ▸ Provide good ventilation (either forced or natural) ▸ Where possible, enclose sources of dust and provide dust extraction at the source. ▸ Restrict access to work areas involved in handling man-made mineral fibres and ensure that adequate training, in the handling of such materials, has been provided. ▸ Use operating procedures which limit the generation of dusts. ▸ When working with unbonded fibres, local exhaust ventilation is generally a requirement.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> ▸ Safety glasses with side shields. ▸ Chemical goggles. ▸ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> ▸ Wear chemical protective gloves, e.g. PVC. ▸ Wear safety footwear or safety gumboots, e.g. Rubber
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> ▸ Disposable coveralls or long sleeve, loose fitting protective clothing, e.g. overalls (launder clothing separately from other clothing). ▸ When working above head height, use head covering. ▸ Minimise dust generation by using sharp hand cutting tools if possible. ▸ Powered tools (e.g. saws etc.) should only be used if fitted with dust extraction and containment equipment. ▸ Personnel involved in the installation of unbonded ceramic materials should wear disposable coveralls, or long-sleeve loose fitting clothing, gloves and suitable respirator. Such equipment should also be used by personnel employed in removing materials which have not become embrittled. ▸ Personnel involved in the removal of embrittled material should in addition, use a full-face cartridge respirator, or full-face powered air purifying respirator, each with suitable particulate filter, or a full-face pressure demand airline respirator.

Respiratory protection

**Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915,
840-5526, 840-5529 (NZ)**

- ▶ Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- ▶ The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- ▶ Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- ▶ Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- ▶ Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

Use appropriate respiratory protective equipment against excessive concentrations of fibrous dusts.

Airborne Fibre Concentration	Full Face P2	Full Face P3
Above Exposure Limit Value	Recommended	-
For short-term operation where excursions above the limit value are less than factor of 10		Required

- ▶ Correct respirator fit is essential to obtain adequate protection.
- ▶ Even though the recommended level for respirable fibre is not exceeded in normal conditions, respiratory protection is advisable in dusty areas.
- ▶ In very dusty conditions and confined spaces greater comfort may be afforded by a full-face powered air-purifying respirator.
- ▶ Preforms (batts) designed for high temperature applications (above 177 degrees Celsius), may release gases (CO₂, formaldehyde, amines) irritating to the eyes, nose and throat during initial heat-up. In confined or poorly ventilated areas, use air supplied respirators during the first heat-up cycle.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	White fiber with no odour; insoluble in water.		
Physical state	Manufactured	Relative density (Water = 1)	0.05-0.24
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	>1200	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Applicable	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Applicable
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Applicable

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health).
Skin Contact	Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after

Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)

	prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.
Eye	Although the material is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course.

Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)	TOXICITY	IRRITATION
	Not Available	Not Available
alkaline earth silicate wool (biosoluble)	TOXICITY	IRRITATION
	Not Available	Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

ALKALINE EARTH SILICATE WOOL (BIOSOLUBLE)	Insulation wools belong to the generic group of man-made vitreous fibres (MMVF) also known as man-made mineral fibres (MMMF) or synthetic mineral fibres (SMF). The insulation wools are significantly different from other types of MMVF such as refractory ceramic fibres, reinforcement fibres and glass microfibres used for special applications.
	Insulation wools are different not only in the dimensions of their fibres but also in their chemical composition and their biopersistence. Specifically, insulation wools are defined within the European Union and elsewhere as being man-made vitreous (silicate) fibres with random orientation and with the Na ₂ O+K ₂ O+CaO+MgO+BaO content exceeding 18% by weight. The sum of percentages of the weights of oxides in the fibre (KI) has been shown to be the best predictor of in-vitro solubility at pH 7.4. Fibres with a KI of 40 or more are highly soluble and are unlikely to pose a carcinogenic risk.
	For glass wool reducing the alumina content of fibres and increasing boron has been found to significantly increase in-vitro solubility at pH 7.4 whilst at pH 4.5 the dissolution rate is very low at low alumina contents.

Acute Toxicity	✘	Carcinogenicity	✘
Skin Irritation/Corrosion	✔	Reproductivity	✘
Serious Eye Damage/Irritation	✘	STOT - Single Exposure	✘
Respiratory or Skin sensitisation	✘	STOT - Repeated Exposure	✘
Mutagenicity	✘	Aspiration Hazard	✘

Legend: ✘ – Data either not available or does not fill the criteria for classification
✔ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915, 840-5526, 840-5529 (NZ)	Endpoint	Test Duration (hr)	Species	Value	Source
		Not Available	Not Available	Not Available	Not Available
alkaline earth silicate wool (biosoluble)	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation
	No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal. ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▶ Where in doubt contact the responsible authority. ▶ Recycle wherever possible or consult manufacturer for recycling options. ▶ Consult State Land Waste Management Authority for disposal. ▶ Bury residue in an authorised landfill. ▶ Recycle containers if possible, or dispose of in an authorised landfill.
-------------------------------------	--

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002624	N.O.S. (Subsidiary Hazard) Group Standard 2017
HSR002535	Gas Under Pressure Mixtures (Subsidiary Hazard) Group Standard 2017
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2017
HSR002530	Cleaning Products (Subsidiary Hazard) Group Standard 2017
HSR002585	Fuel Additives (Subsidiary Hazard) Group Standard 2017
HSR002519	Aerosols (Subsidiary Hazard) Group Standard 2017
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2017
HSR002606	Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) Group Standard 2017
HSR002644	Polymers (Subsidiary Hazard) Group Standard 2017
HSR002647	Reagent Kits Group Standard 2017
HSR002670	Surface Coatings and Colourants (Subsidiary Hazard) Group Standard 2017
HSR002638	Photographic Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002565	Embalming Products (Subsidiary Hazard) Group Standard 2017
HSR002578	Food Additives and Fragrance Materials (Subsidiary Hazard) Group Standard 2017
HSR002558	Dental Products (Subsidiary Hazard) Group Standard 2017
HSR002684	Water Treatment Chemicals (Subsidiary Hazard) Group Standard 2017
HSR002573	Fire Fighting Chemicals Group Standard 2017
HSR100425	Pharmaceutical Active Ingredients Group Standard 2017
HSR002600	Leather and Textile Products (Subsidiary Hazard) Group Standard 2017
HSR002605	Lubricants (Low Hazard) Group Standard 2017
HSR002571	Fertilisers (Subsidiary Hazard) Group Standard 2017
HSR002648	Refining Catalysts Group Standard 2017
HSR002653	Solvents (Subsidiary Hazard) Group Standard 2017
HSR002544	Construction Products (Subsidiary Hazard) Group Standard 2017
HSR002549	Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2017
HSR100757	Veterinary Medicine (Limited Pack Size, Finished Dose) Standard 2017
HSR100758	Veterinary Medicines (Non-dispersive Closed System Application) Group Standard 2017

**Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915,
840-5526, 840-5529 (NZ)**

HSR Number	Group Standard
HSR100759	Veterinary Medicines (Non-dispersive Open System Application) Group Standard 2017
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2017
HSR002612	Metal Industry Products (Subsidiary Hazard) Group Standard 2017
HSR002503	Additives, Process Chemicals and Raw Materials (Subsidiary Hazard) Group Standard 2017
HSR002552	Cosmetic Products Group Standard 2017

alkaline earth silicate wool (biosoluble) is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
Not Applicable	Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC	No (alkaline earth silicate wool (biosoluble))
Australia Non-Industrial Use	No (alkaline earth silicate wool (biosoluble))
Canada - DSL	No (alkaline earth silicate wool (biosoluble))
Canada - NDSL	No (alkaline earth silicate wool (biosoluble))
China - IECSC	No (alkaline earth silicate wool (biosoluble))
Europe - EINEC / ELINCS / NLP	No (alkaline earth silicate wool (biosoluble))
Japan - ENCS	No (alkaline earth silicate wool (biosoluble))
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (alkaline earth silicate wool (biosoluble))
USA - TSCA	No (alkaline earth silicate wool (biosoluble))
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	No (alkaline earth silicate wool (biosoluble))
Legend:	<i>Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)</i>

SECTION 16 Other information

Revision Date	28/08/2020
Initial Date	28/08/2020

SDS Version Summary

Version	Issue Date	Sections Updated
2.1.1.1	28/08/2020	Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
 PC—STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit

**Superwool Bulk, Superwool Blanket #137-2238, 137-2239, 724-8903, 724-8912, 724-8915,
840-5526, 840-5529 (NZ)**

TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.