

Technical data


32020XU

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage



VISUAL (S)



PRODUCT DEFINITION	
Brand	NTN
d - Internal diameter	100 mm
D - External diameter	150 mm
B - Bearing/Inner ring width	32 mm
C - Outer ring width	24 mm
T - Total width	32 mm
d1 - External diameter inner ring	126 mm
a - Charge load application point	32,5 mm
rs - Min fillet radius	2 mm
r1s - Min fillet radius	1,5 mm
Mass	1,91 kg
ISO 355 reference	T4CC100

PRODUCT PERFORMANCE	
C - Dynamic load	188000000 mN
C0 - Static load	281000000 mN
Cu - Fatigue limit load	32000000 mN
A2 - Rating life coefficient	1
e - Coefficient	0.46
Y0 - Static axial load coefficient	0.72
Y2 - Upper axial load coefficient	1.31
N lim - Oil lubrication limit speed	18000 °/s
N lim - Grease lubrication limit speed	13200 °/s
Tmin - Min operating temperature	233,15 °K



PRODUCT PERFORMANCE

Tmax - Max operating temperature	393,15 °K
---	-----------

ABUTMENT

da max - Max shoulder diameter IR	109 mm
db min - Min IR shoulder diameter	110 mm
Da min - Min shoulder diameter OR	134 mm
Da max - Max shoulder diameter OR	141,5 mm
Db min - Min OR shoulder diameter	144 mm
Ca - Min clearance	6 mm
Cb - Min clearance	8 mm
ra max - Max fillet radius	2 mm
r1a - Max fillet radius	1,5 mm

OE EQUIVALENTS

Manufacturer	Part number
Mercedes	001 981 7205



INDUSTRY CALCUL FACTORS

Equivalent dynamic radial load

$P = X.F_r + Y.F_a$

$F_a / F_r \leq e$		$F_a / F_r > e$	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$P_0 = X_0.F_r + Y_0.F_a$

X_0	Y_0
0.5	Y0

If $P_0 \leq F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table

