


Product description	M8 Male angled connector, Contacts: 4, 3.5-5.0 mm, unshielded, solder, IP67, UL 2238
Area	M8
Coding	A-coded
Series	768
Part no.	99 3387 00 04


Illustration



Scale drawing



Contact arrangement (Plug-in side)



You can find the assembly instructions on the next page.

Technical data

General features

Part no.	99 3387 00 04
Connector design	Male angled connector
Type standard	DIN EN 61076-2-104
Coding	A-coded
Version	Connector pin angled
Connector locking system	screw
Termination	solder
Degree of protection	IP67
Connection cross-section	0.25 mm ² / AWG 24
Cable outlet	3.5-5.0 mm
Twistability	90° (4 coding options)
Temperature range from/to	-40 °C / 85 °C
Mechanical operation	> 100 Mating cycles
Weight (g)	8.47
Customs tariff number	85369010
Country of Origin	DE

Electrical parameters

Rated voltage	60 V (UL 30 V)
Rated impulse voltage	1500 V
Rated current	4.0 A
Pollution degree	3
Overvoltage category	III

Product data sheet

Automation technology - Sensors and actuators



Product description **M8 Male angled connector, Contacts: 4, 3.5-5.0 mm, unshielded, solder, IP67, UL 2238**

Area **M8**
Coding **A-coded**
Series **768**
Part no. **99 3387 00 04**

Insulating material group III
EMC compliance unshielded

Material

Housing material PA
Contact body material PA
Contact material CuZn (brass)
Contact plating Au (gold)
Locking material CuZn (brass)
REACH SVHC CAS 7439-92-1 (Lead)
SCIP number acea2b75-11f9-4897-ba0b-038c9250c15e

Authorization/approvals

Approvals UL 2238

Classifications

eCl@ss 11.1 27-44-01-02
ETIM 9.0 EC002635

Declarations of conformity


Low Voltage Directive 2014/35/EU (EN 60529:1991 | 2014/35/EU;EN 60204-1:2018)

Product description **M8 Male angled connector, Contacts: 4, 3.5-5.0 mm, unshielded, solder, IP67, UL 2238**

Area **M8**
Coding **A-coded**
Series **768**
Part no. **99 3387 00 04**

Assembly instructions

1. Bead pressing screw, pinch ring, seal and angled housing to cable.
2. Dismantle cable.
3. Strip and solder single wires.
4. Screw angled housing to male/female insert.
5. Push seal and pinch ring into angled housing.
6. Tighten pressing screw.



Product description	M8 Male angled connector, Contacts: 4, 3.5-5.0 mm, unshielded, solder, IP67, UL 2238
Area	M8
Coding	A-coded
Series	768
Part no.	99 3387 00 04

General Disclaim Notice

The connector must not be plugged or unplugged under load. Non-observance and improper use can result in personal injury.

The connectors have been developed for applications in plant engineering, control and electrical equipment construction. The user is responsible for checking whether the connectors can also be used in other areas of application.

To protect against unintentional opening of the connector, the thread between the housing and the connector head must be secured with a suitable cyanoacrylate adhesive when used in circuits with voltages dangerous to the touch. This does not apply to connectors used in SELV and PELV circuits according to IEC 61140 (EN 61140, VDE 0140-1).

Connectors which are used in circuits with voltages dangerous to the touch may only be installed and used by, or under the supervision of, persons with electrical engineering training, taking into account the applicable regulations and standards.

The user must take suitable safety precautions to ensure that the connector cannot be accidentally disconnected.

Plug connectors with enclosure protection IP67 and IP68 are not suitable for use under water. When used outdoors, the plug connectors must be protected separately against corrosion. For further information on the IP protection classes, please refer to the "Technical Information" download centre.

Please observe the pollution degree and the overvoltage category. For further information, please refer to the download center "Technical Information".

To lock the cable connector with the device connector, the threaded ring is tightened "hand-tight" (approx. 50 cNm).