




PRODUCT-DETAILS

# AFS305-30-12-13

## AFS305-30-12-13



| General Information   |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | AFS305-30-12-13                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Product ID            | 1SFL587082R1312                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| EAN                   | 7320500541425                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Catalog Description   | AFS305-30-12-13                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Long Description      | <p>The AFS305-30-12-13 is a 3 pole - 1000 V IEC or 600 V UL contactor with pre-mounted 1 left (1 N.O + 1 N.C.) and fixed 1 right (1 N.C.) side mounted auxiliary contact blocks with Main Circuit Bars connections, controlling motors up to 160 kW / 400 V AC (AC-3) or 250 hp / 480 V UL and switching power circuits up to 500 A (AC-1) or 400 A UL general use. AFS contactors can be easily integrated in machine manufacturer's systems complying with main standards EN ISO 13849 and EN 62061 - guaranteeing the safe use of your machinery and equipment. An easily identifiable yellow low energy auxiliary contact block ensures the status feedback circuits required in machine safety applications. Thanks to the AF technology, the contactor has a wide control voltage range (100-250 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.</p> |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

### Popular Downloads

|                                            |                  |
|--------------------------------------------|------------------|
| EPLAN Data                                 | 9AAC412762_EPLAN |
| Data Sheet, Technical Information          | 1SBC100214C0202  |
| Data Sheet, Technical Information (Part 2) | 1SAC200017M0002  |
| Instructions and Manuals                   | 1SFC100008M0201  |
| CAD Dimensional Drawing                    | 2CDC001079B0201  |

### Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 140 mm |
| Product Net Depth / Length | 180 mm |
| Product Net Height         | 225 mm |
| Product Net Weight         | 4 kg   |

### Technical

|                                                          |                                                                                                                                                                                  |
|----------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO                               | 3                                                                                                                                                                                |
| Number of Main Contacts NC                               | 0                                                                                                                                                                                |
| Number of Auxiliary Contacts NO                          | 1                                                                                                                                                                                |
| Number of Auxiliary Contacts NC                          | 2                                                                                                                                                                                |
| Number of Poles                                          | 3P                                                                                                                                                                               |
| Rated Operational Voltage                                | Main Circuit 1000 V                                                                                                                                                              |
| Rated Frequency (f)                                      | Main Circuit 50 / 60 Hz                                                                                                                                                          |
| Conventional Free-air Thermal Current (I <sub>th</sub> ) | acc. to IEC 60947-4-1, Open Contactors $\Theta = 40\text{ °C}$ 500 A                                                                                                             |
| Rated Operational Current AC-1 (I <sub>e</sub> )         | (1000 V) 40 °C 375 A<br>(1000 V) 60 °C 325 A<br>(1000 V) 70 °C 260 A<br>(690 V) 40 °C 500 A<br>(690 V) 60 °C 400 A<br>(690 V) 70 °C 325 A                                        |
| Rated Operational Current AC-3 (I <sub>e</sub> )         | (415 V) 60 °C 305 A<br>(440 V) 60 °C 305 A<br>(500 V) 60 °C 290 A<br>(690 V) 60 °C 290 A<br>(1000 V) 60 °C 131 A<br>(380 / 400 V) 60 °C 305 A<br>(220 / 230 / 240 V) 60 °C 305 A |
| Rated Operational Current DC-1 (I <sub>e</sub> )         | (110 V) 1-Pole, 40 °C 500 A<br>(220 V) 2 Poles in Series, 40 °C 500 A<br>(220 V) 3 Poles in Series, 40 °C 500 A                                                                  |
| Rated Operational Current DC-3 (I <sub>e</sub> )         | (110 V) 1-Pole, 40 °C 400 A<br>(220 V) 2 Poles in Series, 40 °C 400 A<br>(220 V) 3 Poles in Series, 40 °C 400 A                                                                  |
| Rated Operational                                        | (110 V) 1-Pole, 40 °C 400 A                                                                                                                                                      |

|                                                                   |                                                                                                                                                                                                                                                                                                                                                                              |
|-------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Current DC-5 ( $I_e$ )                                            | (220 V) 2 Poles in Series, 40 °C 400 A<br>(220 V) 3 Poles in Series, 40 °C 400 A                                                                                                                                                                                                                                                                                             |
| Rated Operational Power<br>AC-3 ( $P_e$ )                         | (415 V) 160 kW<br>(440 V) 160 kW<br>(500 V) 200 kW<br>(690 V) 250 kW<br>(1000 V) 185 kW<br>(380 / 400 V) 160 kW<br>(220 / 230 / 240 V) 90 kW                                                                                                                                                                                                                                 |
| Rated Breaking Capacity<br>AC-3                                   | 8 x $I_e$ AC-3                                                                                                                                                                                                                                                                                                                                                               |
| Rated Making Capacity<br>AC-3                                     | 10 x $I_e$ AC-3                                                                                                                                                                                                                                                                                                                                                              |
| Short-Circuit Protective<br>Devices                               | gG Type Fuses 500 A                                                                                                                                                                                                                                                                                                                                                          |
| Rated Short-time<br>Withstand Current Low<br>Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2440 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 500 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 996 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3050 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1409 A                        |
| Maximum Breaking<br>Capacity                                      | $\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 4600 A<br>$\cos \phi = 0.45$ ( $\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 3800 A                                                                                                                                                                                                                     |
| Rated Insulation Voltage<br>( $U_i$ )                             | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                                                                                                                                    |
| Rated Impulse<br>Withstand Voltage ( $U_{imp}$ )                  | Main Circuit 8 kV                                                                                                                                                                                                                                                                                                                                                            |
| Maximum Electrical<br>Switching Frequency                         | (AC-1) 300 cycles per hour<br>(AC-2 / AC-4) 150 cycles per hour<br>(AC-3) 300 cycles per hour                                                                                                                                                                                                                                                                                |
| Mechanical Durability                                             | 5 million                                                                                                                                                                                                                                                                                                                                                                    |
| Maximum Mechanical<br>Switching Frequency                         | 300 cycles per hour                                                                                                                                                                                                                                                                                                                                                          |
| Coil Operating Limits                                             | (acc. to IEC 60947-4-1) 0.85 x $U_c$ Min. ... 1.1 x $U_c$ Max. (at $\theta \leq 70$ °C)                                                                                                                                                                                                                                                                                      |
| Rated Control Circuit<br>Voltage ( $U_c$ )                        | 50 Hz 100 ... 250 V<br>60 Hz 100 ... 250 V<br>DC Operation 100 ... 250 V                                                                                                                                                                                                                                                                                                     |
| Coil Consumption                                                  | Holding at Max. Rated Control Circuit Voltage 50 Hz 17.5 V-A<br>Holding at Max. Rated Control Circuit Voltage 60 Hz 17.5 V-A<br>Holding at Max. Rated Control Circuit Voltage DC 3 W<br>Pull-in at Max. Rated Control Circuit Voltage 50 Hz 385 V-A<br>Pull-in at Max. Rated Control Circuit Voltage 60 Hz 385 V-A<br>Pull-in at Max. Rated Control Circuit Voltage DC 410 W |
| Power Loss                                                        | at Rated Operating Conditions per Pole 19 W                                                                                                                                                                                                                                                                                                                                  |
| Operate Time                                                      | Between Coil De-energization and NO Contact Opening 37 ... 47 ms<br>Between Coil Energization and NO Contact Closing 25 ... 55 ms                                                                                                                                                                                                                                            |
| Connecting Capacity<br>Main Circuit                               | Flexible 2 x 70 ... 185 mm <sup>2</sup><br>Rigid Al-Cable 1 x 185 ... 240 mm <sup>2</sup><br>Rigid Cu-Cable 1 x 6 ... 300 mm <sup>2</sup>                                                                                                                                                                                                                                    |
| Connecting Capacity<br>Auxiliary Circuit                          | Flexible with Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible 2x0.75 ... 2.5 mm <sup>2</sup><br>Solid 2 x 1 ... 4 mm <sup>2</sup><br>Stranded 2 x 1 ... 4 mm <sup>2</sup>                                                                                                                             |
| Connecting Capacity                                               | Flexible 2 x 70 ... 185 mm <sup>2</sup><br>Rigid Al-Cable 1 x 185 ... 240 mm <sup>2</sup><br>Rigid Cu-Cable 2 x 70 ... 185 mm <sup>2</sup>                                                                                                                                                                                                                                   |
| Degree of Protection                                              | acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00                                                                                                                                                                                                                                                 |
| Recommended Screw<br>Driver                                       | Main Circuit M10<br>Control Circuit M3.5<br>Control Circuit Pozidriv 2                                                                                                                                                                                                                                                                                                       |
| Tightening Torque                                                 | Cable Lug 28 N·m<br>Main Circuit 22 ... 43 N·m                                                                                                                                                                                                                                                                                                                               |

|               |                    |
|---------------|--------------------|
| Terminal Type | Main Circuit: Bars |
| Product Name  | Block Contactor    |

## Technical UL/CSA

|                                  |                                                                                                                                                                  |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V                                                                                                                                               |
| General Use Rating UL/CSA        | (600 V AC) 400 A                                                                                                                                                 |
| Horsepower Rating UL/CSA         | (200 ... 208 V AC) Three Phase 100 hp<br>(220 ... 240 V AC) Three Phase 125 hp<br>(440 ... 480 V AC) Three Phase 250 hp<br>(550 ... 600 V AC) Three Phase 300 hp |
| Full Load Amps Motor Use         | (200 ... 208 V AC) Three Phase 285 A<br>(220 ... 240 V AC) Three Phase 312 A<br>(440 ... 480 V AC) Three Phase 302 A<br>(550 ... 600 V AC) Three Phase 289 A     |

## Environmental

|                                        |                                                                                                                                                                                                                  |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                | Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... 50 °C<br>Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... 70 °C<br>Close to Contactor for Storage -40 ... 70 °C |
| Maximum Operating Altitude Permissible | Without Derating 3000 m                                                                                                                                                                                          |

## Material Compliance

|                                             |                                                                        |
|---------------------------------------------|------------------------------------------------------------------------|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658                                                        |
| REACH Declaration                           | 2CMT2021-006202                                                        |
| RoHS Declaration                            | 2CMT2021-006277                                                        |
| RoHS Information                            | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA         | 2CMT2023-006525                                                        |
| WEEE B2C / B2B                              | Business To Business                                                   |
| WEEE Category                               | 5. Small Equipment (No External Dimension More Than 50 cm)             |

## ABB EcoSolutions

|                                                   |                                                                                                                                          |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| ABB EcoSolutions                                  | Yes                                                                                                                                      |
| ABB Site Meeting Group Waste To Landfill Target   | Non-hazardous waste is sent to a landfill, where there is no alternative option available within 100km of a facility                     |
| End Of Life Disassembling Instructions            | 1SFC100112M0002                                                                                                                          |
| Environmental Product Declaration - EPD           | 1SFC100104D0201                                                                                                                          |
| Improved Energy Efficiency for Customers          | Product Efficiency - Product considered more energy-efficient compared to similar product on market or older products from the same line |
| Recyclability Rate of the Product acc. to EN45555 | Design for Closing Resource Loops - Standard EN45555 - 76.3 %                                                                            |
| Sustainable Material Content in Product (wt. %)   | Recycled Metal - 33 %                                                                                                                    |

## Certificates and Declarations

|                                     |                     |
|-------------------------------------|---------------------|
| CB Certificate                      | SE-89316            |
| CQC Certificate                     | CQC2014010304676670 |
| Declaration of<br>Conformity - CCC  | 2020980304001305    |
| Declaration of<br>Conformity - CE   | 2CMT2018-005695     |
| Declaration of<br>Conformity - UKCA | 2CMT2020-006125     |
| EAC Certificate                     | 1SFC101360D1101     |
| SUVA Certificate                    | 2CMT2019-005858     |
| UL Certificate                      | 20121217-E36588     |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 263 mm        |
| Package Level 1 Depth /<br>Length | 203 mm        |
| Package Level 1 Height            | 289 mm        |
| Package Level 1 Gross<br>Weight   | 4.7 kg        |
| Package Level 1 EAN               | 7320500541425 |

## External Classifications and Standards

|                                       |                                          |
|---------------------------------------|------------------------------------------|
| Object Classification<br>Code         | Q                                        |
| ETIM 7                                | EC000066 - Power contactor, AC switching |
| ETIM 8                                | EC000066 - Power contactor, AC switching |
| ETIM 9                                | EC000066 - Power contactor, AC switching |
| eClass                                | V11.0 : 27371003                         |
| UNSPSC                                | 39121529                                 |
| IDEA Granular Category<br>Code (IGCC) | 4755 >> Contactors                       |
| E-Number (Finland)                    | 3709025                                  |

## Accessories

| Identifier      | Description                      | Type      | Quantity | Unit Of Measure |
|-----------------|----------------------------------|-----------|----------|-----------------|
| 1SFN010832R1010 | CEL19-10 Auxiliary Contact Block | CEL19-10  | 1        | piece           |
| 1SFN010832R1001 | CEL19-01 Auxiliary Contact Block | CEL19-01  | 1        | piece           |
| 1SFN010820R1011 | CAL19-11 Auxiliary Contact Block | CAL19-11  | 1        | piece           |
| 1SFN074208R1000 | LD146-30 Connection Module       | LD146-30  | 1        | piece           |
| 1SFN124203R1000 | LT140-30L Terminal Shroud        | LT140-30L | 1        | piece           |
| 1SFN074207R1000 | LW140 Terminal Enlargement       | LW140     | 1        | piece           |
| 1SFN074210R1000 | LX140 Terminal Extension         | LX140     | 1        | piece           |
| 1SFN074203R1000 | LY140 Connecting Strip           | LY140     | 1        | piece           |
| 1SFN124801R1000 | LT205-30C Terminal Shroud        | LT205-30C | 1        | piece           |
| 1SFN124803R1000 | LT205-30L Terminal Shroud        | LT205-30L | 1        | piece           |
| 1SFN124804R1000 | LT205-30Y Terminal Shroud        | LT205-30Y | 1        | piece           |
| 1SFN074807R1000 | LW205 Terminal Enlargement       | LW205     | 1        | piece           |
| 1SFN074810R1000 | LX205 Terminal Extension         | LX205     | 1        | piece           |
| 1SFN074703R1000 | LY185 Connecting Strip           | LY185     | 1        | piece           |
| 1SFN075103R1000 | LY300 Connecting Strip           | LY300     | 1        | piece           |
| 1SFN075410R1000 | LX370 Terminal Extension         | LX370     | 1        | piece           |
| 1SFN125406R1000 | LT370-30D Terminal Shroud        | LT370-30D | 1        | piece           |
| 1SFN125404R1000 | LT370-30Y Terminal Shroud        | LT370-30Y | 1        | piece           |
| 1SFN125403R1000 | LT370-30L Terminal Shroud        | LT370-30L | 1        | piece           |
| 1SFN125401R1000 | LT370-30C Terminal Shroud        | LT370-30C | 1        | piece           |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AFS Contactors → AFS305

