


# CABLE END-SLEEVES

Material: copper  
 Surface: tin plated  
 Dimensions DIN 46228, part 4  
**Insulated**, free of halide  
 synthetic material: Polypropylene



| Conductor<br>mm <sup>2</sup> | Part No.                                       | Colour     | Dimensions mm  |                |                |                |                | Tools                           | <br>1000 pcs<br>~ kg | <br>pcs |
|------------------------------|--|------------|----------------|----------------|----------------|----------------|----------------|---------------------------------|----------------------|---------|
|                              |  |            | d <sub>1</sub> | d <sub>3</sub> | l <sub>1</sub> | l <sub>2</sub> | s <sub>1</sub> |                                 |                      |         |
| <b>0.14</b>                  | 166/GR   | grey       | 0.7            | 2.3            | 10.4           | 6              | 0.12           | Chart<br>Page<br>6.09 –<br>6.10 | 0.035                | 1000    |
|                              | 166/GRL  |            |                |                | 12.4           | 8              | 0.040          |                                 |                      |         |
| <b>0.25</b>                  | 167/H  | light blue | 0.8            | 2.3            | 10.4           | 6              | 0.15           |                                 | 0.045                | 1000    |
|                              | 167/HL   |            |                |                | 12.4           | 8              | 0.050          |                                 |                      |         |
| <b>0.34</b>                  | 168/T  | turquoise  | 0.8            | 2.5            | 10.4           | 6              | 0.15           |                                 | 0.045                | 1000    |
|                              | 168/TL   |            |                |                | 12.4           | 8              | 0.050          |                                 |                      |         |
| <b>0.5</b>                   | 169/OK<br>169/O<br>169/OH                      | orange     | 1              | 3              | 12             | 6              | 0.15           |                                 | 0.070                | 1000    |
|                              |  |            |                |                | 14             | 8              | 0.070          |                                 |                      |         |
|                              |  |            |                |                | 16             | 10             | 0.085          |                                 |                      |         |
| <b>0.75</b>                  | 170/WK<br>170/W<br>170/WH<br>170/WL            | white      | 1.2            | 3.2            | 12.4           | 6              | 0.15           |                                 | 0.080                | 1000    |
|                              |  |            |                |                | 14.6           | 8              | 0.080          |                                 |                      |         |
|                              |  |            |                |                | 16.4           | 10             | 0.100          |                                 |                      |         |
|                              |  |            |                |                | 18.4           | 12             | 0.105          |                                 |                      |         |
| <b>1</b>                     | 171/GK<br>171/G<br>171/GH<br>171/GL            | yellow     | 1.4            | 3.5            | 12.4           | 6              | 0.15           | 0.090                           | 1000                 |         |
|                              |  |            |                |                | 14.6           | 8              | 0.100          |                                 |                      |         |
|                              |  |            |                |                | 16.4           | 10             | 0.120          |                                 |                      |         |
|                              |  |            |                |                | 18.4           | 12             | 0.125          |                                 |                      |         |
| <b>1.5</b>                   | 172/RK<br>172/RO<br>172/RH<br>172/RM<br>172/RL | red        | 1.7            | 4              | 12             | 6              | 0.15           | 0.105                           | 1000                 |         |
|                              |  |            |                |                | 14.6           | 8              | 0.110          |                                 |                      |         |
|                              |  |            |                |                | 16.4           | 10             | 0.130          |                                 |                      |         |
|                              |  |            |                |                | 18.4           | 12             | 0.140          |                                 |                      |         |
|                              |  |            |                |                | 24.4           | 18             | 0.190          |                                 |                      |         |
| <b>2.5</b>                   | 173/B<br>173/BH<br>173/BL                      | blue       | 2.3            | 4.9            | 15.2           | 8              | 0.15           | 0.150                           | 1000                 |         |
|                              |  |            |                |                | 19             | 12             | 0.200          |                                 |                      |         |
|                              |  |            |                |                | 25             | 18             | 0.250          |                                 |                      |         |
| <b>4</b>                     | 174/GR<br>174/GRH<br>174/GRL                   | grey       | 2.9            | 5.5            | 16.5           | 10             | 0.15           | 0.210                           | 1000                 |         |
|                              |  |            |                |                | 19.5           | 12             | 0.250          |                                 |                      |         |
|                              |  |            |                |                | 25.5           | 18             | 0.320          |                                 |                      |         |
| <b>6</b>                     | 175/S<br>175/SL                                | black      | 3.5            | 6.3            | 20             | 12             | 0.2            | 0.350                           | 100                  |         |
|                              |  |            |                |                | 26             | 18             | 0.460          |                                 |                      |         |
| <b>10</b>                    | 176/E<br>176/EL                                | ivory      | 4.5            | 8              | 21.5           | 12             | 0.2            | 0.450                           | 100                  |         |
|                              |  |            |                |                | 27.5           | 18             | 0.650          |                                 |                      |         |
| <b>16</b>                    | 177/GR<br>177/GRL                              | green      | 5.8            | 9.6            | 22.2           | 12             | 0.2            | 0.650                           | 100                  |         |
|                              |  |            |                |                | 28.2           | 18             | 0.800          |                                 |                      |         |
| <b>25</b>                    | 178/BR<br>178/BRL                              | brown      | 7.3            | 12.1           | 29             | 16             | 0.2            | 1.600                           | 50                   |         |
|                              |  |            |                |                | 35             | 22             | 2.000          |                                 |                      |         |
| <b>35</b>                    | 179/B<br>179/BL                                | beige      | 8.3            | 13.6           | 30             | 16             | 0.2            | 1.900                           | 50                   |         |
|                              |  |            |                |                | 39             | 25             | 2.500          |                                 |                      |         |
| <b>50</b>                    | 180/O<br>180/OL                                | olive      | 10.3           | 16.4           | 36.4           | 20             | 0.35           | 3.300                           | 50                   |         |
|                              |  |            |                |                | 41.4           | 25             | 4.000          |                                 |                      |         |

