

0806518  
<https://www.phoenixcontact.com/gb/products/0806518>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Engraving plate, Plate, white, unlabeled, can be labeled with: P1 ENGRAVING UNIT, ENGRAVING UNIT, mounting type: adhesive, Number of individual labels: 1, text field height: 610 mm, text field width: 610 mm



Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 0806518       |
| Packing unit                         | 10 pc         |
| Minimum order quantity               | 10 pc         |
| Sales key                            | BG2415        |
| Product key                          | BG2415        |
| GTIN                                 | 4017918138592 |
| Weight per piece (including packing) | 666 g         |
| Weight per piece (excluding packing) | 652 g         |
| Customs tariff number                | 39203000      |
| Country of origin                    | DE            |

# GPK/SK 610X610X1,5 WH/BK - Engraving plate



0806518

<https://www.phoenixcontact.com/gb/products/0806518>

## Technical data

### Product properties

|                             |                |
|-----------------------------|----------------|
| Product type                | Device marking |
| Marking                     |                |
| Number of individual labels | 1              |

### Mounting

|               |          |
|---------------|----------|
| Mounting type | adhesive |
|---------------|----------|

### Material specifications

|                   |                  |
|-------------------|------------------|
| Adhesive strength | 50 µm            |
| Adhesive          | Acrylic          |
| Color             | white (RAL 9010) |
| Material          | TRANSPLY-ABS     |

### Environmental and real-life conditions

|               |                                |
|---------------|--------------------------------|
| UV resistance |                                |
| Specification | ISO 4892-2:2013-03 (following) |

|                                 |                                     |
|---------------------------------|-------------------------------------|
| Wipe resistance of inscriptions |                                     |
| Specification                   | DIN EN 61010-1 (VDE 0411-1):2011-07 |

|                                                     |                                                                                 |
|-----------------------------------------------------|---------------------------------------------------------------------------------|
| Ambient conditions                                  |                                                                                 |
| Ambient temperature (operation)                     | -20 °C ... 85 °C                                                                |
| Recommended storage conditions                      | 20°C/50% relative humidity. Storage in the original packaging is recommended.   |
| Recommended ambient temperature (storage/transport) | 20 °C                                                                           |
| Recommended humidity (storage/transport)            | 50 % (Storage in a dry and dark place in the original packaging is recommended) |
| Shelf life                                          | 12 months                                                                       |

### Dimensions

|                   |         |
|-------------------|---------|
| Width             | 610 mm  |
| Height            | 0.8 mm  |
| Length            | 610 mm  |
| Material strength | 1.50 mm |

|                   |        |
|-------------------|--------|
| Text field        |        |
| Text field width  | 610 mm |
| Text field height | 610 mm |

# GPK/SK 610X610X1,5 WH/BK - Engraving plate



0806518

<https://www.phoenixcontact.com/gb/products/0806518>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27281103 |
|-------------|----------|

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001288 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131500 |
|-------------|----------|

# GPK/SK 610X610X1,5 WH/BK - Engraving plate



0806518

<https://www.phoenixcontact.com/gb/products/0806518>

## Environmental product compliance

### EU RoHS

|                                         |                    |
|-----------------------------------------|--------------------|
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
|-----------------------------------------|--------------------|

### EU REACH SVHC

|                                     |                            |
|-------------------------------------|----------------------------|
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |
|-------------------------------------|----------------------------|

Phoenix Contact 2025 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)