

## Features

- Standard Oilite® bearings are impregnated with highly refined mineral oil to ISO VG (SAE 30) having a high viscosity index and containing anti-oxidant, anti-rust and defoamant additives.
- Standard Oilite® oil retaining tin bronze is the generally specified material. It gives a good balance between strength, wear resistance, conformability, and durability in operation. Ideal in a wide variety of applications where self-lubricating properties are required over a long period of time.

## RS PRO Oilite® Flanged Bearing

RS Stock No.: 0594740




RS PRO is the own brand of RS. The RS PRO Seal of Approval is your assurance of professional quality, a guarantee that every part is rigorously tested, inspected, and audited against demanding standards. Making RS PRO the Smart Choice for our customers.

RS PRO is offering range of Oilite® plain bearings - self-lubricating bearings that are made from metal alloys with pores that channel lubricants between the bearing itself and the shaft.

- Standard Oilite® bearings are impregnated with highly refined mineral oil to ISO VG (SAE 30) having a high viscosity index and containing anti-oxidant, anti-rust and defoamant additives.
- Lubricant : Shell Tellus S2 MX68
- Temperature range of -15°C to +75°C.
- Standard Oilite® oil retaining tin bronze is the generally specified material. It gives a good balance between strength, wear resistance, conformability, and durability in operation. Ideal in a wide variety of applications where self-lubricating properties are required over a long period of time.
- All dimensions and tolerances of our metric ranges conform to ISO 2795:1991
- Wide range of metric and imperial sizes
- Wide range of different types: Plain, Flanged

\* Below dimensions in mm



## Specifications

### Details

Inner Diameter	50	Outer Diameter	60	Length	50
Tolerance Range	UK Standard	Flange Thickness	5	Flange Diameter	70

### Material Specification

Structure	Oil impregnated sintered bronze*			
Max PV (N/mm <sup>2</sup> x m/s)	1.8	Max Static load (N/mm <sup>2</sup> )	50	
Max Dynamic load (N/mm <sup>2</sup> )	14	Max Sliding speed (m/s)	5	
Operating temperature (°C)	-60 to 200*	Density (g/cm <sup>3</sup> )	6.6	
	*dependant on lubrication			
Radial crushing strength (K Min M/mm <sup>2</sup> )	160			

### Tolerances & Fittings (Metric)

	Min	Max	Tolerance
Inside Diameter	50.009	50.048	G8
Outside Diameter	60.053	60.099	s8
Overall Length	49.805	50.195	js13
Flange Thickness Tolerance	4.910	5.090	js13
Flange Diameter Tolerance	69.770	70.230	js13
Recommended Housing Size	60.000	60.030	H7
Shaft Diameter	49.950	49.975	f7
Fitting Pin Size	50.009	50.020	m5
Concentricity Max	0.120	0.120	IT10
Inside Diameter When Fitted	50.000	50.025	H7