



### Water and oil repellent meta-aramid braided sleeving

#### Helagaine HEGMANWO

Helagaine HEGMANWO is especially resistant to water and oil and is designed for applications requiring mechanical protection at high temperatures, particularly in the aerospace, military, railway and ship-building industries.

#### Features and Benefits

- Made of non-flammable meta-aramid
- Water and oil-repellent
- Extremely flexible
- High expansion for easy installation over long lengths
- Optimal mechanical protection for harnesses
- Able to withstand the most severe environments
- Superior protection against abrasion, flames and high temperatures
- Highly resistant to radiation and fluids



Helagaine HEGMAN and HEGMANWO are available in various sizes.

<b>MATERIAL</b>	Polyaramid Polymetaphenylene Isophthalamide (NOMEX)
<b>Operating Temperature</b>	-60 °C to +240 °C
<b>Melting Point</b>	Does not melt / Carbonisation above +370 °C
<b>Flammability</b>	UL94 V0 (Raw material), UL224 VW-1
<b>Specifications</b>	DIN EN 6049

RoHS

TYPE	Bundle Ø min.	Bundle Ø max.	Colour	Reel Length	Article-No.
HEGMANWO-02	1.0	2.0	Green (GN)	100 m	170-02000
HEGMANWO-04	2.0	4.0	Green (GN)	100 m	170-02001
HEGMANWO-06	4.0	8.0	Green (GN)	100 m	170-02002
HEGMANWO-08	6.0	12.0	Green (GN)	50 m	170-02003
HEGMANWO-10	8.0	16.0	Green (GN)	50 m	170-02004
HEGMANWO-15	10.0	20.0	Green (GN)	50 m	170-02005
HEGMANWO-20	12.0	24.0	Green (GN)	50 m	170-02006
HEGMANWO-25	15.0	30.0	Green (GN)	50 m	170-02007
HEGMANWO-30	20.0	40.0	Green (GN)	50 m	170-02008

All dimensions in mm. Subject to technical changes.

Cuts in any lengths. NOMEX® is a registered trademark of DuPont. Minimum Order Quantity (MOQ) may differ from package content.



For product specific approvals and specifications please refer to the Appendix.